



March 29, 2016

William Durham, Director
Division of Air Quality
West Virginia Department of
Environmental Protection
601 – 57th Street, SE
Charleston, WV 25304

Re: Permit No. R13-1364G
Plant ID No. 033-00034
Aurora Flight Sciences of WV, Inc.

Dear Mr. Durham:

The purpose of this correspondence is to comply with section 4.1.3 of the above referenced permit and inform the WVDEP-DAQ that Aurora is adding two new surface coatings to our paint inventory. The two new surface coatings which are being added are “Temperkote No. 888 Primer” and Temperkote No. 888” manufactured by Flame Control Coatings LLC, both of which contain “Manganese Ferrite Black Spinel”, CAS# 068186-91-4, which is a member of the HAP Category “Manganese Compounds”, which is not currently listed in section 4.1.3 of Aurora’s permit.

Aurora estimates that the usage of this primer and paint will range from 5 to 10 gallons each, per year which will yield the following potential HAP discharge:

Temperkote No. 888 Primer

10 gallon per year X 11.25 lbs. (product weight) X .05 (5% maximum ingredient weight of Manganese Ferrite Black Spinel as listed on the MSDS) = 5.625 lbs./yr.

Temperkote No. 888

10 gallon per year X 10.01 lbs. (product weight) X .05 (5% maximum ingredient weight of Manganese Ferrite Black Spinel as listed on the MSDS) = 5.01 lbs./yr.

Annual combined potential emissions of Manganese Compounds (Manganese Ferrite Black Spinel)

5.625 lbs./yr. (Temperkote No. 888 Primer) + 5.01 lbs./yr. (Temperkote No. 888) =
10.635 lbs./yr. Potential Manganese Compounds Emissions

Aurora Flight Sciences Corporation

www.aurora.aero

9950 Wakeman Drive
Manassas, VA 20110-2702
703-369-3633 • Fax 703-369-4514

3000 East Benedum Industrial Drive
Bridgeport, WV 26330-9683
304-842-8100 • Fax 304-842-8116


One Broadway, 12th Floor
Cambridge, MA 02142-1100
617-500-4800 • Fax 617-500-4810

200 Aurora Way
Columbus, MS 39701
662-328-8227 • Fax 662-328-8971

John Benedict, Director
August 25, 2005
Page 2 of 2

Aurora has attached a copy of the MSDSs for the new "Temperkote No. 888 Primer and the Temperkote No. 888 as required. If addition information is needed, please contact me at (304) 848-5564.

Sincerely,



Dennis Klingensmith
EH&S Manager

enclosures

MATERIAL SAFETY DATA SHEET

No. 888-PR-LG, PRIMER LIGHT GRAY

Page 1 of 5

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MANUFACTURER'S NAME / ADDRESS

FLAME CONTROL COATINGS LLC
4120 HYDE PARK BLVD.
NIAGARA FALLS, N.Y. 14305

TRADE NAME: TEMPERKOTE No. 888 PRIMER
COLOR: LIGHT GRAY
MAIN USE: INDUSTRIAL HI-HEAT® PRIMER

EMERGENCY TELEPHONE NUMBER: 800-535-5053

ISSUE DATE: SEPTEMBER 25, 2008

REVISION DATE: MARCH 20, 2015

PREPARED BY: A. MAHMOOD

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS

	Wt. %	CAS Number
XYLENE-MIXED ORTHO, META AND PARA ISOMERS	10-30	001330-20-7
ETHYLBENZENE	0.1-1.0	000100-41-4
TALC	10-30	014807-96-6
TITANIUM DIOXIDE	5-10	013463-67-7
MANGANESE FERRITE BLACK SPINEL**	1-5	068186-91-4
TERT-BUTYL ACETATE	5-10	000540-88-5
AROMATIC PETROLEUM DISTILLATES	5-10	064742-95-6
METHYL PROPYL KETONE	5-10	000107-87-9
MICA	1-5	012001-26-2
CARBON BLACK	0.1-1.0	001333-86-4
COBALT 2-ETHYLHEXANOATE	0.1-1.0	000136-52-7
ZIRCONIUM 2-ETHYLHEXANOATE	0.1-1.0	022464-99-9

** This product is the result of high temperature calcinations of the component substances. Due to its unique crystalline structure the properties of this finished pigment do not necessarily reflect the properties of the component metals or oxides.

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: DANGER!
HARMFUL OR FATAL IF SWALLOWED
HARMFUL IF INHALED
CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION
CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING
ORGANS: BLOOD, KIDNEYS, LIVER, GASTROINTESTINAL TRACT,
RESPIRATORY TRACT, SKIN, NERVOUS SYSTEM, EYE, LENSE OR CORNEA
FLAMMABLE LIQUID AND VAPOR
VAPOR MAY CAUSE FLASH FIRE
MAY BE HARMFUL IF ABSORBED THROUGH SKIN
POSSIBLE CANCER HAZARD
CONTAINS MATERIAL WHICH CAN CAUSE CANCER

PRIMARY ROUTES OF ENTRY: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

HEALTH HAZARDS (ACUTE AND CHRONIC EXPOSURES)

EYES:

ACUTE – LIQUID, AEROSOLS OR VAPORS ARE SEVERELY IRRITATING AND CAN CAUSE PAIN, TEARING, REDDENING AND SWELLING. IF LEFT UNTREATED, CORNEAL DAMAGE CAN OCCUR AND INJURY IS SLOW TO HEAL. HOWEVER, DAMAGE IS USUALLY REVERSIBLE

CHRONIC – PROLONGED VAPOR CONTACT MAY CAUSE CONJUNCTIVITIS

SKIN CONTACT:

ACUTE – REPEATED OR PROLONGED SKIN CONTACT CAN RESULT IN DRY, DEFATTED AND CRACKED SKIN CAUSING INCREASED SUSCEPTIBILITY TO INFECTION. IN ADDITION IRRITATION MAY DEVELOP INTO DERMATITIS. SOLVENTS CAN PENETRATE THE SKIN AND MAY CAUSE EFFECTS SIMILAR TO THOSE IDENTIFIED UNDER ACUTE INHALATION SYMPTOMS.

CHRONIC – MAY CAUSE EFFECTS SIMILAR TO THOSE IDENTIFIED UNDER CHRONIC INHALATION EFFECTS.

MATERIAL SAFETY DATA SHEET

No. 888-PR-LG, PRIMER LIGHT GRAY

Page 2 of 5

SECTION 3: HAZARDS IDENTIFICATION (CON'T)

SKIN ABSORPTION:

ACUTE - ND

CHRONIC - ND

INHALATION:

ACUTE - SOLVENT VAPORS ARE IRRITATING TO THE EYES, NOSE, AND THROAT. SYMPTOMS OF IRRITATION MAY INCLUDE RED, ITCHY EYES, DRYNESS OF THE THROAT AND A FEELING OF TIGHTNESS IN THE CHEST. OTHER POSSIBLE SYMPTOMS OF OVEREXPOSURE INCLUDE: HEADACHE, DIZZINESS, NAUSEA, NARCOSIS FATIGUE AND LOSS OF APPETITE. PERSONS EXPOSED TO 200 PPM OF XYLENE EXPERIENCED EYE, NOSE AND THROAT IRRITATION. CONCENTRATIONS OF 10,000 PPM OF XYLENE CAN BE IMMEDIATELY DANGEROUS TO LIFE AND HEALTH

CHRONIC - CHRONIC EXPOSURE TO ORGANIC SOLVENTS HAS BEEN ASSOCIATED WITH VARIOUS NEUROTOXIC EFFECTS INCLUDING PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. SYMPTOMS INCLUDE LOSS OF MEMORY, LOSS OF INTELLECTUAL ABILITY AND LOSS OF COORDINATION.

INGESTION:

ACUTE - CAN RESULT IN IRRITATION OF THE DIGESTIVE TRACT. SYMPTOMS CAN INCLUDE SORE THROAT ABDOMINAL PAIN NAUSEA, VOMITING AND DIARRHEA. VOMITING MAY CAUSE ASPIRATION OF SOLVENT RESULTING IN CHEMICAL PNEUMONITIS

CHRONIC - ND

CONDITIONS AGGRAVATED BY EXPOSURE: SKIN DISORDERS AND ALLERGIES.

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

INGESTION: GIVE 3 - 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. DO NOT INDUCE VOMITING! OBTAIN MEDICAL CARE AND TREATMENT.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: 4.4°C (40°F) TCC (TBAC)

CONDITIONS OF FLAMMABILITY: NA

FLAMMABLE LIMITS: LEL: 1.26% UEL: 6.88%

AUTO IGNITION TEMP.: ND

OSHA CLASS: FLAMMABLE LIQUID, PACKING GROUP III

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂, ALDEHYDES, ACIDS

SENSITIVITY TO IMPACT: ND

SENSITIVITY TO STATIC DISCHARGE: ND

EXTINGUISHING MEDIA: IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, OR ALCOHOL FOAM.

SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. WATER SPRAY IS USEFUL IN COOLING FIRE-EXPOSED VESSELS AND IN DISPERSING VAPORS.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT. SOLVENT VAPORS MAY BE HEAVIER THAN AIR. UNDER CONDITIONS OF STAGNANT AIR, VAPORS MAY BUILD UP AND TRAVEL ALONG THE GROUND TO AN IGNITION SOURCE.

MATERIAL SAFETY DATA SHEET

No. 888-PR-LG, PRIMER LIGHT GRAY

Page 3 of 5

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

SECTION 7: HANDLING AND STORAGE

GENERAL: STORE IN COOL, WELL VENTILATED AREAS. KEEP AWAY FROM HEAT AND OPEN FLAMES. AVOID PROLONGED INHALATION OF HEATED VAPORS OR MISTS. AVOID PROLONGED SKIN CONTACT. USE NON-SPARKING TOOLS AND GROUNDING CABLES WHEN TRANSFERRING. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY.

STORAGE: AVOID TEMPERATURE EXTREMES. STORE AWAY FROM EXCESSIVE HEAT, FROM SOURCES OF IGNITION AND FROM REACTIVE MATERIALS. MATERIAL CAN BURN; LIMIT INDOOR STORAGE TO AREAS EQUIPPED WITH AUTOMATIC SPRINKLERS. STORE OUT OF DIRECT SUNLIGHT IN A COOL PLACE. KEEP CONTAINERS TIGHTLY CLOSED. GROUND ALL METAL CONTAINERS DURING STORAGE AND HANDLING.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

EXPOSURE LIMITS (ppm)

INGREDIENTS (CAS)	OSHA		ACGIH		OTHER
	TWA	STEL	TWA	STEL	
001330-20-7	100	150	100	150	
000100-41-4	100	125	100	125	
014807-96-6	10mg/m ³	ND	10mg/m ³	ND	(SEE NOTE 1)
013463-67-7	10mg/m ³	ND	10mg/m ³	ND	(SEE NOTE 1)
068186-91-4*	NE	NE	NE	NE	
*manganese compounds (as Mn)	1mg/m ³	3mg/m ³	0.2mg/m ³	ND	(SEE NOTE 1, 2)
000540-88-5	200	ND	200	ND	
000107-87-9	200	250	200	250	
064742-95-6	NE	NE	NE	NE	
012001-26-2	3mg/m ³	ND	3mg/m ³	ND	(SEE NOTE 1)
001333-86-4	3.5mg/m ³	ND	3.5mg/m ³	ND	(SEE NOTE 1)
000136-52-7	0.1mg/m ³	ND	0.02mg/m ³	ND	(SEE NOTE 1)
022464-99-9	5mg/m ³	ND	10mg/m ³	ND	(SEE NOTE 1)

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK

NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

NOTE 2: HAZARDOUS COMPONENTS OF PIGMENT SEE ** SECTION 2 FOR DETAILS.

ENGINEERING CONTROLS: EXHAUST VENTILATION IS SUFFICIENT TO KEEP AIRBORNE CONCENTRATION OF THE SOLVENTS BELOW THEIR RESPECTIVE TLV'S. EXHAUST AIR MAY NEED TO BE CLEANED BY SCRUBBERS OR FILTERS TO REDUCE ENVIRONMENTAL CONTAMINATION.

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >98°C (>208°F)

SPECIFIC GRAVITY: 1.25-1.35

VAPOR PRESSURE: 34 mmHg @25°C (77°F)

MELTING POINT: ND

VAPOR DENSITY: ND
(AIR = 1)

EVAPORATION RATE: >1
(BUTYL ACETATE = 1)

MATERIAL SAFETY DATA SHEET

No. 888-PR-LG, PRIMER LIGHT GRAY

Page 4 of 5

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (CON'T)

SOLUBILITY IN WATER: INSOLUBLE **pH:** NA
COEFFICIENT of WATER/OIL DISTRIBUTION: ND **ODOR THRESHOLD:** ND
APPEARANCE AND ODOR: PIGMENTED LIQUID, AROMATIC SOLVENT ODOR
% VOLATILES BY VOLUME: 52% **%SOLIDS BY WEIGHT:** 65%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE; HOWEVER MAY FORM PEROXIDES OF UNKNOWN STABILITY
CONDITIONS TO AVOID: NOT APPLICABLE (MATERIAL IS STABLE).
INCOMPATIBILITY (MATERIAL TO AVOID): OXIDIZING AGENTS (PERCHLORATES, NITRATES), STRONG ACIDS, HYPOCHLORITES, AND PEROXIDES SHOULD NOT BE COMBINED WITH PHOSPHOROUS CONTAINING MATERIALS BECAUSE HIGHLY TOXIC FUMES CAN BE EMITTED IN A FIRE SITUATION.
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂
HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

CARCINOGENIC DATA: THIS PRODUCT CONTAINS XYLENE, ETHYL BENZENE IN CONCENTRATIONS OF 0.1% OR GREATER.
TERATOGENICITY: YES **MUTAGENICITY:** ND
EMBRYOTOXICITY: ND **SYNERGISTIC MATERIAL:** ND
OVEREXPOSURE EFFECTS: LACRIMATION OF EYES, SKIN IRRITATION, DIZZINESS.
IRRITANCY: YES
SENSITIZER: YES
ACUTE TOXICITY EFFECTS: ORAL LD₅₀: 11.4g/kg (Rats); DERMAL LD₅₀: >20ml/kg (Rabbit); INHALATION: ND

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: NOT READILY BIODEGRADABLE.
ECOTOXICITY: ECO Daphnia Magna: 1-10 mg/l; Bacteria: >100 mg/l

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: INCINERATION IS PREFERRED. COMPLY WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. RCRA CLASSIFIED HAZARDOUS WASTE WITH CHARACTERISTIC OF IGNITABILITY.

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME: PAINT **UN NUMBER:** UN1263
PACKAGING GROUP: III **DOT PRODUCT RQ LBS (KGS):** 800 LBS. (362.9 KGS)
HAZARD LABEL: FLAMMABLE LIQUID **HAZARD PLACARD:** FLAMMABLE LIQUID
IMO SHIPPING DATA: PAINT, HAZARD CLASS 3, UN1263, PACKING GROUP III, FLAMMABLE LIQUID
ICAO/IATA SHIPPING DATA: PAINT, HAZARD CLASS 3, UN1263, PACKING GROUP III, FLAMMABLE LIQUID
PASSENGER AIR MAX QUANTITY: 60L **PASSENGER PACKING INSTRUCTION:** 355
CARGO AIR- MAX QAUNTITY.: 220L **CARGO AIR INSTRUCTION NUMBER:** 366

SECTION 15: REGULATORY INFORMATION

MATERIAL VOC = 370 gram / liter **COATING VOC =** 416 gram/liter
TSCA (TOXIC SUBSTANCE CONTROL ACT): ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

MATERIAL SAFETY DATA SHEET

No. 888-PR-LG, PRIMER LIGHT GRAY

Page 5 of 5

SECTION 15: REGULATORY INFORMATION (CON'T)

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT): REPORTABLE QUANTITY, XYLENE 100 LBS.

SARA TITLE III

SECTION 312 HAZARD CLASS: IMMEDIATE (ACUTE) HEALTH HAZARD, DELAYED HEALTH HAZARD; FIRE HAZARD.

SECTION 313 LISTED INGREDIENTS: XYLENE (CAS #001330-20-7), ETHYL BENZENE (CAS #000100-41-4), MANGANESE COMPOUNDS

CALIFORNIA PROPOSITION 65: The below list of compounds is known to the State of California to cause cancer, birth defects or other reproductive harm: CAS #001330-20-7, CAS #000100-41-4, and CAS #001333-86-4.

SECTION 16: OTHER INFORMATION

HAZARD RATING

HMIS: HEALTH 2 FLAMMABILITY 3 REACTIVITY 0

LEGEND

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
STEL: SHORT TERM EXPOSURE LIMIT
TWA: TIME WEIGHTED AVERAGE
PEL: PERMISSABLE EXPOSURE LIMIT
TLV: THRESHOLD LIMIT VALUE
NA: NOT APPLICABLE
NE: NOT ESTABLISHED
ND: NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.

MATERIAL SAFETY DATA SHEET

No. 888-15 CHARCOAL

Page 1 of 5

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MANUFACTURER'S NAME / ADDRESS

FLAME CONTROL COATINGS LLC
4120 HYDE PARK BLVD.
NIAGARA FALLS, N.Y. 14305

TRADE NAME: TEMPERKOTE No. 888
COLOR: 15 CHARCOAL
MAIN USE: INDUSTRIAL HI-HEAT® COATING

EMERGENCY TELEPHONE NUMBER: 800-535-5053

ISSUE DATE: SEPTEMBER 15, 2008 REVISION DATE: NOVEMBER 2, 2015 PREPARED BY: P. PISARSKI

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>HAZARDOUS INGREDIENTS</u>	<u>Wt. %</u>	<u>CAS Number</u>
XYLENE-MIXED ORTHO, META AND PARA ISOMERS	10-30	001330-20-7
ETHYLBENZENE	0.1-1.0	000100-41-4
TITANIUM DIOXIDE	5-10	013463-67-7
MANGANESE FERRITE BLACK SPINEL**	1-5	068186-94-7
TERT-BUTYL ACETATE	5-10	000540-88-5
AROMATIC PETROLEUM DISTILLATES	5-10	064742-95-6
METHYL PROPYL KETONE	5-10	000107-87-9
PARACHLOROBENZOTRIFLOURIDE	1-5	000098-56-6
MICA	1-5	012001-26-2
CARBON BLACK	0.1-1.0	001333-86-4
COBALT 2-ETHYLHEXANOATE	0.1-1.0	000136-52-7
ZIRCONIUM 2-EHTYLHEXANOATE	0.1-1.0	022464-99-9

** This product is the result of high temperature calcinations of the component substances. Due to its unique crystalline structure the properties of this finished pigment do not necessarily reflect the properties of the component metals or oxides.

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: DANGER!
HARMFUL OR FATAL IF SWALLOWED
HARMFUL IF INHALED
CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION
CONTAINS MATERIAL WHICH CAUSES DAMAGE TO THE FOLLOWING
ORGANS: BLOOD, KIDNEYS, LIVER, GASTROINTESTINAL TRACT,
RESPIRATORY TRACT, SKIN, NERVOUS SYSTEM, EYE, LENSE OR CORNEA
FLAMMABLE LIQUID AND VAPOR
VAPOR MAY CAUSE FLASH FIRE
MAY BE HARMFUL IF ABSORBED THROUGH SKIN
POSSIBLE CANCER HAZARD
CONTAINS MATERIAL WHICH CAN CAUSE CANCER

PRIMARY ROUTES OF ENTRY: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

HEALTH HAZARDS (ACUTE AND CHRONIC EXPOSURES)

EYES:

ACUTE – LIQUID, AEROSOLS OR VAPORS ARE SEVERELY IRRITATING AND CAN CAUSE PAIN, TEARING, REDDENING AND SWELLING. IF LEFT UNTREATED, CORNEAL DAMAGE CAN OCCUR AND INJURY IS SLOW TO HEAL. HOWEVER, DAMAGE IS USUALLY REVERSIBLE

CHRONIC – PROLONGED VAPOR CONTACT MAY CAUSE CONJUNCTIVITIS

SKIN CONTACT:

ACUTE – REPEATED OR PROLONGED SKIN CONTACT CAN RESULT IN DRY, DEFATTED AND CRACKED SKIN CAUSING INCREASED SUSCEPTIBILITY TO INFECTION. IN ADDITION IRRITATION MAY DEVELOP INTO DERMATITUS. SOLVENTS CAN PENETRATE THE SKIN AND MAY CAUSE EFFECTS SIMILAR TO THOSE IDENTIFIED UNDER ACUTE INHALATION SYMPTOMS.

CHRONIC – MAY CAUSE EFFECTS SIMILAR TO THOSE IDENTIFIED UNDER CHRONIC INHALATION EFFECTS.

MATERIAL SAFETY DATA SHEET

No. 888-15 CHARCOAL

Page 2 of 5

SECTION 3: HAZARDS IDENTIFICATION (CON'T)

SKIN ABSORPTION:

ACUTE - ND

CHRONIC - ND

INHALATION:

ACUTE - SOLVENT VAPORS ARE IRRITATING TO THE EYES, NOSE, AND THROAT. SYMPTOMS OF IRRITATION MAY INCLUDE RED, ITCHY EYES, DRYNESS OF THE THROAT AND A FEELING OF TIGHTNESS IN THE CHEST. OTHER POSSIBLE SYMPTOMS OF OVEREXPOSURE INCLUDE: HEADACHE, DIZZINESS, NAUSEA, NARCOSIS FATIGUE AND LOSS OF APPETITE. PERSONS EXPOSED TO 200 PPM OF XYLENE EXPERIENCED EYE, NOSE AND THROAT IRRITATION. CONCENTRATIONS OF 10,000 PPM OF XYLENE CAN BE IMMEDIATELY DANGEROUS TO LIFE AND HEALTH

CHRONIC - CHRONIC EXPOSURE TO ORGANIC SOLVENTS HAS BEEN ASSOCIATED WITH VARIOUS NEUROTOXIC EFFECTS INCLUDING PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. SYMPTOMS INCLUDE LOSS OF MEMORY, LOSS OF INTELLECTUAL ABILITY AND LOSS OF COORDINATION.

INGESTION:

ACUTE - CAN RESULT IN IRRITATION OF THE DIGESTIVE TRACT. SYMPTOMS CAN INCLUDE SORE THROAT ABDOMINAL PAIN NAUSEA, VOMITING AND DIARRHEA. VOMITING MAY CAUSE ASPIRATION OF SOLVENT RESULTING IN CHEMICAL PNEUMONITIS

CHRONIC - ND

CONDITIONS AGGRAVATED BY EXPOSURE: SKIN DISORDERS AND ALLERGIES.

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

INGESTION: GIVE 3 - 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. DO NOT INDUCE VOMITING! OBTAIN MEDICAL CARE AND TREATMENT.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: 4.4°C (40°F) TCC (TBAC)

CONDITIONS OF FLAMMABILITY: NA

FLAMMABLE LIMITS: LEL: 1.26% UEL: 6.88%

AUTO IGNITION TEMP.: ND

OSHA CLASS: FLAMMABLE LIQUID, PACKING GROUP II

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂, ALDEHYDES, ACIDS

SENSITIVITY TO IMPACT: ND

SENSITIVITY TO STATIC DISCHARGE: ND

EXTINGUISHING MEDIA: IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, OR ALCOHOL FOAM.

SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. WATER SPRAY IS USEFUL IN COOLING FIRE-EXPOSED VESSELS AND IN DISPERSING VAPORS.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT. SOLVENT VAPORS MAY BE HEAVIER THAN AIR. UNDER CONDITIONS OF STAGNANT AIR, VAPORS MAY BUILD UP AND TRAVEL ALONG THE GROUND TO AN IGNITION SOURCE.

MATERIAL SAFETY DATA SHEET

No. 888-15 CHARCOAL

Page 3 of 5

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

SECTION 7: HANDLING AND STORAGE

GENERAL: STORE IN COOL, WELL VENTILATED AREAS. KEEP AWAY FROM HEAT AND OPEN FLAMES. AVOID PROLONGED INHALATION OF HEATED VAPORS OR MISTS. AVOID PROLONGED SKIN CONTACT. USE NON-SPARKING TOOLS AND GROUNDING CABLES WHEN TRANSFERRING. CONTAINERS MAY BE HAZARDOUS WHEN EMPTY.

STORAGE: AVOID TEMPERATURE EXTREMES. STORE AWAY FROM EXCESSIVE HEAT, FROM SOURCES OF IGNITION AND FROM REACTIVE MATERIALS. MATERIAL CAN BURN; LIMIT INDOOR STORAGE TO AREAS EQUIPPED WITH AUTOMATIC SPRINKLERS. STORE OUT OF DIRECT SUNLIGHT IN A COOL PLACE. KEEP CONTAINERS TIGHTLY CLOSED. GROUND ALL METAL CONTAINERS DURING STORAGE AND HANDLING.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

EXPOSURE LIMITS (ppm)

INGREDIENTS (CAS)	OSHA		ACGIH		OTHER
	TWA	STEL	TWA	STEL	
001330-20-7	100	150	100	150	
000100-41-4	100	125	100	125	
013463-67-7	10mg/m ³	ND	10mg/m ³	ND	(SEE NOTE 1)
068186-94-7*	NE	NE	NE	NE	
*manganese compounds (as Mn)	1mg/m ³	3mg/m ³	0.2mg/m ³	ND	(SEE NOTE 1, 2)
000540-88-5	200	ND	200	ND	
000107-87-9	200	250	200	250	
064742-95-6	NE	NE	NE	NE	
000098-56-6	NE	NE	NE	NE	
012001-26-2	3mg/m ³	ND	3mg/m ³	ND	(SEE NOTE 1)
001333-86-4	3.5mg/m ³	ND	3.5mg/m ³	ND	(SEE NOTE 1)
000136-52-7	0.1mg/m ³	ND	0.02mg/m ³	ND	(SEE NOTE 1)
022464-99-9	5mg/m ³	ND	10mg/m ³	ND	(SEE NOTE 1)

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK
NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.
NOTE 2: HAZARDOUS COMPONENTS OF PIGMENT, SEE ** SECTION 2 FOR DETAILS.

ENGINEERING CONTROLS: EXHAUST VENTILATION IS SUFFICIENT TO KEEP AIRBORNE CONCENTRATION OF THE SOLVENTS BELOW THEIR RESPECTIVE TLV'S. EXHAUST AIR MAY NEED TO BE CLEANED BY SCRUBBERS OR FILTERS TO REDUCE ENVIRONMENTAL CONTAMINATION.

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >98°C (>208°F)

SPECIFIC GRAVITY: 1.1-1.2

VAPOR PRESSURE: 34 mmHg @25°C (77°F)

MELTING POINT: ND

MATERIAL SAFETY DATA SHEET

No. 888-15 CHARCOAL

Page 4 of 5

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (CON'T)

VAPOR DENSITY: ND
(AIR = 1) EVAPORATION RATE: >1
(BUTYL ACETATE = 1)

SOLUBILITY IN WATER: INSOLUBLE pH: NA

COEFFICIENT of WATER/OIL DISTRIBUTION: ND ODOR THRESHOLD: ND

APPEARANCE AND ODOR: PIGMENTED LIQUID, AROMATIC SOLVENT ODOR

% VOLATILES BY VOLUME: 51% %SOLIDS BY WEIGHT: 61%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE; HOWEVER MAY FORM PEROXIDES OF UNKNOWN STABILITY

CONDITIONS TO AVOID: NOT APPLICABLE (MATERIAL IS STABLE).

INCOMPATIBILITY (MATERIAL TO AVOID): OXIDIZING AGENTS (PERCHLORATES, NITRATES), STRONG ACIDS, HYPOCHLORITES, AND PEROXIDES SHOULD NOT BE COMBINED WITH PHOSPHOROUS CONTAINING MATERIALS BECAUSE HIGHLY TOXIC FUMES CAN BE EMITTED IN A FIRE SITUATION.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR.

SECTION 11: TOXICOLOGICAL INFORMATION

CARCINOGENIC DATA: THIS PRODUCT CONTAINS XYLENE, ETHYL BENZENE IN CONCENTRATIONS OF 0.1% OR GREATER.

TERATOGENICITY: YES MUTAGENICITY: ND
EMBRYOTOXICITY: ND SYNERGISTIC MATERIAL: ND

OVEREXPOSURE EFFECTS: LACRIMATION OF EYES, SKIN IRRITATION, DIZZINESS.
IRRITANCY: YES
SENSITIZER: YES

ACUTE TOXICITY EFFECTS: ORAL LD₅₀: 11.4g/kg (Rats); DERMAL LD₅₀: >20ml/kg (Rabbit); INHALATION: ND

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: NOT READILY BIODEGRADABLE.

ECOTOXICITY: ECO Daphnia Magna: 1-10 mg/l; Bacteria: >100 mg/l

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: INCINERATION IS PREFERRED. COMPLY WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. RCRA CLASSIFIED HAZARDOUS WASTE WITH CHARACTERISTIC OF IGNITABILITY.

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME: PAINT UN NUMBER: UN1263

PACKAGING GROUP: II DOT PRODUCT RQ LBS (KGS): 800 LBS. (362.9 KGS)

HAZARD LABEL: FLAMMABLE LIQUID HAZARD PLACARD: FLAMMABLE LIQUID

IMO SHIPPING DATA: PAINT, HAZARD CLASS 3, UN1263, PACKING GROUP II, FLAMMABLE LIQUID

ICAO/IATA SHIPPING DATA: PAINT, HAZARD CLASS 3, UN1263, PACKING GROUP II, FLAMMABLE LIQUID

PASSENGER AIR MAX QUANTITY: 5L PASSENGER PACKING INSTRUCTION: 353

CARGO AIR- MAX QAUNTITY.: 60L CARGO AIR INSTRUCTION NUMBER: 364

