



west virginia department of environmental protection

Division of Air Quality
601 57th Street SE
Charleston, WV 25304
Phone (304) 926-0475 • FAX: (304) 926-0479

Ear Ray Tomblin, Governor
Randy C. Huffman, Cabinet Secretary
www.dep.wv.gov

ENGINEERING EVALUATION / FACT SHEET

BACKGROUND INFORMATION

Application No.: G70-A132
Plant ID No.: 017-00038
Applicant: EQT Production Company
Facility Name: OXF-131
Location: Doddridge County
NAICS Code: 211111
Application Type: Modification
Received Date: December 29, 2014
Engineer Assigned: Roy F. Kees, P.E.
Fee Amount: \$500.00
Date Received: January 5, 2015
Complete Date: January 28, 2015
Due Date: March 15, 2015
Applicant Ad Date: December 30, 2015
Newspaper: *The Herald Record*
UTM's: Easting: 517.8 km Northing: 4,337.2 km Zone: 17
Description: Modification to increase condensate throughput, add one uncontrolled tank for produced water and sand, add one thermoelectric generator and register under the G70-A General Permit.

DESCRIPTION OF PROCESS

EQT Production Company (EQT) has submitted a general permit registration application for an existing natural gas production facility permitted under R13-3001, primarily consisting of five (5) natural gas-fired line heaters (S0016 to S0020) varying between 0.77 and 1.54 mmBtu/hr, fifteen (15) 8,820-gallon condensate storage tanks (S001 through S015), an 11.66 mmBtu/hr enclosed vapor combustor (C001), and one (1) 0.013 mmBtu/hr natural gas-fired thermoelectric generator (S0015). Truck loading of condensate will also take place at the site. The facility began operation on May 1, 2012. This modification seeks to add one (1) sand and water separator tank, one (1) thermoelectric generator and to increase condensate throughput.

When in production, raw gas from the wells pass through a separator where the condensate is removed from the gas and sent to one of the storage tanks, and sand, water, and residual solids are displaced and sent to the sand separator tank. Gas passing through the separator will be sent to pipeline for transportation. Working, breathing, and flashing losses from the storage tanks shall be captured and sent to an enclosed vapor combustor for control. The combustor will have a minimum

hydrocarbon destruction efficiency of 95.0%. The line heaters shall be used to keep the lines at the facility from freezing and to promote gas/liquids flow.

From the storage tanks, condensate is loaded into trucks for removal from the site. Emissions from the truck loading are uncontrolled but mitigated by using pipe racks and submerged fill methods. The thermoelectric generators are used to provide small amounts of electricity for switching/monitoring purposes when the facility is unable to generate sufficient solar power.

SITE INSPECTION

On November 28, 2012, the Joe Kessler conducted an inspection of the OXF-131 natural gas production facility. The OXF-131 site is located in a remote and rural area of Doddridge County approximately 7.9 miles southwest of New Milton, WV along a new access road created off of Upper Run Road (CR 23/3). The wells were producing gas and the production facility was in operation at the time of the site inspection. No opacity was visible from any of the units and no noticeable smell was detected. No occupied residences were visible from the site. The following is a picture of the OXF-131 well-pad taken on the day of the inspection:



Directions: [Latitude: 39.18385, Longitude: -80.79390] From the junction of Taylor Drain Rd. (CR 19) and Harmony Road (CR19/6), proceed north on Harmony Road for 0.8 miles and bear right on Upper Run Road (CR 23/3) for 0.7 miles until reaching the EQT access road on the left. Proceed on the access road (bearing right at forks in the road) for 1.6 miles up the hill and along the ridge to the well-pad.

AIR EMISSIONS AND CALCULATION METHODOLOGIES

EQT included in Attachment I of the permit application air emissions calculations for the equipment and processes at the OXF-131 natural gas production facility. The following will

summarize the calculation methodologies used by EQT to calculate the potential-to-emit (PTE) of the proposed facility.

Gas-Fired Line Heaters/Thermoelectric Generator

Criteria Pollutant emissions from the natural gas-fired line heaters (E016 through E020) and the thermoelectric generator (E021) were based on the emission factors provided for natural gas combustion as given in AP-42 (AP-42 is a database of emission factors maintained by USEPA) Section 1.4. Emissions of Greenhouse Gases (GHGs) were based on Tables C-1 and C-2 of 40 CFR 98 - Federal GHG Reporting Rule.

Hourly emissions were based on the maximum design heat input (MDHI) of each unit and annual emissions were based on an annual operation of 8,760 hours. A heat content of the gas of 1,050 Btu/scf was used in the calculations.

Storage Tanks

Emissions from working, breathing & flashing in the tanks were calculated using E&P Tanks 2.0. Input and summary sheets for the program were included in the permit application. As all uncontrolled emissions from the storage tanks are routed to the vapor combustor for control, the controlled emissions from the tanks are based on the vapor combustor's minimum 95% control efficiency. An aggregate annual throughput of 41,573,000 gallons of condensate (increased from 605,000 gallons) was used in the calculations the storage tanks.

Truck Loading

Air emissions from condensate truck loading operations occur as fugitive emissions generated by displacement of vapors when loading trucks. The emission factor used to generate the VOC emissions is based on Equation (1) of AP-42 Section 5.2-4. In this equation, EQT used variables specific to the liquids loaded and to the method of loading - in this case "submerged filling - dedicated normal service." Additionally, worst-case annual emissions were based on a maximum loading rate of 41,573,000 gal/year of condensate. As no maximum hourly pumping rate was provided, hourly emissions were based on 1,000 hours of loading per year.

Fugitives

EQT based their fugitive equipment leak calculations on emission factors taken from the document EPA-453/R-95-017 - "Protocol for Equipment Leak Emission Estimates." Emission factors were taken from Table 2-4 and no control efficiency, as based on a Leak Detection and Repair (LDAR) protocol, was applied. Emissions of Greenhouse Gases (GHGs) were based on Subpart W of 40 CFR 98 - Federal GHG Reporting Rule.

Vapor Combustor

The vapor combustor will receive captured vapors from the storage tanks. The amount of emissions received is determined by the calculation methodologies described above. A 95% control was applied to the uncontrolled VOC/HAP/methane emissions received by the vapor combustor to determine the amount of pass-through emissions of the combustor. The emissions of NO_x, CO, particulate matter, SO₂, and GHGs from the combustion of the vapors were based on emission factors taken from AP-42 Section 1.4 and the maximum design heat input (MDHI) of the unit.

Haul Roads

EQT included in their application an estimate of fugitive emissions created by truck traffic and employee vehicles at the facility. As all the roadways around the building are unpaved, EQT used the equation given in Section 13.2.2 of AP-42 and appropriate variables to estimate potential emissions.

Emissions Summary

Based on the above estimation methodology, which is determined to be appropriate, the PTE of the OXF-131 natural gas production facility is given in the following tables:

Table 2: Facility-Wide Aggregate Hourly (lb/hr) Criteria Pollutant PTE Summary.

Source	CO	NO _x	PM ⁽¹⁾	SO ₂	VOCs	HAPs
Process Heaters/Generators ⁽²⁾	0.71	0.85	0.06	0.01	0.05	0.02
Vapor Combustor ⁽³⁾	0.93	1.11	0.08	0.01	7.18	0.09
Fugitive Emissions	0.00	0.00	0.00	0.00	3.83	0.00
Truck Loading ⁽⁴⁾	0.00	0.00	0.00	0.00	3.28	0.08
Haul Roads ⁽⁴⁾	0.00	0.00	18.04	0.00	0.00	0.00
Facility-Wide Totals →	1.64	1.96	18.18	0.02	14.34	0.19

- (1) Conservatively, all particulate matter emissions are assumed to be less than 2.5 microns. Includes condensables.
- (2) Aggregate emission rate of all such units.
- (3) Includes both pass-through emissions generated by storage tanks and products of combustion.
- (4) As a maximum hourly pump rate was not provided, hourly emissions based on 1,000 hours/year.

Table 3: Facility-Wide Aggregate Annual (ton/yr) Criteria Pollutant/GHG PTE Summary.

Source	CO	NO _x	PM ⁽¹⁾	SO ₂	VOCs	HAPs	CO ₂ e
Process Heaters/Generator ⁽²⁾	3.12	3.71	0.28	0.02	0.20	0.07	4,537.88
Vapor Combustor ⁽³⁾	4.09	4.87	0.37	0.03	31.44	0.38	6,301.95
Fugitive Emissions	0.00	0.00	0.00	0.00	16.79	0.65	598.58
Truck Loading	0.00	0.00	0.00	0.00	1.64	0.04	0.00
Haul Roads	0.00	0.00	9.02	0.00	0.00	0.00	0.00
Facility-Wide Totals →	7.21	8.58	9.67	0.05	50.07	1.14	11,438.41

- (1) Conservatively, all particulate matter emissions are assumed to be less than 2.5 microns. Includes condensables.
- (2) Aggregate emission rate of all such units.
- (3) Includes both pass-through emissions generated by storage tanks and products of combustion.

Table 4: Facility-Wide Aggregate Annual (ton/yr) HAP PTE Summary⁽¹⁾

Source	Hexane	Benzene	Toluene	Ethyl-benzene	Xylene	Formaldehyde	Total HAPs
Process Heaters/Generator ⁽²⁾	~0.00	~0.00	~0.00	~0.00	~0.00	~0.00	0.07
Vapor Combustor ⁽³⁾	0.33	0.02	0.03	~0.00	0.02	0.00	0.40
Fugitive Emissions	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Truck Loading	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Haul Roads	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Facility-Wide Totals →	0.33	0.02	0.03	0.00	0.02	0.00	0.47

- (1) As the PTE of all individual HAPs is less than 10 TPY and the PTE of total HAPs is less than 25 TPY, the OXF-131 natural gas production facility is defined as a minor source of HAPs for purposes of 40 CFR 61, 40CFR63, and Title V.
- (2) Aggregate emission rate of all such units.
- (3) Includes both pass-through emissions generated by storage tanks and products of combustion.

REGULATORY APPLICABILITY

The proposed EQT natural gas production facility is subject to substantive requirements in the following state and federal air quality rules and regulations: 45CSR2, 45CSR6, 45CSR13, and 40 CFR 60 Subpart OOOO. Each applicable rule (and ones that have reasoned non-applicability), and EQT's compliance therewith, will be discussed in detail below.

45CSR2: To Prevent and Control Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers

The Line Heaters (S0016 to S0020) each have been determined to meet the definition of a "fuel burning unit" under 45CSR2 and are, therefore, subject to the applicable requirements therein. However, pursuant to the exemption given under §45-2-11, as the MDHI of the units are less than 10 mmBtu/hr, they are not subject to sections 4, 5, 6, 8 and 9 of 45CSR2. The only remaining substantive requirement is under Section 3.1 - Visible Emissions Standards.

Pursuant to 45CSR2, Section 3.1, the line heaters are subject to an opacity limit of 10%. Proper maintenance and operation of the units (and the use of natural gas as fuel) should keep the opacity of the units well below 10% during normal operations.

45CSR6: To Prevent and Control Particulate Air Pollution from Combustion of Refuse

EQT has proposed an enclosed combustor for controlling the working/breathing/flashing emissions produced from the condensate storage tanks. The vapor combustor meets the definition of an "incinerator" under 45CSR6 and is, therefore, subject to the requirements therein. The substantive requirements applicable to the vapor combustor are discussed below.

45CSR6 Emission Standards for Incinerators - Section 4.1

Section 4.1 limits PM emissions from incinerators to a value determined by the following formula:

$$\text{Emissions (lb/hr)} = F \times \text{Incinerator Capacity (tons/hr)}$$

Where, the factor, F, is as indicated in Table I below:

Table I: Factor, F, for Determining Maximum Allowable Particulate Emissions

<u>Incinerator Capacity</u>	<u>Factor F</u>
A. Less than 15,000 lbs/hr	5.43
B. 15,000 lbs/hr or greater	2.72

While particulate matter emissions from the combustor are expected to be nominal, for a conservative estimate, EQT calculated potential particulate matter emissions from the unit based on an emission factor taken from AP-42, Section 1.4. Using this emission factor, the hourly particulate matter emission rate from the combustor is 0.37 lbs/hr. Based on information included in the application, the maximum vapor mass sent to the combustor will be 500 lb/hr (0.25 tons/hour). Based on the above, the aggregate particulate matter limit of the combustor is 1.36 lbs/hr. As the total hourly particulate matter emission rate from the combustor is 0.37 lbs/hr, the unit is in compliance with this emission limit.

45CSR6 Opacity Limits for - Section 4.3, 4.4

Pursuant to Section 4.3, and subject to the exemptions under 4.4, the combustor has a 20% limit on opacity during operation. As the primary constituent in the vapors combusted in the unit shall be clean burning methane/ethane, particulate matter emissions from the combustor are expected to be nominal. Therefore, the vapor combustor should easily meet this requirement.

45CSR10: To Prevent and Control Air Pollution from the Emission of Sulfur Oxides (non-applicability)

Pursuant to the exemption given under §45-10-10.1, as the MDHI of the Line Heaters (S015 and S020) are less than 10 mmBtu/hr, the units are not subject to the substantive sections of 45CSR10.

45CSR13: Permits for Construction, Modification, Relocation and Operation of Stationary Sources of Air Pollutants, Notification Requirements, Administrative Updates, Temporary Permits, General Permits, and Procedures for Evaluation

The construction of the OXF-131 natural gas production facility has a potential to emit a regulated pollutant in excess of six (6) lbs/hour and ten (10) TPY and, therefore, pursuant to §45-13-2.24, the facility is defined as a “stationary source” under 45CSR13. Pursuant to §45-13-5.1, “[n]o person shall cause, suffer, allow or permit the construction . . . and operation of any stationary source to be commenced without . . . obtaining a permit to construct.” Therefore, EQT is required to obtain a permit under 45CSR13 for the construction and operation of the natural gas production facility.

As required under §45-13-8.3 (“Notice Level A”), EQT placed a Class I legal advertisement in a “newspaper of general circulation in the area where the source is . . . located.” The ad ran on December 30, 2014 in *The Herald Record* and the affidavit of publication for this legal advertisement was submitted on January 2, 2015.

45CSR14 (NON APPLICABILITY)

The facility-wide potential-to-emit of the OXF-131 natural gas production facility (see Table 3 above) is below the levels that would define the source as "major" under 45CSR14 and, therefore, the construction evaluated herein is not subject to the provisions of 45CSR14.

Potential Source Aggregation

Classifying multiple facilities as one "stationary source" under 45CSR13, 45CSR14, and 45CSR19 is based on the definition of "Building, structure, facility, or installation" as given in §45-14-2.13 and §45-19-2.12. The definition states:

"Building, Structure, Facility, or Installation" means all of the pollutant-emitting activities which belong to the same industrial grouping, are located on one or more contiguous or adjacent properties, and are under the control of the same person (or persons under common control). Pollutant-emitting activities are a part of the same industrial grouping if they belong to the same "Major Group" (i.e., which have the same two (2)-digit code) as described in the Standard Industrial Classification Manual, 1987 (United States Government Printing Office stock number GPO 1987 0-185-718:QL 3).

The proposed OXF-131 natural gas production facility will be located approximately 0.31 miles from the known nearest other EQT facility (OXF-160 well-pad and production facility). OXF-160 shares the same SIC code as OXF-131 and is owned by EQT. Therefore, the potential classification of the OXF-131 facility as one stationary source with OXF-160 depends on the determination if these stations are considered "contiguous or adjacent properties."

"Contiguous or Adjacent" determinations are made on a case by case basis. These determinations are proximity-based, and it is important to focus on this and whether or not it meets the common sense notion of one stationary source. The terms "contiguous" or "adjacent" are not defined by USEPA. Contiguous has a dictionary definition of being in actual contact; *touching along a boundary or at a point*. Adjacent has a dictionary definition of not distant; nearby; *having a common endpoint or border*.

The OXF-131 natural gas production facility is not located contiguous with, or *directly* adjacent to the OXF-160 facility. As noted above, the facilities are 0.31 miles apart. Facilities separated by this distance do not meet the common sense notion of a single plant. Therefore, the OXF-131 and OXF-160 facilities are not considered to be on contiguous or adjacent property.

45CSR17: To Prevent and Control Particulate Matter Air Pollution from Materials Handling, Preparation, Storage and Other Sources of Fugitive Particulate Matter

45CSR17 requires facilities to “prevent and control particulate matter air pollution from materials handling, preparation, storage and other sources of fugitive particulate matter.” Specifically, §45-17-3.2b requires “[a]pplication of . . . water or suitable chemicals on unpaved roads. . . and other surfaces which can create airborne particulate matter.” To meet this requirement, the draft permit, pursuant to 4.1.8, requires EQT to maintain all paved roads/work areas and use a water truck on all unpaved roads/work areas when necessary.

45CSR30: Requirements for Operating Permits - (NON APPLICABILITY)

45CSR30 provides for the establishment of a comprehensive air quality permitting system consistent with the requirements of Title V of the Clean Air Act. The proposed facility does not meet the definition of a "major source under § 112 of the Clean Air Act" as outlined under §45-30-2.26 and clarified (fugitive policy) under 45CSR30b. However, as the facility is subject to a New Source Performance Standard (NSPS) - 40 CFR 60, Subpart OOOO - the facility would, in most cases, be subject to Title V as a “deferred source.” However, pursuant to §60.5370(c), as a non-major “area source,” EQT is not required to obtain a Title V permit for the proposed facility. Therefore, the OXF-131 natural gas production facility is not subject to 45CSR30.

Subpart Kb—Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984 - (NON APPLICABILITY)

Pursuant to §60.110b, 40 CFR 60, Subpart Kb applies to “each storage vessel with a capacity greater than or equal to 75 cubic meters (m³) that is used to store volatile organic liquids (VOL) for which construction, reconstruction, or modification is commenced after July 23, 1984.” The largest storage tanks located at the OXF-131 facility are each 8,820 gallons, or 33.38 m³. Therefore, Subpart Kb does not apply to any of the storage tanks.

40 CFR 60, Subpart OOOO: Standards of Performance for Crude Oil and Natural Gas Production, Transmission and Distribution

On April 27, 2012 the USEPA issued a final rule (published in the Federal Register on August 16, 2012) that consists of federal air standards for natural gas wells that are hydraulically fractured, along with requirements for several other sources of pollution in the oil and gas industry that currently are not regulated at the federal level. Pursuant to §60.5365(a) each “gas well affected facility, which is a single natural gas well” that is constructed after August 23, 2011 is subject to the applicable provisions of Subpart OOOO as well as “[e]ach storage vessel affected facility, which is a single storage vessel, located in the oil and natural gas production segment, natural gas processing

segment or natural gas transmission and storage segment.”

Gas Wells - §60.5370

EQT has drilled gas wells at the OXF-131 well-pad and, therefore, these are defined as “affected facilities” under Subpart OOOO and subject to applicable provisions. The substantive requirements for gas wells drilled prior to January 1, 2015 are given under §60.5375(a)(3) of the rule. It requires that flowback emissions (gas produced from the well after fracturing) must be directed to the flow line or a completion combustion device. EQT shall directed all gas from wells during flowback at the OXF-131 site into the flow line. Other requirements pertaining to the gas wells include:

- EQT must maintain a log for each well completion operation at each gas well affected facility. The log must be completed on a daily basis for the duration of the well completion operation and must contain the records specified in §60.5420(c)(1)(iii).
[40CFR§60.5375(b)]
- EQT must demonstrate initial compliance with the standards that apply to gas well affected facilities as required by §60.5410.
[40CFR§60.5375(c)]
- EQT must demonstrate continuous compliance with the standards that apply to gas well affected facilities as required by §60.5415.
[40CFR§60.5375(d)]
- EQT must perform the required notification, recordkeeping and reporting as required by §60.5420.
[40CFR§60.5375(e)]

Storage Tanks - §60.5395 - (NON APPLICABILITY)

Under §60.5395, the requirements for storage tanks take effect on October 15, 2013. However, as the site is expected to be in production at that time, the storage tank requirements will be reviewed. The substantive requirement for storage tanks is given under §60.5395(a) of the rule. It requires that for each storage vessel “emitting more than 6 tpy VOC, [the permittee] must reduce VOC emissions by 95.0 percent of greater. . .” Based on a letter from USEPA to the American Petroleum Instituted dated September 28, 2012, applicability of storage vessels to Subpart OOOO is based on individual tank PTE - which includes federally enforceable control devices.

The fifteen (15) condensate/produced water storage tanks are each calculated to have a PTE (including controls) of less than 6 TPY of VOCs and, therefore, these storage tanks are not subject requirements under §60.5395.

Pneumatic Controllers

Pursuant to §60.5365(d)(2), “[f]or the natural gas production segment (between the wellhead and the point of custody transfer to the natural gas transmission and storage segment and not including natural gas processing plants), each pneumatic controller affected facility, which is a single continuous bleed natural gas-driven pneumatic controller operating at a natural gas bleed rate greater than 6 scfh” that is constructed after August 23, 2011 is subject to the applicable provisions of Subpart OOOO. The substantive requirements for pneumatic controllers are given under §60.5390. While not identified, it is assumed the facility will use pneumatic controllers and will be required to meet this requirement.

TOXICITY ANALYSIS OF NON-CRITERIA REGULATED POLLUTANTS

This section provides an analysis for those regulated pollutants that may be emitted from the OXF-131 natural gas production facility and that are not classified as “criteria pollutants.” Criteria pollutants are defined as Carbon Monoxide (CO), Lead (Pb), Oxides of Nitrogen (NO_x), Ozone, Particulate Matter (PM), Particulate Matter less than 10 microns (PM₁₀), Particulate Matter less than 2.5 microns (PM_{2.5}), and Sulfur Dioxide (SO₂). These pollutants have National Ambient Air Quality Standards (NAAQS) set for each that are designed to protect the public health and welfare. Other pollutants of concern, although designated as non-criteria and without national concentration standards, are regulated through various federal programs designed to limit their emissions and public exposure. These programs include federal source-specific Hazardous Air Pollutants (HAPs) standards promulgated under 40 CFR 61 (NESHAPS) and 40 CFR 63 (MACT). Any potential applicability to these programs were discussed above under REGULATORY APPLICABILITY.

The majority of non-criteria regulated pollutants fall under the definition of HAPs which, with some revision since, were 188 compounds identified under Section 112(b) of the Clean Air Act (CAA) as pollutants or groups of pollutants that EPA knows or suspects may cause cancer or other serious human health effects. EQT included the following HAPs as emitted in substantive amounts in their emissions estimate: Benzene, n-Hexane, Toluene, and Xylenes. The following table lists each HAP’s carcinogenic risk (as based on analysis provided in the Integrated Risk Information System (IRIS)):

Table 5: Potential HAPs - Carcinogenic Risk

HAPs	Type	Known/Suspected Carcinogen	Classification
n-Hexane	VOC	No	Inadequate Data
Benzene	VOC	Yes	Category A - Known Human Carcinogen
Toluene	VOC	No	Inadequate Data
Xylenes	VOC	No	Inadequate Data

All HAPs have other non-carcinogenic chronic and acute effects. These adverse health effects may be associated with a wide range of ambient concentrations and exposure times and are influenced by source-specific characteristics such as emission rates and local meteorological conditions. Health impacts are also dependent on multiple factors that affect variability in humans such as genetics, age, health status (e.g., the presence of pre-existing disease) and lifestyle. As stated previously, *there are no federal or state ambient air quality standards for these specific chemicals*. For a complete discussion of the known health effects of each compound refer to the IRIS database located at www.epa.gov/iris.

AIR QUALITY IMPACT ANALYSIS

The estimated maximum emissions from the proposed OXF-131 natural gas production facility are less than applicability thresholds that would define the proposed facility as a “major stationary source” under 45CSR14 and, therefore, no air quality impacts modeling analysis was required. Additionally, based on the nature of the proposed construction, modeling was not required under 45CSR13, Section 7.

MONITORING, COMPLIANCE DEMONSTRATIONS, REPORTING, AND RECORDING OF OPERATIONS

The following substantive monitoring, compliance demonstration, and record-keeping requirements (MRR) shall be required:

- For the purposes of demonstrating compliance with maximum limit for the aggregate production of condensate/liquids from the wells set forth in 4.1.3 of the draft permit, EQT shall be required to monitor and record the monthly and rolling twelve month total of

condensate/liquids (in gallons) produced in the wells. Monitoring and recording the monthly and rolling twelve month total of condensate/liquids (in gallons) unloaded from the storage tanks can be used to show compliance with this requirement.

- For the purposes of demonstrating compliance with visible emissions limitations set forth in 4.1.2(d) of the draft permit, EQT shall be required to:
 - (1) Conduct an initial Method 22 visual emission observation on the line heaters to determine the compliance with the visible emission provisions. EQT shall be required to take a minimum of two (2) hours of visual emissions observations on the line heaters.
 - (2) Conduct monthly Method 22 visible emission observations of the line heaters stack to ensure proper operation for a minimum of ten (10) minutes each month the line heaters are in operation.
 - (3) In the event visible emissions are observed in excess of the limitations given under 4.1.2(d) of the draft permit, EQT shall be required to take immediate corrective action.
- EQT shall be required to maintain records of all startups, shutdowns, and/or malfunctions of the vapor combustor. These records shall include the date, time, and duration of each event.
- EQT shall be required to maintain records of the date, time, and duration each time the permittee does not detect the presence of a pilot flame in the vapor combustor.
- For the purposes of demonstrating compliance with visible emissions limitations set forth in 4.1.6(f) of the draft permit, EQT shall be required to:
 - (1) Conduct an initial Method 22 visual emission observation on the vapor combustor to determine the compliance with the visible emission provisions. EQT shall be required to take a minimum of two (2) hours of visual emissions observations on the vapor combustor.
 - (2) Conduct monthly Method 22 visible emission observations of the vapor combustor stack to ensure proper operation for a minimum of ten (10) minutes each month the vapor combustor is in operation.
 - (3) In the event visible emissions are observed in excess of the limitations given under 4.1.6(f) of the draft permit, EQT shall be required to take immediate corrective action.

- EQT shall be required to maintain records of all visual emission observations pursuant to the monitoring required under 4.22 and 4.2.3(c) of the draft permit including any corrective action taken.
- EQT shall be required to meet all applicable Monitoring, Compliance Demonstration and Source-Specific Recordkeeping Requirements as given under 40 CFR 60, Subpart OOOO.


PERFORMANCE TESTING OF OPERATIONS

The following substantive performance testing requirements shall be required:


- Within sixty (60) days of the issuance date of the draft permit, EQT shall be required to perform, or have performed, an analysis to determine the constituent properties of the condensate (testing done previous to permit issuance deemed to be appropriate by the Director shall be accepted). The analysis shall, at a minimum, include the same components as the analysis used to calculate storage tank emissions in Permit Application R13-3001. Where applicable, if the analysis shows average constituent properties that, when used to calculate emissions in the same manner as submitted in Permit Application R13-3001, result in emissions that are greater than the levels that define a "modification" under 45CSR13, EQT shall be required to, within thirty (30) days of receiving the results of the analysis, submit to the Director an appropriate permit application to increase emissions.
- EQT shall be required to meet all applicable Testing Requirements as given under 40 CFR 60, Subpart OOOO.

RECOMMENDATION TO DIRECTOR

The information provided in general permit registration application G70-A132 indicates that compliance with all applicable regulations will be achieved. Therefore, I recommend to the Director the issuance of Permit Registration Number G70-A132 to EQT Production Company for the modification and operation of the OXF-131 natural gas production facility located near New Milton, Doddridge County, WV.



Roy F. Kees, P.E.
Engineer - NSR Permitting



Date