



---

**west virginia** department of environmental protection

---

Division of Air Quality  
601 57<sup>th</sup> Street SE  
Charleston, WV 25304  
Phone (304) 926-0475 • FAX: (304) 926-0479

Earl Ray Tomblin, Governor  
Randy C. Huffman, Cabinet Secretary  
[www.dep.wv.gov](http://www.dep.wv.gov)

## **ENGINEERING EVALUATION / FACT SHEET**

### BACKGROUND INFORMATION

Application No.: R13-2960  
Plant ID No.: 069-00126  
Applicant: Chesapeake Appalachia LLC  
Facility Name: Mason Cottrell Pad  
Location: Ohio County  
NAICS Code: 211111  
Application Type: Construction  
Received Date: July 7, 2012  
Engineer Assigned: David Keatley  
Fee Amount: \$2,000  
Date Received: July 11, 2012  
Complete Date: August 30, 2012  
Due Date: November 28, 2012  
Applicant Ad Date: July 2, 2012  
Newspaper: *The Intelligencer*  
UTM's: Easting: 532.584 km Northing: 4,436.246 km Zone: 17  
Description: Installation of one (1) 145 bhp engine, two (2) 1.00 MMBTU/hr GPU burners, one (1) 1.5 MMBTU/hr line heater, two (2) 0.5 MMBTU/hr heater treaters, six (6) 400 bbl condensate tanks, six (6) 400 bbl produced water tanks, and two (2) vapor combustors.

### DESCRIPTION OF PROCESS

The facility is an oil and natural gas exploration and production facility, responsible for the production of natural gas. Storage of condensate and produced water will also be on-site. Condensate, gas, and water come from two (2) wellheads to two (2) production units, where the first state of separation occurs. Fluids (condensate and produced water) will be sent to two (2) 0.5 MMBTU/hr heater treater (EU-HT1 and EU-HT2). The flash from the heater treaters is captured via the one (1) natural gas-fired flash gas compressor engines

(EU-ENG1). The natural gas fired compressor engine is a four-stroke rich-burn Caterpillar G3306 NA equipped with a NSCR catalyst which will reduce the emissions of NO<sub>x</sub>, CO, and VOCs. Produced water from the heater treaters flows into the produced water storage tanks EU-TANKS-PW. There are six (6) 12,400 gallon water storage tanks. Condensate flows into the two low-pressure towers. Flash gases from the low-pressure tower(s) are routed via hard-piping to the two (2) vapor combustors to be burned with at least 98% combustion efficiency. Condensate flows to the condensate storage tanks EP-TANKS-COND. There are six (6) 12,400 gallon condensate storage tanks. The natural gas stream will exit the facility for transmission via pipeline. Condensate and produced water are transported offsite via truck. Loading emissions will be controlled with vapor return, which has a 70% capture efficiency, routed to the vapor combustors EU-PILOTS for at least 98% destruction efficiency. Working, breathing, and flashing vapors from the condensate and produced water storage tanks will be routed to the vapor combustors to be burned with at least 98% combustion efficiency. Each vapor combustor has a natural gas-fired pilot EU-PILOTS to ensure a constant flame for combustion. A line heater (EU-LH1) may be used during the beginning phase of facility operations.

### SITE INSPECTION

From I 70 take exit 2A. Turn right onto US 40, travel 0.45 miles to the intersection of US 40 and SR 88 N (Bethany Pike). Turn left onto SR 88 N, travel 5.02 miles to CR 33 (Dement Road) and turn right and travel 1.6 miles to CR 8 (Chapel Hill Road). Turn right on CR 8 and drive approximately 2.49 miles to CR 40/3 (Gashell Run Road) and turn left. Well pad access will be approximately 0.43 miles down 40/3 on the right.

Steven J. Sobutka from the DAQ's Compliance and Enforcement performed a site visit on August 10, 2012. The closest residence is at least 1,000 feet away.

### ESTIMATE OF EMISSIONS BY REVIEWING ENGINEER

The Caterpillar Engine emission factors are from the catalyst manufacturer (CM), the engine manufacturer (EM), and AP-42. Emission factors from the EM in g/bhp-hr are: VOC, 0.49; and formaldehyde, 0.27. Emissions factors for the CM in g/bhp-hr are: NO<sub>x</sub>, 1.0; and CO, 2.0. The emission factors from AP-42 in lb/MMBTU are: PM and PM<sub>10</sub>, 0.00999; and SO<sub>2</sub>, 0.000588.

The GPU burner(s), Heater Treater(s), and Line Heater(s) use emission factors from AP-42. The emission factors in lb/MMscf are: NO<sub>x</sub>, 100; CO, 84; SO<sub>2</sub>, 0.6; PM, 7.6; and VOC, 5.5.

Emissions for EP-TANKS-COND working and breathing emissions were estimated using TANKS 4.0.9d and the flash emissions were estimated using ProMax. The Vapor Combustors are considered to have a 98% efficiency.

The emissions from the other tanks were considered negligible due to the combination of

small tank size and low vapor pressure of tank contents.

The following table lists the estimated emissions:

Source ID	Emission Source	Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (tpy)
EU-MC4248	Flash Gas Compressor Engine Caterpillar 3306 NA	NO <sub>x</sub>	0.32	1.40
		CO	0.64	2.80
		VOC	0.16	0.67
		PM	0.02	0.09
		PM <sub>10</sub>	0.02	0.09
		Formaldehyde	0.09	0.38
		CO <sub>2e</sub>	155.18	679.70
EU-GPU1	GPU Burner 1 1.00 MMBTU/hr	NO <sub>x</sub>	0.11	0.48
		CO	0.09	0.39
		VOC	0.01	0.03
		PM	0.01	0.04
		PM <sub>10</sub>	0.01	0.04
		CO <sub>2e</sub>	117.00	512.48
EU-GPU2	GPU Burner 2 1.00 MMBTU/hr	NO <sub>x</sub>	0.11	0.48
		CO	0.09	0.39
		VOC	0.01	0.03
		PM	0.01	0.04
		PM <sub>10</sub>	0.01	0.04
		CO <sub>2e</sub>	117.00	512.48
EU-LH1	Line Heater 1 1.5 MMBTU/hr	NO <sub>x</sub>	0.17	0.74
		CO	0.14	0.61
		VOC	0.01	0.04
		PM	0.01	0.06
		PM <sub>10</sub>	0.01	0.06
		CO <sub>2e</sub>	175.51	767.96
EU-HT1	Heater Treater 1 0.5 MMBTU/hr	NO <sub>x</sub>	0.06	0.26
		CO	0.05	0.22
		VOC	<0.01	0.01
		CO <sub>2e</sub>	58.50	256.24
EU-HT2	Heater Treater 2 0.5 MMBTU/hr	NO <sub>x</sub>	0.06	0.26
		CO	0.05	0.22
		VOC	<0.01	0.01
		CO <sub>2e</sub>	58.50	256.24
EP-TANKS-COND	Six (6) Condensate Tanks 400-bbl	VOC	0.45	1.96
		Ethylbenzene	<0.01	0.01
		n-Hexane	0.03	0.11
		Toluene	<0.01	0.01
		Xylenes	0.01	0.03

EP-TANKS-PW	Six (6) Produced Water Tanks 400-bbl	VOC	<0.01	0.01
EP-LOAD-COND	Condensate Truck Loading	VOC	2.60	11.37
		Benzene	<0.01	0.01
		n-Hexane	0.15	0.66
		Toluene	0.01	0.04
		Ethylbenzene	0.01	0.01
		Xylenes	0.04	0.16
EP-LOAD-PW	Produced Water Truck Loading	CO <sub>2e</sub>	0.32	1.42
		VOC	0.03	0.13
APC-Combustors	Two (2) Vapor Combustors One (1) 30 MMBTU/hr and One (1) 8 MMBTU/hr	NO <sub>x</sub>	5.24	22.95
		CO	10.47	45.86
		VOC	10.20	44.68
		PM	0.11	0.48
		PM <sub>10</sub>	0.11	0.48
		Benzene	0.01	0.03
		n-Hexane	0.59	2.58
		Toluene	0.04	0.18
		Ethyl benzene	0.04	0.18
		Xylenes	0.15	0.66
		CO <sub>2e</sub>	4,446.14	19,474.06
EU-PILOTS	Two (2) Vapor Combustor Pilots 50 scf/hr	NO <sub>x</sub>	0.02	0.09
		CO	0.01	0.04
		CO <sub>2e</sub>	10.59	46.39
EU-FUG	Fugitive Emissions	VOC	0.84	3.70
		CO <sub>2e</sub>	12.60	55.03

The following table represents the total facility emissions:

Pollutant	Maximum Annual Facility Wide Emissions (tons/year)
Nitrogen Oxides	27.40
Carbon Monoxide	51.16
Volatile Organic Compounds	62.68
Particulate Matter	0.80
Sulfur Dioxide	0.02
Formaldehyde	0.38
Benzene	0.05
n-Hexane	3.59
Ethylbenzene	0.24

Toluene	0.24
Xylenes	0.89
Carbon Dioxide Equivalent	23,356.04

The following table indicates the control device efficiencies that are required for this facility:

Emission Unit	Pollutant	Control Device	Control Efficiency
EU-MC4207 Compressor Engine	Nitrogen Oxides	Non Selective Catalytic Reduction (NSCR)	92.58 %
	Carbon Monoxide		85.15 %
EU-TANKS-COND, EU-TANKS-PW Storage Tanks	Volatile Organic Compounds	Vapor Combustor	98.00 %
	Total HAPs		98.00 %
EU-LOAD-COND, EU- LOAD-PW Loadout Racks	Volatile Organic Compounds	Vapor Return/ Combustion	70.00 %

## REGULATORY APPLICABILITY

*Unless otherwise stated WVDEP DAQ did not determine whether the permittee is subject to an area source air toxics standard requiring Generally Achievable Control Technology (GACT) promulgated after January 1, 2007 pursuant to 40 CFR 63, including the area source air toxics provisions of 40 CFR 63, Subpart ZZZZ.*

The following rules apply to the facility:

### **45CSR2** (Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers)

The purpose of 45CSR2 (Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers) is to establish emission limitations for smoke and particulate matter which are discharged from fuel burning units.

45CSR2 states that any fuel burning unit that has a heat input under ten (10) million B.T.U.'s per hour is exempt from sections 4 (weight emission standard), 5 (control of fugitive particulate matter), 6 (registration), 8 (testing, monitoring, recordkeeping, reporting) and 9 (startups, shutdowns, malfunctions). However, failure to attain acceptable air quality in parts of some urban areas may require the mandatory control of these sources at a later date.

The heat input of all of the proposed fuel burning units (EP-GPU1, EP-GPU2, EP-HT1, EP-HT2, and EP-LH1) are below 10 MMBTU/hr. Therefore, these units are exempt from the aforementioned sections of 45CSR2. However, CHK would be subject to the opacity requirements in 45CSR2, which is 10% opacity based on a six minute block average.

**45CSR4** (To Prevent and Control the Discharge of Air Pollutants into the Open Air which Causes or Contributes to an Objectionable Odor or Odors)

This facility shall not cause the discharge of air pollutants which cause or contribute to an objectionable odor at any location occupied by the public. 45CSR4 states that an objectionable odor is an odor that is deemed objectionable when in the opinion of a duly authorized representative of the Air Pollution Control Commission (Division of Air Quality), based upon their investigations and complaints, such odor is objectionable.

**45CSR6** (To Prevent and Control Air Pollution from the Combustion of Refuse)

The purpose of this rule is to prevent and control air pollution from combustion of refuse.

CHK has two (2) vapor combustors at the facility. The vapor combustors are subject to section 4, emission standards for incinerators. The 30 MMBTU/hr vapor combustor has an allowable emission rate of 1.10 pounds of particulate matter per hour. The 8 MMBTU/hr vapor combustor has an allowable emission rate of 0.30 pounds of particulate matter per hour. The 30 MMBTU/hr vapor combustor has an emission limit of 0.09 pounds of particulate matter per hour and the 8 MMBTU/hr vapor combustor has an emission limit of 0.03. Therefore, the facility's vapor combustors should demonstrate compliance with this section. The facility will demonstrate compliance by maintaining records of the amount of natural gas consumed by the vapor combustors and the hours of operation. The facility will also monitor the flame of the vapor combustors and record any malfunctions that may cause no flame to be present during operation. The opacity limit for the flare is 20%.

**45CSR10** (To Prevent and Control Air Pollution from the Emissions of Sulfur Oxides)

45CSR10 states that any fuel burning unit that has a heat input under ten (10) million B.T.U.'s per hour is exempt from sections 3 (weight emission standard), 6 (registration), 7 (permits), and 8 (testing, monitoring, recordkeeping, reporting). However, failure to attain acceptable air quality in parts of some urban areas may require the mandatory control of these sources at a later date.

The heat input of all of the proposed fuel burning units (EP-GPU1, EP-GPU2, EP-LH1, EP-HT1, and EP-HT2) are below 10 MMBTU/hr. Therefore, these units are exempt from the aforementioned sections of 45CSR10.

**45CSR13** (Permits for Construction, Modification, Relocation and Operation of Stationary Sources of Air Pollutants, Notification Requirements, Administrative Updates, Temporary Permits, General Permits, and Procedures for Evaluation)

45CSR13 applies to this source due to the fact that the changes proposed under this permitting action results in an emissions increase above permitting thresholds. Therefore, CHK is required to submit a construction application. CHK has published the required Class I legal

advertisement notifying the public of their permit application, and paid the appropriate application fee (construction).

**45CSR22** (Air Quality Management Fee Program)

This facility is a minor source and not subject to 45CSR30. CHK is required to keep their Certificate to Operate current. CHK also paid a 1,000 NSPS fee.

**40CFR60 Subpart JJJJ** (Standards of Performance for Stationary Spark Ignition Internal Combustion Engines (SI ICE))

40CFR60.4230 states that a source that commenced construction after June 12, 2006 whose SI ICE was less than 500 hp and was manufactured on or after July 1, 2008 is subject to this rule. CHK has proposed to install one (1) 145 HP SI ICE. Since the SI ICE that CHK will install was manufactured on January 3, 2012, CHK is subject to this rule.

**40CFR60 Subpart OOOO** (Standards of Performance for Crude Oil and Natural Gas Production, Transmission and Distribution)

EPA issued its new source performance standards (NSPS) and air toxics rules for the oil and gas sector on April 17, 2012. 40CFR60 Subpart OOOO establishes emission standards and compliance schedules for the control of volatile organic compounds (VOC) and sulfur dioxide (SO<sub>2</sub>) emissions from affected facilities that commence construction, modification or reconstruction after August 23, 2011. The following affected sources which commence construction, modification or reconstruction after August 23, 2011 are subject to the applicable provisions of this subpart:

- a. Each gas well affected facility, which is a single natural gas well.

*The gas wells that currently exist at the Mason Cottrell Pad were drilled principally for the production of natural gas and were done so after August 23, 2011. Therefore, these wells would be considered affected facilities under this subpart.*

- b. Each centrifugal compressor affected facility, which is a single centrifugal compressor using wet seals that is located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment. For the purposes of this subpart, your centrifugal compressor is considered to have commenced construction on the date the compressor is installed (excluding relocation) at the facility. A centrifugal compressor located at a well site, or an adjacent well site and servicing more than one well site, is not an affected facility under this subpart.

*There are no centrifugal compressors at the Mason Cottrell Pad. Therefore, this section would not apply.*

- c. Each reciprocating compressor affected facility, which is a single reciprocating compressor located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment. For the purposes of this subpart, your reciprocating compressor is considered to have commenced construction on the date the compressor is installed (excluding relocation) at the facility. A reciprocating compressor located at a well site, or an adjacent well site and servicing more than one well site, is not an affected facility under this subpart.

*There is one (1) 145 hp reciprocating internal combustion engines located at the Mason Cottrell Pad. This engine was delivered on April 1, 2012 which is after to the effective date of this rule. However, the rule specifically states that any reciprocating compressor located at a well site is not an affected facility under this subpart. Therefore, this section would not apply.*

- d. 1. Each pneumatic controller affected facility, which is a single continuous bleed natural gas-driven pneumatic controller operating at a natural gas bleed rate greater than 6 scfh which commenced construction after August 23, 2011, and is located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment and not located at a natural gas processing plant.
2. Each pneumatic controller affected facility, which is a single continuous bleed natural gas-driven pneumatic controller which commenced construction after August 23, 2011, and is located at a natural gas processing plant.

*There are no pneumatic controllers at the Mason Cottrell Pad. Therefore, this section would not apply.*

- e. Each storage vessel affected facility, which is a single storage vessel, located in the oil and natural gas production segment, natural gas processing segment or natural gas transmission and storage segment.

40CFR60 Subpart OOOO defines a storage vessel as a unit that is constructed primarily of nonearthen materials (such as wood, concrete, steel, fiberglass, or plastic) which provides structural support and is designed to contain an accumulation of liquids or other materials. The following are not considered storage vessels:

1. Vessels that are skid-mounted or permanently attached to something that is mobile (such as trucks, railcars, barges or ships), and are intended to be located at a site for less than 180 consecutive days. If the source does not keep or are not able to produce records, as required by §60.5420(c)(5)(iv), showing that the vessel has been located at a site for less than 180 consecutive days, the vessel described herein is considered to be a storage vessel since the original vessel was first located at the site.

2. Process vessels such as surge control vessels, bottoms receivers or knockout vessels.

3. Pressure vessels designed to operate in excess of 204.9 kilopascals and without emissions to the atmosphere.

This rule requires that the permittee determine the VOC emission rate for each storage vessel affected facility utilizing a generally accepted model or calculation methodology within 30 days of startup, and minimize emissions to the extent practicable during the 30 day period using good engineering practices. For each storage vessel affected facility that emits more than 6 tpy of VOC, the permittee must reduce VOC emissions by 95% or greater within 60 days of startup.

*All six (6) EP-TANKS-COND tanks located at the Mason Cottrell Pad emit more than 6 tpy of VOC (16.32 tpy each). Therefore, CHK would be required by this section to reduce VOC emissions by 95%. To meet this requirements CHK has proposed to install vapor combustors to capture 98% of the VOC emissions from the storage tanks.*

f. The group of all equipment, except compressors, within a process unit is an affected facility.

1. Addition or replacement of equipment for the purpose of process improvement that is accomplished without a capital expenditure shall not by itself be considered a modification under this subpart.

2. Equipment associated with a compressor station, dehydration unit, sweetening unit, underground storage vessel, field gas gathering system, or liquefied natural gas unit is covered by §§60.5400, 60.5401, 60.5402, 60.5421 and 60.5422 of this subpart if it is located at an onshore natural gas processing plant. Equipment not located at the onshore natural gas processing plant site is exempt from the provisions of §§60.5400, 60.5401, 60.5402, 60.5421 and 60.5422 of this subpart.

3. The equipment within a process unit of an affected facility located at onshore natural gas processing plants and described in paragraph (f) of this section are exempt from this subpart if they are subject to and controlled according to subparts VVa, GGG or GGGa of this part.

*The Mason Cottrell Pad is not a natural gas processing plant. Therefore, LDAR for onshore natural gas processing plants would not apply.*

g. Sweetening units located at onshore natural gas processing plants that process natural gas produced from either onshore or offshore wells.

1. Each sweetening unit that processes natural gas is an affected facility; and

2. Each sweetening unit that processes natural gas followed by a sulfur recovery unit is an affected facility.
3. Facilities that have a design capacity less than 2 long tons per day (LT/D) of hydrogen sulfide (H<sub>2</sub>S) in the acid gas (expressed as sulfur) are required to comply with recordkeeping and reporting requirements specified in §60.5423(c) but are not required to comply with §§60.5405 through 60.5407 and paragraphs 60.5410(g) and 60.5415(g) of this subpart.
4. Sweetening facilities producing acid gas that is completely reinjected into oil-or-gas-bearing geologic strata or that is otherwise not released to the atmosphere are not subject to §§60.5405 through 60.5407, 60.5410(g), 60.5415(g), and 60.5423 of this subpart.

*There are no sweetening units at the Mason Cottrell Pad. Therefore, this section would not apply.*

The following rules and regulations do not apply to the facility:

**40CFR60 Subpart 60.18** (General Control Device and Work Practice Requirements)

40CFR60 Subpart 60.18 contains requirements for control devices when they are used to comply with applicable subparts of 40CFR60 and 40CFR61. The vapor combustor that CHK has proposed is not used to comply with one of these rules. The purpose of the vapor combustor is to control emissions from the tanks that are routed to it. However, these tanks are not subject to 40CFR60 Subpart Kb due to their size. In addition 40CFR60.18 refers to flares but makes no mention of vapor combustors, which are essentially enclosed combustion devices. Therefore, CHK is not subject to this standard.

**40CFR60 Subpart Kb** (Standards of Performance for VOC Liquid Storage Vessels)

40CFR60 Subpart Kb does not apply to storage vessels with a capacity less than 75 cubic meters. The tanks that CHK has proposed to install are 63.60 cubic meters each. Therefore, CHK would not be subject to this regulation.

**40CFR60 Subpart KKK** (Standards of Performance for Equipment Leaks of VOC from Onshore Natural Gas Processing Plants)

40CFR60 Subpart KKK applies to onshore natural gas processing plants that commenced construction after January 20, 1984. The Mason Cottrell Pad is not a natural gas processing plant, therefore, CHK would not be subject to this regulation.

**45CSR14** (Permits for Construction and Major Modification of Major Stationary Sources of Air Pollutants)

**45CSR19** (Permits for Construction and Major Modification of Major Stationary Sources of Air Pollution which Cause or Contribute to Nonattainment)

The Mason Cottrell Pad is located in Ohio County which is a non-attainment county for Particulate Matter 2.5. Because Ohio County is a non-attainment county, 45CSR19 does apply to this facility.

As shown in the table below, CHK is not subject to 45CSR14 or 45CSR19 review.

<b>Pollutant</b>	<b>PSD (45CSR14) Threshold (tpy)</b>	<b>NANSR (45CSR19) Threshold (tpy)</b>	<b>PTE (tpy)</b>	<b>45CSR14 or 45CSR19 Review Required?</b>
Carbon Monoxide	250	NA	51.16	No
Nitrogen Oxides	250	100	27.40	No
Sulfur Dioxide	250	100	0.02	No
Particulate Matter 2.5	250	100	0.80	No
Ozone (VOC)	250	NA	62.68	No
Greenhouse Gas (CO <sub>2</sub> e)	100,000	NA	23,356.04	No

## TOXICITY OF NON-CRITERIA REGULATED POLLUTANTS

There will be small amounts of various non-criteria regulated pollutants emitted from the combustion of natural gas. However, due to the concentrations emitted, detailed toxicological information is not included in this evaluation.

## AIR QUALITY IMPACT ANALYSIS

Based on the annual emission rates this facility will not be a major source as defined by 45CSR14, so air quality modeling was not performed.

## SOURCE AGGREGATION

“Building, structure, facility, or installation” is defined as all the pollutant emitting activities which belong to the same industrial grouping, are located on one or more contiguous and adjacent properties, and are under the control of the same person.

The Mason Cottrell Pad is located in Ohio County and will be operated by CHK, who is partial owner and operator. Several different entities are involved in the production, gathering, and transmission of gas. The Operators are the parties who drill and operate the wells. The Shippers are the owners of the gas who may or may not be the same entity as the Operator. There are also

Fact Sheet R13-2960  
Chesapeake Appalachia, LLC  
Mason Cottrell Pad

parties who own and operate the gathering system pipelines and compression station, called Gatherers. In addition, there are parties that own and operate the gas processing plants.

1. The Mason Cottrell Pad will operate under SIC code 1311 (Crude Petroleum and Natural Gas Extraction). There are surrounding wells and compressor stations operated by CHK that share the same two-digit major SIC code of 13 for oil and gas exploration and production. Therefore the Mason Cottrell Pad does share the same SIC code as the wells and surrounding compressor stations.

2. “Contiguous or Adjacent” determinations are made on a case by case basis. These determinations are proximity based, and it is important to focus on this and whether or not it meets the common sense notion of a plant. The terms “contiguous” or “adjacent” are not defined by USEPA. Contiguous has a dictionary definition of being in actual contact; touching along a boundary or at a point. Adjacent has a dictionary definition of not distant; nearby; having a common endpoint or border.

The closest well to the Mason Cottrell Pad is over one quarter (1/4) mile away. Operations separated by these distances do not meet the common sense notion of a plant. Therefore, the properties in question are not considered to be on contiguous or adjacent property.

3. According to CHK, none of the wells in the area are under common control with the Mason Cottrell Pad. The Mason Cottrell Pad is operated by CHK but is owned and controlled by a group of non-affiliated companies. Through proprietary agreements, CHK’s operation of the Mason Cottrell Pad is controlled by the system owners. The ownership and control of the wells in the area may be distinct for each well and is not necessarily known by CHK. The owners and operators of the wells each may take their gas in kind and consequently affect the operation of the wells in which they have an ownership interest. Furthermore, no well is dependent on the operation of the Mason Cottrell Pad to function, nor is the Mason Cottrell Pad dependent on any specific well to operate. From this analysis, CHK is not under common control with other wells in the area.

Because the facilities are not considered to be on contiguous or adjacent properties and are not fully under control of the same person, the emissions from the Mason Cottrell Pad should not be aggregated with other facilities in determining major source or PSD status.

## MONITORING OF OPERATIONS

CHK will be required to perform the following monitoring associated with this permit application:

1. Monitor and record quantity of natural gas consumed for all engines, and combustion sources.
2. Monitor the presence of the vapor combustor pilot flame with a thermocouple or equivalent.

3. Monitor opacity from all fuel burning units.
4. Monitor the tanks to ensure that all vapors are sent to vapor combustor.
5. Monitor the condensate truck loading to ensure that vapor return/combustion is used.

CHK will be required to perform the following recordkeeping associated with this modification application:

1. Maintain records of the amount of natural gas consumed in each combustion source.
2. Maintain records of testing conducted in accordance with the permit. Said records shall be maintained on-site or in a readily accessible off-site location
3. Maintain the corresponding records specified by the on-going monitoring requirements of and testing requirements of the permit.
4. Maintain records of the visible emission opacity tests conducted per the permit.
5. Maintain a record of all potential to emit (PTE) HAP calculations for the entire facility. These records shall include the natural gas compressor engines and ancillary equipment.
6. The records shall be maintained on site or in a readily available off-site location maintained by CHK for a period of five (5) years.
7. Monitor the tanks to ensure that the tanks vapors will be sent to vapor combustor.
8. Monitor the condensate truck loading to ensure that vapor return/combustion is used.

#### RECOMMENDATION TO DIRECTOR

The information provided in the permit application indicates Chesapeake Appalachia LLC's natural gas well pad site should meet applicable requirements of state rules and federal regulations. It is recommended that Chesapeake Appalachia's proposed Mason Cottrell Pad should be granted a 45CSR13 construction permit for their facility.

---

David Keatley  
Permit Writer

---

Date

Fact Sheet R13-2960  
Chesapeake Appalachia, LLC  
Mason Cottrell Pad