

JAY-BEE OIL & GAS, INC.

APPLICATION FOR GENERAL PERMIT

**Moe Well Pad Production Facility
Tyler County, West Virginia**



98 Vanadium Road
Bridgeville, PA 15017
(412) 221-1100

APPLICATION FOR G70-C GENERAL PERMIT

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility

Tyler County, West Virginia

Table of Contents

I. Application Form

II. Attachments

- **Attachment A – Single Source Determination Form**
- **Attachment C – Current Business Certificate**
- **Attachment D – Process Flow Diagram**
- **Attachment E – Process Description**
- **Attachment F – Plot Plan**
- **Attachment G – Area Map**
- **Attachment H – G70-C Section Applicability Form**
- **Attachment I – Emission Units/ERD Table**
- **Attachment J – Fugitive Emissions Summary Sheet**
- **Attachment K – Gas Well Affected Facility Data Sheet**
- **Attachment L – Storage Vessels Data Sheet(s)**
- **Attachment M – Natural Gas Fired Fuel Burning Units Data Sheet(s)**
- **Attachment N – Internal Combustion Engine Data Sheet(s)**
- **Attachment O – Tanker Truck Loading Data Sheet(s)**
- **Attachment P – Glycol Dehydration Unit Data Sheet(s)**
- **Attachment R – Air Pollution Control Device Sheet(s)**
- **Attachment S – Emission Calculations**
- **Attachment T – Facility-wide Emission Summary Sheet(s)**
- **Attachment U – Class I Legal Advertisement**

SECTION I

Application Form



West Virginia Department of Environmental Protection

Division of Air Quality
601 57th Street SE
Charleston, WV 25 4
Phone (304) 926-0475
Fax (304) 926-0479
www.dep.wv.gov

G70-C GENERAL PERMIT REGISTRATION APPLICATION

PREVENTION AND CONTROL OF AIR POLLUTION IN REGARD TO THE CONSTRUCTION, MODIFICATION,
RELOCATION, ADMINISTRATIVE UPDATE AND OPERATION OF
NATURAL GAS PRODUCTION FACILITIES LOCATED AT THE WELL SITE

☒ CONSTRUCTION
☐ MODIFICATION
☐ RELOCATION

☐ CLASS I ADMINISTRATIVE UPDATE
☐ CLASS II ADMINISTRATIVE UPDATE

SECTION 1. GENERAL INFORMATION

Name of Applicant (as registered with the WV Secretary of State's Office): **Jay-Bee Oil & Gas, Inc.**

Federal Employer ID No. (FEIN): **55-073-8862**

Applicant's Mailing Address: **3570 Shields Hill Rd**

City: **Cairo**

State: **WV**

ZIP Code: **26337**

Facility Name: **Moe Well Pad Production Facility**

Operating Site Physical Address: **Off Klondike Acres Rd**
If none available, list road, city or town and zip of facility.

City: **Middlebourne**

Zip Code: **26149**

County: **Tyler**

Latitude & Longitude Coordinates (NAD83, Decimal Degrees to 5 digits):

Latitude: **39.46791**

Longitude: **-80.88719**

SIC Code: **1311**

DAQ Facility ID No. (For existing facilities)

NAICS Code: **211111**

CERTIFICATION OF INFORMATION

This G70-C General Permit Registration Application shall be signed below by a Responsible Official. A Responsible Official is a President, Vice President, Secretary, Treasurer, General Partner, General Manager, a member of the Board of Directors, or Owner, depending on business structure. A business may certify an Authorized Representative who shall have authority to bind the Corporation, Partnership, Limited Liability Company, Association, Joint Venture or Sole Proprietorship. Required records of daily throughput, hours of operation and maintenance, general correspondence, compliance certifications and all required notifications must be signed by a Responsible Official or an Authorized Representative. If a business wishes to certify an Authorized Representative, the official agreement below shall be checked off and the appropriate names and signatures entered. **Any administratively incomplete or improperly signed or unsigned G70-C Registration Application will be returned to the applicant. Furthermore, if the G70-C forms are not utilized, the application will be returned to the applicant. No substitution of forms is allowed.**

I hereby certify that _____ is an Authorized Representative and in that capacity shall represent the interest of the business (e.g., Corporation, Partnership, Limited Liability Company, Association Joint Venture or Sole Proprietorship) and may obligate and legally bind the business. If the business changes its Authorized Representative, a Responsible Official shall notify the Director of the Division of Air Quality immediately.

I hereby certify that all information contained in this G70-C General Permit Registration Application and any supporting documents appended hereto is, to the best of my knowledge, true, accurate and complete, and that all reasonable efforts have been made to provide the most comprehensive information possible.

Responsible Official Signature: _____

Name and Title: **Office Manager**

Email: **sdowell@jaybeoil.com**

Phone: **304-628-3119**

Fax: _____

Date: **8-17-16**

If applicable:

Authorized Representative Signature: _____

Name and Title:

Phone:

Fax:

Email:

Date:

If applicable:

Environmental Contact

Name and Title:

Phone:

Fax:

Email:

Date:

OPERATING SITE INFORMATION	
Briefly describe the proposed new operation and/or any change(s) to the facility: Natural gas production and separation of liquids. Then, the facility will dehydrate the gas and inject it into a gather line owned and operated by others.	
Directions to the facility: From Middlebourne, proceed southwest on State Route 18 (Main Street) out of town. Turn right onto Bridgeway Rd. Turn left onto Wick Rd and follow for approximately 2.0 miles. Turn left onto Klondike Acres Rd and follow for approximately 2.5 miles to well pad entrance.	
ATTACHMENTS AND SUPPORTING DOCUMENTS	
I have enclosed the following required documents:	
Check payable to WVDEP – Division of Air Quality with the appropriate application fee (per 45CSR13 and 45CSR22).	
<input checked="" type="checkbox"/> Check attached to front of application. <input type="checkbox"/> I wish to pay by electronic transfer. Contact for payment (incl. name and email address): <input type="checkbox"/> I wish to pay by credit card. Contact for payment (incl. name and email address):	
<input checked="" type="checkbox"/> \$500 (Construction, Modification, and Relocation) <input type="checkbox"/> \$300 (Class II Administrative Update) <input checked="" type="checkbox"/> \$1,000 NSPS fee for 40 CFR60, Subpart IIII, JJJJ and/or OOOO ¹ <input checked="" type="checkbox"/> \$2,500 NESHAP fee for 40 CFR63, Subpart ZZZZ and/or HH ²	
¹ Only one NSPS fee will apply. ² Only one NESHAP fee will apply. The Subpart ZZZZ NESHAP fee will be waived for new engines that satisfy requirements by complying with NSPS, Subparts IIII and/or JJJJ. <i>NSPS and NESHAP fees apply to new construction or if the source is being modified.</i>	
<input checked="" type="checkbox"/> Responsible Official or Authorized Representative Signature (if applicable)	
<input checked="" type="checkbox"/> Single Source Determination Form (must be completed in its entirety) – Attachment A	
<input type="checkbox"/> Siting Criteria Waiver (if applicable) – Attachment B	<input checked="" type="checkbox"/> Current Business Certificate – Attachment C
<input checked="" type="checkbox"/> Process Flow Diagram – Attachment D	<input checked="" type="checkbox"/> Process Description – Attachment E
<input checked="" type="checkbox"/> Plot Plan – Attachment F	<input checked="" type="checkbox"/> Area Map – Attachment G
<input checked="" type="checkbox"/> G70-C Section Applicability Form – Attachment H	<input checked="" type="checkbox"/> Emission Units/ERD Table – Attachment I
<input checked="" type="checkbox"/> Fugitive Emissions Summary Sheet – Attachment J	
<input checked="" type="checkbox"/> Gas Well Affected Facility Data Sheet (if applicable) – Attachment K	
<input checked="" type="checkbox"/> Storage Vessel(s) Data Sheet (include gas sample data, USEPA Tanks, simulation software (e.g. ProMax, E&P Tanks, HYSYS, etc.), etc. where applicable) – Attachment L	
<input checked="" type="checkbox"/> Natural Gas Fired Fuel Burning Unit(s) Data Sheet (GPUs, Heater Treaters, In-Line Heaters if applicable) – Attachment M	
<input checked="" type="checkbox"/> Internal Combustion Engine Data Sheet(s) (include manufacturer performance data sheet(s) if applicable) – Attachment N	
<input checked="" type="checkbox"/> Tanker Truck Loading Data Sheet (if applicable) – Attachment O	
<input checked="" type="checkbox"/> Glycol Dehydration Unit Data Sheet(s) (include wet gas analysis, GRI- GLYCalc™ input and output reports and information on reboiler if applicable) – Attachment P	
<input type="checkbox"/> Pneumatic Controllers Data Sheet – Attachment Q	
<input checked="" type="checkbox"/> Air Pollution Control Device/Emission Reduction Device(s) Sheet(s) (include manufacturer performance data sheet(s) if applicable) – Attachment R	
<input checked="" type="checkbox"/> Emission Calculations (please be specific and include all calculation methodologies used) – Attachment S	
<input checked="" type="checkbox"/> Facility-wide Emission Summary Sheet(s) – Attachment T	
<input checked="" type="checkbox"/> Class I Legal Advertisement – Attachment U	
<input checked="" type="checkbox"/> One (1) paper copy and two (2) copies of CD or DVD with pdf copy of application and attachments	

All attachments must be identified by name, divided into sections, and submitted in order.

SECTION II

Attachments

ATTACHMENT A

Single Source Determination Form

ATTACHMENT A - SINGLE SOURCE DETERMINATION FORM

Classifying multiple facilities as one “stationary source” under 45CSR13, 45CSR14, and 45CSR19 is based on the definition of Building, structure, facility, or installation as given in §45-14-2.13 and §45-19-2.12. The definition states:

“Building, Structure, Facility, or Installation” means all of the pollutant-emitting activities which belong to the same industrial grouping, are located on one or more contiguous or adjacent properties, and are under the control of the same person (or persons under common control). Pollutant-emitting activities are a part of the same industrial grouping if they belong to the same “Major Group” (i.e., which have the same two (2)-digit code) as described in the Standard Industrial Classification Manual, 1987 (United States Government Printing Office stock number GPO 1987 0-185-718:QL 3).

Is there a facility owned by or associated with the natural gas industry located within one (1) mile of the proposed facility? Yes ☒ No ☐

If Yes, please complete the questionnaire on the following page (Attachment A).

Please provide a source aggregation analysis for the proposed facility below:

The closest Jay-Bee facility to the Moe Well Pad Production Facility is the Larry Well Pad Production Facility. This facility is under the same SIC code and may, from time to time, have a sharing of staff. These two well pads are approximately 3,130 feet (0.59 miles) apart, and they are on the same (very large) parcel. There is no interconnection or interdependency between these two facilities. Gas from one well pad does not flow to the other. Accordingly, the operation of one well pad is not dependent upon the operation of the other. Thus, given the lack of dependency and the distance of separation, emissions from these two well pads should not be aggregated.

ATTACHMENT A - SINGLE SOURCE DETERMINATION FORM

Answer each question with a detailed explanation to determine contiguous or adjacent properties which are under a common control and any support facilities. This section must be completed in its entirety.

Provide a map of contiguous or adjacent facilities (production facilities, compressor stations, dehydration facilities, etc.) which are under common control and those facilities that are not under common control but are support facilities. Please indicate the SIC code, permit number (if applicable), and the distance between facilities in question on the map.

Are the facilities owned by the same parent company or a subsidiary of the parent company? Provide the owners identity and the percentage of ownership of each facility. Jay-Bee Oil & Gas owns 100%	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Does an entity such as a corporation have decision making authority over the operation of a second entity through a contractual agreement or voting interest? Please explain.	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Is there a contract for service relationship between the two (2) companies or, a support/dependency relationship that exists between the two (2) companies? Please explain. Jay-Bee Oil & Gas owns both.	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Do the facilities share common workforces, plant managers, security forces, corporate executive officers or board executives?	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Will managers or other workers frequently shuttle back and forth to be involved actively at both facilities?	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Do the facilities share common payroll activities, employee benefits, health plans, retirement funds, insurance coverage, or other administrative functions? Please explain. Jay-Bee Oil & Gas owns and operates both facilities.	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Does one (1) facility operation support the operation of the other facility?	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Is one (1) facility dependent on the other? If one (1) facility shuts down, what are the limitations on the other to pursue outside business? Please explain. No limitations on either facility if the other were to shutdown.	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Are there any financial arrangements between the two (2) entities? Jay-Bee Oil & Gas owns and operates both facilities.	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Are there any legal or lease agreements between the two (2) facilities? Jay-Bee Oil & Gas owns and operates both facilities.	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Do the facilities share products, byproducts, equipment, or other manufacturing or air pollution control device equipment? Please explain. Well pads operate independently.	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Do all the pollutant-emitting activities at the facilities belong to the same SIC Code? Please provide the SIC Codes. 1311	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
Was the location of the new facility chosen primarily because of its proximity to the existing facility to integrate the operation of the two (2) facilities? Please explain.	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Will materials be routinely transferred between the two (2) facilities? Please explain the amount of transfer and how often the transfers take place and what percentages go to the various entities.	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Does the facility influence production levels or compliance with environmental regulations at other facilities? Who accepts the responsibility for compliance with air quality requirements? Please explain. No, facilities operate independently. Jay-Bee Oil & Gas Office Manager is responsible for Air Quality Requirements for both facilities.	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>

ATTACHMENT C

Current Business Certificate

**WEST VIRGINIA
STATE TAX DEPARTMENT
BUSINESS REGISTRATION
CERTIFICATE**

ISSUED TO:
**JAY-BEE OIL & GAS INC
RR 1 BOX 5
CAIRO, WV 26337-9701**

BUSINESS REGISTRATION ACCOUNT NUMBER 1043-4424

This certificate is issued on: **06/11/2010**

This certificate is issued by
the West Virginia State Tax Commissioner
in accordance with W. Va. Code § 11-12

The person or organization identified on this certificate is registered
to conduct business in the State of West Virginia at the location above.

This certificate is not transferrable and must be displayed at the location for which issued.

This certificate shall be permanent until cessation of the business for which the certificate of registration
was granted or until it is suspended, revoked or cancelled by the Tax Commissioner.

Change in name or change of location shall be considered a cessation of the business and a new
certificate shall be required.

TRAVELING STREET VENDORS: Must carry a copy of this certificate in every vehicle operated by them.

CONTRACTORS, DRILLING OPERATORS, TIMBER/LOGGING OPERATIONS: Must have a copy of
this certificate displayed at every job site within West Virginia.

all.008 v.1
L1388180484


SCANNED

JUN 14 10

JUN 14 2010
WV

ATTACHMENT D

Process Flow Diagram



DRAWN BY	DJF
DATE	8/16/16
CHECKED BY	LFM
SET JOB NO.	214054-19
SET DWG FILE	MOE FDb01.dwg
DRAWING SCALE	N.T.S.



98 Vanadium Road Bridgeville, PA 15017 (412) 221-1100

JAY-BEE OIL & GAS, INC.
MOE WELL PRODUCTION FACILITY
TYLER COUNTY, WEST VIRGINIA
PROCESS FLOW DIAGRAM

DRAWING NAME

FIGURE 3

REV.

2

ATTACHMENT E

Process Description

Jay-Bee Oil & Gas, Incorporated
Moe Well Pad Production Facility
Attachment E
Process Description

At this facility, Natural gas and Produced Fluids (condensate and water) will be received from three wells and passed through Gas Processing Units (one per Marcellus well and two per Utica well) to avoid ice formation during subsequent pressure drops. These materials will then pass through a three-way separator where gas, condensate and water are separated. All gas fired equipment will use natural gas produced at the site as fuel. The Facility will then dehydrate the gas and then injected into a gathering pipeline owned and operated by others.

Both Condensate and Produced Water will be accumulated in six (6) 210 BBL tanks (three for Condensate and three for Produced Water), pending truck transportation by others. The Condensate will be transported to a regional processing facility and the Produced Water will be transported to a regional disposal facility. Flash, working and breathing losses from these tanks will be routed to a Vapor Recovery Unit (VRU) with the captured vapors routed back to the raw gas discharge line. An enclosed combustor will be utilized as a backup control device for times when the VRU is not available, and will also be utilized if a large slug of condensate production generates flash gas in excess of the capacity of the VRU. A capture and control efficiency of 98% is being claimed for this overall combination of controls.

The dehydration unit will generate emissions from the still vent and re-boiler. There is no flash tank. Vapors from the still vent will be comprised of water and various low molecular weight hydrocarbons. Still vent vapors will be routed to an enclosed combustor. A capture and control efficiency of 98% is being claimed for the combustor. Although needs are anticipated to be minimal, supplemental re-boiler fuel is available from the dehydrated gas stream prior to injection into the sales line. Any water condensing in the still vent column will be routed to the wastewater tanks.


Lastly, Jay-Bee is seeking approval for installation of a Thermo-electric generator to meet the minor electric demands for various monitoring and data tracking equipment.


In summary, upon approval of this application, emission sources at this facility will include the following:

- Three Gas Processing Units (GPUs), each with a 1.5 MMBTU/hr heater (Sources 1E, 2E and 3E).
- One Line Heater (Source 4E).
- Condensate Truck Loading (Source 5E)
- Produced Water Truck Loading (Source 6E)
- One Vapor Recovery Unit (VRU) with driver engine (Source 7E), controlling emissions from T01-T06.
- One Thermo-electric Generator (Source 8E)
- Backup Enclosed Combustor for VRU (Source 9E)
- Three Produced Water Tanks (T01-T03)
- Three Condensate Tanks (T04-T06)
- Dehydration Unit (Source 10E – reboiler vent and 11E – still vent)
- Enclosed Combustor for control of still vent (Source 11E)

ATTACHMENT F


Plot Plan



DRAWN BY	DJF	JAY-BEE OIL & GAS, INC.	
DATE	8/16/16	MOE WELL PRODUCTION FACILITY	
CHECKED BY	LFM	TYLER COUNTY, WEST VIRGINIA	
SET JOB NO.	214054-19	SITE LAYOUT PLAN	
SET DWG FILE	MOEa01.dwg	DRAWING NAME	FIGURE 2
DRAWING SCALE	N.T.S.	REV.	0
		98 Vanadium Road Bridgeville, PA 15017 (412) 221-1100	

ATTACHMENT G

Area Map



REFERENCE: USGS 7.5' QUADRANGLE MAP OF: MIDDLEBOURNE, WEST VIRGINIA; DATED 1960, PHOTOREVISED 1976.

DRAWN BY DJF
DATE 7/11/16
CHECKED BY RAD
SET JOB NO. 214054
SET DWG FILE LARRY & MOEm01.dwg
DRAWING SCALE 1"=2000'



98 Vonadium Road Bridgeville, PA 15017 (412) 221-1100

JAY-BEE OIL & GAS, INC.

LARRY & MOE WELL PADS
TYLER COUNTY, WEST VIRGINIA
SITE LOCATION MAP

DRAWING NO.

FIGURE 1



REV.

0

Radius Map - 300 ft

Moe Well Pad Production Facility

Legend

-  300 ft Radius
-  Moe

Moe

Google earth

© 2016 Google

500 ft



ATTACHMENT H

G-70C Section Applicability Form

ATTACHMENT H – G70-C SECTION APPLICABILITY FORM

General Permit G70-C Registration Section Applicability Form

General Permit G70-C was developed to allow qualified applicants to seek registration for a variety of sources. These sources include gas well affected facilities, storage vessels, gas production units, in-line heaters, heater treaters, glycol dehydration units and associated reboilers, pneumatic controllers, centrifugal compressors, reciprocating compressors, reciprocating internal combustion engines (RICEs), tank truck loading, fugitive emissions, completion combustion devices, flares, enclosed combustion devices, and vapor recovery systems. All registered facilities will be subject to Sections 1.0, 2.0, 3.0, and 4.0.

General Permit G70-C allows the registrant to choose which sections of the permit they are seeking registration under. Therefore, please mark which additional sections that you are applying for registration under. If the applicant is seeking registration under multiple sections, please select all that apply. Please keep in mind, that if this registration is approved, the issued registration will state which sections will apply to your affected facility.

GENERAL PERMIT G70-C APPLICABLE SECTIONS	
<input checked="" type="checkbox"/> Section 5.0	Gas Well Affected Facility (NSPS, Subpart OOOO)
<input checked="" type="checkbox"/> Section 6.0	Storage Vessels Containing Condensate and/or Produced Water ¹
<input type="checkbox"/> Section 7.0	Storage Vessel Affected Facility (NSPS, Subpart OOOO)
<input checked="" type="checkbox"/> Section 8.0	Control Devices and Emission Reduction Devices not subject to NSPS Subpart OOOO and/or NESHAP Subpart HH
<input checked="" type="checkbox"/> Section 9.0	Small Heaters and Reboilers not subject to 40CFR60 Subpart Dc
<input type="checkbox"/> Section 10.0	Pneumatic Controllers Affected Facility (NSPS, Subpart OOOO)
<input type="checkbox"/> Section 11.0	Centrifugal Compressor Affected Facility (NSPS, Subpart OOOO) ²
<input checked="" type="checkbox"/> Section 12.0	Reciprocating Compressor Affected Facility (NSPS, Subpart OOOO) ²
<input checked="" type="checkbox"/> Section 13.0	Reciprocating Internal Combustion Engines, Generator Engines, Microturbines
<input checked="" type="checkbox"/> Section 14.0	Tanker Truck Loading ³
<input checked="" type="checkbox"/> Section 15.0	Glycol Dehydration Units ⁴

¹ Applicants that are subject to Section 6 may also be subject to Section 7 if the applicant is subject to the NSPS, Subpart OOOO control requirements or the applicable control device requirements of Section 8.

² Applicants that are subject to Section 11 and 12 may also be subject to the applicable RICE requirements of Section 13.

³ Applicants that are subject to Section 14 may also be subject to control device and emission reduction device requirements of Section 8.

⁴ Applicants that are subject to Section 15 may also be subject to the requirements of Section 9 (reboilers). Applicants that are subject to Section 15 may also be subject to control device and emission reduction device requirements of Section 8.

ATTACHMENT I

Emissions Units/ERD Table

ATTACHMENT I – EMISSION UNITS / EMISSION REDUCTION DEVICES (ERD) TABLE

Include ALL emission units and air pollution control devices/ERDs that will be part of this permit application review. Do not include fugitive emission sources in this table. Deminimis storage tanks shall be listed in the Attachment L table. This information is required for all sources regardless of whether it is a construction, modification, or administrative update.

Emission Unit ID ¹	Emission Point ID ²	Emission Unit Description	Year Installed	Manufac. Date ³	Design Capacity	Type ⁴ and Date of Change	Control Device(s) ⁵	ERD(s) ⁶
HTR-1	1E	Gas Processing Unit	TBD		1.5 MMBTU/hr	NEW	None	None
HTR-2	2E	Gas Processing Unit	TBD		1.5 MMBTU/hr	NEW	None	None
HTR-3	3E	Gas Processing Unit	TBD		1.5 MMBTU/hr	NEW	None	None
HTR-4	4E	Line Heater	TBD		0.5 MMBTU/hr	NEW	None	None
TL-1	5E	Condensate Truck Loading	TBD		30,000 BBL/yr	NEW	None	None
TL-2	6E	Produced Water Truck Loading	TBD		63,600 BBL/yr	NEW	None	None
VRU-1	7E	VRU Driver	TBD	3/19/12	84 HP	NEW	1C	None
TEG-1	8E	Thermoelectric Generator	TBD		4.4 KW/hr	NEW	None	None
EC-1	9E	Enclosed Combustor	TBD		10.0 MMBTU/hr	NEW	N/A	None
T01	7E/9E	Condensate Tank	TBD		210 BBL	NEW	EC-1	VRU-1
T02	7E/9E	Condensate Tank	TBD		210 BBL	NEW	EC-1	VRU-1
T03	7E/9E	Condensate Tank	TBD		210 BBL	NEW	EC-1	VRU-1
T04	7E/9E	Produce Water Tank	TBD		210 BBL	NEW	EC-1	VRU-1
T05	7E/9E	Produced Water Tank	TBD		210 BBL	NEW	EC-1	VRU-1
T06	7E/9E	Produced Water Tank	TBD		210 BBL	NEW	EC-1	VRU-1
RBV-1	10E	Dehydration Unit Re-boiler Vent	TBD		0.500 MMBTU/hr	NEW	None	None
RSV-1	11E	Dehydration Unit Still Vent	TBD		40 MMSCFD	NEW	EC-2	None
EC-2	11E	Enclosed Combustor	TBD		10.0 MMBTU/hr	NEW	None	None

¹ For Emission Units (or Sources) use the following numbering system: 1S, 2S, 3S,... or other appropriate designation.

² For Emission Points use the following numbering system: 1E, 2E, 3E, ... or other appropriate designation.

³ When required by rule

⁴ New, modification, removal, existing

⁵ For Control Devices use the following numbering system: 1C, 2C, 3C,... or other appropriate designation.

⁶ For ERDs use the following numbering system: 1D, 2D, 3D,... or other appropriate designation.

ATTACHMENT J

Fugitive Emissions Summary Sheet

ATTACHMENT J – FUGITIVE EMISSIONS SUMMARY SHEET							
Sources of fugitive emissions may include loading operations, equipment leaks, blowdown emissions, etc.							
Source/Equipment:							
Leak Detection Method Used		<input checked="" type="checkbox"/> Audible, visual, and olfactory (AVO) inspections		<input type="checkbox"/> Infrared (FLIR) cameras	<input type="checkbox"/> Other (please describe)		<input type="checkbox"/> None required
Component Type	Closed Vent System	Count	Source of Leak Factors (EPA, other (specify))	Stream type (gas, liquid, etc.)	Estimated Emissions (tpy)		
					VOC	HAP	GHG (CO ₂ e)
Pumps	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	1	API	<input checked="" type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both	<0.01	<0.01	0.34
Valves	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	44	EPA	<input type="checkbox"/> Gas <input type="checkbox"/> Liquid <input checked="" type="checkbox"/> Both	0.26	<0.01	2.65
Safety Relief Valves	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	3	EPA	<input type="checkbox"/> Gas <input type="checkbox"/> Liquid <input checked="" type="checkbox"/> Both	0.01	<0.01	0.45
Open Ended Lines	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	20	EPA	<input checked="" type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both	0.06	<0.01	4.60
Sampling Connections	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	17	TECQ	<input type="checkbox"/> Gas <input type="checkbox"/> Liquid <input checked="" type="checkbox"/> Both	1.16	0.01	25.60
Connections (Not sampling)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	180	EPA	<input type="checkbox"/> Gas <input type="checkbox"/> Liquid <input checked="" type="checkbox"/> Both	0.12	<0.01	1.36
Compressors	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	1	API	<input checked="" type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both	0.02	<0.01	1.26
Flanges	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	120	API	<input type="checkbox"/> Gas <input type="checkbox"/> Liquid <input checked="" type="checkbox"/> Both	0.09	<0.01	4.47
Other ¹	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	16	n/a	<input checked="" type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both	0.04	<0.01	0.055

¹ Other equipment types may include compressor seals, relief valves, diaphragms, drains, meters, etc.

Please provide an explanation of the sources of fugitive emissions (e.g. pigging operations, equipment blowdowns, pneumatic controllers, etc.):
Blowdowns

Please indicate if there are any closed vent bypasses (include component):
No

Specify all equipment used in the closed vent system (e.g. VRU, ERD, thief hatches, tanker truck loading, etc.)
Thief Hatch, VRU and Enclosed Combustors

ATTACHMENT K

Gas Well Affected Facility Data Sheet

ATTACHMENT K – GAS WELL AFFECTED FACILITY DATA SHEET

Complete this data sheet if you are the owner or operator of a gas well affected facility for which construction, modification or reconstruction commenced after August 23, 2011. This form must be completed for natural gas well affected facilities regardless of when flowback operations occur (or have occurred).

API Number	Date of Flowback	Date of Well Completion	Green Completion and/or Combustion Device
47-095-02321	December 2016	TBD	Flow to separator and into gathering line as soon as practical.
47-095-02322	December 2016	TBD	Flow to separator and into gathering line as soon as practical.

Note: If future wells are planned and no API number is available please list as PLANNED. If there are existing wells that commenced construction prior to August 23, 2011, please acknowledge as existing.

This is the same API (American Petroleum Institute) well number(s) provided in the well completion notification and as provided to the WVDEP, Office of Oil and Gas for the well permit. The API number may be provided on the application without the state code (047).

Every oil and gas well permitted in West Virginia since 1929 has been issued an API number. This API is used by agencies to identify and track oil and gas wells.

The API number has the following format: 047-001-00001

Where,

*047 = State code. The state code for WV is 047.
001 = County Code. County codes are odd numbers, beginning with 001 (Barbour) and continuing to 109 (Wyoming).
00001= Well number. Each well will have a unique well number.*

ATTACHMENT L

Storage Vessels Data Sheet(s)

ATTACHMENT L – STORAGE VESSEL DATA SHEET

Complete this data sheet if you are the owner or operator of a storage vessel that contains condensate and/or produced water. This form must be completed for *each* new or modified bulk liquid storage vessel(s) that contains condensate and/or produced water. (If you have more than one (1) identical tank (i.e. 4-400 bbl condensate tanks), then you can list all on one (1) data sheet). **Include gas sample analysis, flashing emissions, working and breathing losses, USEPA Tanks, simulation software (ProMax, E&P Tanks, HYSYS, etc.), and any other supporting documents where applicable.**

The following information is REQUIRED:

- ☐ Composition of the representative sample used for the simulation
- ☐ For each stream that contributes to flashing emissions:
 - ☐ Temperature and pressure (inlet and outlet from separator(s))
 - ☐ Simulation-predicted composition
 - ☐ Molecular weight
 - ☐ Flow rate
- ☐ Resulting flash emission factor or flashing emissions from simulation
- ☐ Working/breathing loss emissions from tanks and/or loading emissions if simulation is used to quantify those emissions

Additional information may be requested if necessary.

GENERAL INFORMATION (REQUIRED)

1. Bulk Storage Area Name Moe Tank Farm	2. Tank Name T01-T03
3. Emission Unit ID number N/A Vapors to combustors, emission point 9E	4. Emission Point ID number 7E/9E
5. Date Installed , Modified or Relocated (<i>for existing tanks</i>) Pending Permit Approval Was the tank manufactured after August 23, 2011? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	6. Type of change: <input checked="" type="checkbox"/> New construction <input type="checkbox"/> New stored material <input type="checkbox"/> Other <input type="checkbox"/> Relocation
7A. Description of Tank Modification (<i>if applicable</i>)	
7B. Will more than one material be stored in this tank? <i>If so, a separate form must be completed for each material.</i> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
7C. Was USEPA Tanks simulation software utilized? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>If Yes, please provide the appropriate documentation and items 8-42 below are not required.</i>	

TANK INFORMATION

8. Design Capacity (<i>specify barrels or gallons</i>). Use the internal cross-sectional area multiplied by internal height. 210 BBL	
9A. Tank Internal Diameter (ft.) 12.5	9B. Tank Internal Height (ft.) 15
10A. Maximum Liquid Height (ft.) 14	10B. Average Liquid Height (ft.) 10
11A. Maximum Vapor Space Height (ft.) 14	11B. Average Vapor Space Height (ft.) 7
12. Nominal Capacity (<i>specify barrels or gallons</i>). This is also known as “working volume”. 196 BBL	
13A. Maximum annual throughput (gal/yr) 420,000	13B. Maximum daily throughput (gal/day) 7,000
14. Number of tank turnovers per year 51	15. Maximum tank fill rate (gal/min) 50
16. Tank fill method <input type="checkbox"/> Submerged <input type="checkbox"/> Splash <input checked="" type="checkbox"/> Bottom Loading	
17. Is the tank system a variable vapor space system? <input type="checkbox"/> Yes <input type="checkbox"/> No	

If yes, (A) What is the volume expansion capacity of the system (gal)?
 (B) What are the number of transfers into the system per year?

18. Type of tank (check all that apply):

☒ Fixed Roof ☐ vertical ☐ horizontal ☐ flat roof ☐ cone roof ☐ dome roof ☐ other (describe)

☐ External Floating Roof ☐ pontoon roof ☐ double deck roof

☐ Domed External (or Covered) Floating Roof

☐ Internal Floating Roof ☐ vertical column support ☐ self-supporting

☐ Variable Vapor Space ☐ lifter roof ☐ diaphragm

☐ Pressurized ☐ spherical ☐ cylindrical

☐ Other (describe)

PRESSURE/VACUUM CONTROL DATA

19. Check as many as apply:

☐ Does Not Apply ☐ Rupture Disc (psig)

☐ Inert Gas Blanket of _____ ☐ Carbon Adsorption¹

☒ Vent to Vapor Combustion Device¹ (vapor combustors, flares, thermal oxidizers, enclosed combustors) **as back-up to VRU**

☒ Conservation Vent (psig) ☐ Condenser¹

0.4 oz. Vacuum Setting **14 oz.** Pressure Setting

☐ Emergency Relief Valve (psig)

 Vacuum Setting Pressure Setting

☒ Thief Hatch Weighted ☒ Yes ☐ No

¹ Complete appropriate Air Pollution Control Device Sheet

20. Expected Emission Rate (submit Test Data or Calculations here or elsewhere in the application).

Material Name	Flashing Loss		Breathing Loss		Working Loss		Total Emissions Loss		Estimation Method ¹
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	
VOC (uncontrolled)	90.09	394.59	0.11	0.48	0.38	1.66	90.6	396.7	MB and EPA
HAP (uncontrolled)	2.94	12.88	<0.01	0.02	0.01	0.05	2.96	12.95	MB

¹ EPA = EPA Emission Factor, MB = Material Balance, SS = Similar Source, ST = Similar Source Test, Throughput Data, O = Other (specify)
 Remember to attach emissions calculations, including TANKS Summary Sheets and other modeling summary sheets if applicable.

TANK CONSTRUCTION AND OPERATION INFORMATION		
21. Tank Shell Construction:		
<input type="checkbox"/> Riveted <input type="checkbox"/> Gunit lined <input type="checkbox"/> Epoxy-coated rivets <input checked="" type="checkbox"/> Other (describe) Welded		
21A. Shell Color: Blue	21B. Roof Color: Blue	21C. Year Last Painted: NEW
22. Shell Condition (if metal and unlined):		
<input checked="" type="checkbox"/> No Rust <input type="checkbox"/> Light Rust <input type="checkbox"/> Dense Rust <input type="checkbox"/> Not applicable		
22A. Is the tank heated? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	22B. If yes, operating temperature:	22C. If yes, how is heat provided to tank?
23. Operating Pressure Range (psig): 2 oz – 14 oz Must be listed for tanks using VRUs with closed vent system.		
24. Is the tank a Vertical Fixed Roof Tank ? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	24A. If yes, for dome roof provide radius (ft):	24B. If yes, for cone roof, provide slop (ft/ft):
25. Complete item 25 for Floating Roof Tanks <input type="checkbox"/> Does not apply <input checked="" type="checkbox"/>		
25A. Year Internal Floaters Installed:		
25B. Primary Seal Type (check one): <input type="checkbox"/> Metallic (mechanical) shoe seal <input type="checkbox"/> Liquid mounted resilient seal		

<input type="checkbox"/> Vapor mounted resilient seal <input type="checkbox"/> Other (describe):			
25C. Is the Floating Roof equipped with a secondary seal? <input type="checkbox"/> Yes <input type="checkbox"/> No			
25D. If yes, how is the secondary seal mounted? (<i>check one</i>) <input type="checkbox"/> Shoe <input type="checkbox"/> Rim <input type="checkbox"/> Other (describe):			
25E. Is the floating roof equipped with a weather shield? <input type="checkbox"/> Yes <input type="checkbox"/> No			
25F. Describe deck fittings:			
26. Complete the following section for Internal Floating Roof Tanks <input checked="" type="checkbox"/> Does not apply			
26A. Deck Type: <input type="checkbox"/> Bolted <input type="checkbox"/> Welded		26B. For bolted decks, provide deck construction:	
26C. Deck seam. Continuous sheet construction: <input type="checkbox"/> 5 ft. wide <input type="checkbox"/> 6 ft. wide <input type="checkbox"/> 7 ft. wide <input type="checkbox"/> 5 x 7.5 ft. wide <input type="checkbox"/> 5 x 12 ft. wide <input type="checkbox"/> other (describe)			
26D. Deck seam length (ft.):	26E. Area of deck (ft ²):	26F. For column supported tanks, # of columns:	26G. For column supported tanks, diameter of column:
27. Closed Vent System with VRU? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No			
28. Closed Vent System with Enclosed Combustor? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Back-up to VRU			
SITE INFORMATION			
29. Provide the city and state on which the data in this section are based:			
30. Daily Avg. Ambient Temperature (°F):		31. Annual Avg. Maximum Temperature (°F):	
32. Annual Avg. Minimum Temperature (°F):		33. Avg. Wind Speed (mph):	
34. Annual Avg. Solar Insulation Factor (BTU/ft ² -day):		35. Atmospheric Pressure (psia):	
LIQUID INFORMATION			
36. Avg. daily temperature range of bulk liquid (°F): 60	36A. Minimum (°F): 36	36B. Maximum (°F):	
37. Avg. operating pressure range of tank (psig): 0-0.5 psi	37A. Minimum (psig): <0.1 psi	37B. Maximum (psig): 0.8 psi	
38A. Minimum liquid surface temperature (°F): 36	38B. Corresponding vapor pressure (psia): 0.11		
39A. Avg. liquid surface temperature (°F): 65	39B. Corresponding vapor pressure (psia): 0.31		
40A. Maximum liquid surface temperature (°F): 100	40B. Corresponding vapor pressure (psia): 0.95		
41. Provide the following for each liquid or gas to be stored in the tank. Add additional pages if necessary.			
41A. Material name and composition:	Condensate		
41B. CAS number:	68919-39-1		
41C. Liquid density (lb/gal):	5.49		
41D. Liquid molecular weight (lb/lb-mole):	81.3		
41E. Vapor molecular weight (lb/lb-mole):	39.56		
41F. Maximum true vapor pressure (psia):			
41G. Maximum Reid vapor pressure (psia):	5.28		
41H. Months Storage per year. From: Jan To: Dec	12		
42. Final maximum gauge pressure and temperature prior to transfer into tank used as inputs into flashing emission calculations.			

GENERAL INFORMATION (REQUIRED)

1. Bulk Storage Area Name Moe Tank Farm	2. Tank Name T04-T06
3. Emission Unit ID number N/A Vapors to combustors, emission point 9E	4. Emission Point ID number 7E/9E
5. Date Installed , Modified or Relocated (for existing tanks) Pending Permit Approval Was the tank manufactured after August 23, 2011? <input type="checkbox"/> Yes <input type="checkbox"/> No	6. Type of change: <input checked="" type="checkbox"/> New construction <input type="checkbox"/> New stored material <input type="checkbox"/> Other <input type="checkbox"/> Relocation
7A. Description of Tank Modification (<i>if applicable</i>)	
7B. Will more than one material be stored in this tank? <i>If so, a separate form must be completed for each material.</i> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
7C. Was USEPA Tanks simulation software utilized? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>If Yes, please provide the appropriate documentation and items 8-42 below are not required.</i>	

TANK INFORMATION

8. Design Capacity (<i>specify barrels or gallons</i>). Use the internal cross-sectional area multiplied by internal height. 210 BBL	
9A. Tank Internal Diameter (ft.) 10	9B. Tank Internal Height (ft.) 15
10A. Maximum Liquid Height (ft.) 14	10B. Average Liquid Height (ft.) 8
11A. Maximum Vapor Space Height (ft.) 14.5	11B. Average Vapor Space Height (ft.) 7
12. Nominal Capacity (<i>specify barrels or gallons</i>). This is also known as "working volume". 190 BBL	
13A. Maximum annual throughput (gal/yr) 924,000 (each)	13B. Maximum daily throughput (gal/day) 5,000 (each)
14. Number of tank turnovers per year 116 (max)	15. Maximum tank fill rate (gal/min) 50
16. Tank fill method <input type="checkbox"/> Submerged <input checked="" type="checkbox"/> Splash <input type="checkbox"/> Bottom Loading	
17. Is the tank system a variable vapor space system? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If yes, (A) What is the volume expansion capacity of the system (gal)? (B) What are the number of transfers into the system per year?	
18. Type of tank (check all that apply): <input checked="" type="checkbox"/> Fixed Roof <input checked="" type="checkbox"/> vertical <input type="checkbox"/> horizontal <input type="checkbox"/> flat roof <input type="checkbox"/> cone roof <input type="checkbox"/> dome roof <input type="checkbox"/> other (describe) <input type="checkbox"/> External Floating Roof <input type="checkbox"/> pontoon roof <input type="checkbox"/> double deck roof <input type="checkbox"/> Domed External (or Covered) Floating Roof <input type="checkbox"/> Internal Floating Roof <input type="checkbox"/> vertical column support <input type="checkbox"/> self-supporting <input type="checkbox"/> Variable Vapor Space <input type="checkbox"/> lifter roof <input type="checkbox"/> diaphragm <input type="checkbox"/> Pressurized <input type="checkbox"/> spherical <input type="checkbox"/> cylindrical <input type="checkbox"/> Other (describe)	

PRESSURE/VACUUM CONTROL DATA

19. Check as many as apply:	
<input type="checkbox"/> Does Not Apply	<input type="checkbox"/> Rupture Disc (psig)
<input type="checkbox"/> Inert Gas Blanket of _____	<input type="checkbox"/> Carbon Adsorption ¹
<input checked="" type="checkbox"/> Vent to Vapor Combustion Device ¹ (vapor combustors, flares, thermal oxidizers, enclosed combustors) as back-up to VRU	
<input checked="" type="checkbox"/> Conservation Vent (psig)	<input type="checkbox"/> Condenser ¹
0.4 oz Vacuum Setting 14 oz Pressure Setting	
<input type="checkbox"/> Emergency Relief Valve (psig)	
Vacuum Setting	Pressure Setting
<input checked="" type="checkbox"/> Thief Hatch Weighted <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
¹ Complete appropriate Air Pollution Control Device Sheet	

20. Expected Emission Rate (submit Test Data or Calculations here or elsewhere in the application).									
Material Name	Flashing Loss		Breathing Loss		Working Loss		Total Emissions Loss		Estimation Method ¹
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	
VOC	0.88	3.84					0.88	3.84	MB
HAPs	0.07	0.32					0.07	0.32	MB

¹ EPA = EPA Emission Factor, MB = Material Balance, SS = Similar Source, ST = Similar Source Test, Throughput Data, O = Other (specify)
Remember to attach emissions calculations, including TANKS Summary Sheets and other modeling summary sheets if applicable.

TANK CONSTRUCTION AND OPERATION INFORMATION			
21. Tank Shell Construction: <input type="checkbox"/> Riveted <input type="checkbox"/> Gunite lined <input type="checkbox"/> Epoxy-coated rivets <input checked="" type="checkbox"/> Other (describe) Welded			
21A. Shell Color: Blue		21B. Roof Color: Blue	
21C. Year Last Painted: 2016			
22. Shell Condition (if metal and unlined): <input checked="" type="checkbox"/> No Rust <input type="checkbox"/> Light Rust <input type="checkbox"/> Dense Rust <input type="checkbox"/> Not applicable			
22A. Is the tank heated? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		22B. If yes, operating temperature:	
22C. If yes, how is heat provided to tank?			
23. Operating Pressure Range (psig): 2 oz – 14 oz Must be listed for tanks using VRUs with closed vent system.			
24. Is the tank a Vertical Fixed Roof Tank ? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		24A. If yes, for dome roof provide radius (ft): n/a	
24B. If yes, for cone roof, provide slop (ft/ft): n/a			
25. Complete item 25 for Floating Roof Tanks <input type="checkbox"/> Does not apply <input checked="" type="checkbox"/>			
25A. Year Internal Floaters Installed:			
25B. Primary Seal Type (<i>check one</i>): <input type="checkbox"/> Metallic (mechanical) shoe seal <input type="checkbox"/> Liquid mounted resilient seal <input type="checkbox"/> Vapor mounted resilient seal <input type="checkbox"/> Other (describe):			
25C. Is the Floating Roof equipped with a secondary seal? <input type="checkbox"/> Yes <input type="checkbox"/> No			
25D. If yes, how is the secondary seal mounted? (<i>check one</i>) <input type="checkbox"/> Shoe <input type="checkbox"/> Rim <input type="checkbox"/> Other (describe):			
25E. Is the floating roof equipped with a weather shield? <input type="checkbox"/> Yes <input type="checkbox"/> No			
25F. Describe deck fittings:			
26. Complete the following section for Internal Floating Roof Tanks <input checked="" type="checkbox"/> Does not apply			
26A. Deck Type: <input type="checkbox"/> Bolted <input type="checkbox"/> Welded		26B. For bolted decks, provide deck construction:	
26C. Deck seam. Continuous sheet construction: <input type="checkbox"/> 5 ft. wide <input type="checkbox"/> 6 ft. wide <input type="checkbox"/> 7 ft. wide <input type="checkbox"/> 5 x 7.5 ft. wide <input type="checkbox"/> 5 x 12 ft. wide <input type="checkbox"/> other (describe)			
26D. Deck seam length (ft.):	26E. Area of deck (ft ²):	26F. For column supported tanks, # of columns:	26G. For column supported tanks, diameter of column:
27. Closed Vent System with VRU? <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> No			
28. Closed Vent System with Enclosed Combustor? <input checked="" type="checkbox"/> Yes <input checked="" type="checkbox"/> No			
SITE INFORMATION Items 29 through 35 are N/A for Water Tank			
29. Provide the city and state on which the data in this section are based:			
30. Daily Avg. Ambient Temperature (°F):		31. Annual Avg. Maximum Temperature (°F):	

ATTACHMENT M

Natural Gas Fired Fuel Burning Units Data Sheet(s)

**ATTACHMENT M – SMALL HEATERS AND REBOILERS NOT SUBJECT TO
40CFR60 SUBPART DC
DATA SHEET**

Complete this data sheet for each small heater and reboiler not subject to 40CFR60 Subpart Dc at the facility. *The Maximum Design Heat Input (MDHI) must be less than 10 MMBTU/hr.*

Emission Unit ID# ¹	Emission Point ID# ²	Emission Unit Description (manufacturer, model #)	Year Installed/Modified	Type ³ and Date of Change	Maximum Design Heat Input (MMBTU/hr) ⁴	Fuel Heating Value (BTU/scf) ⁵
HTR-1	1E	Gas Processing Unit	TBD	NEW	1.5	1263
HTR-2	2E	Gas Processing Unit	TBD	NEW	1.5	1263
HTR-3	3E	Gas Processing Unit	TBD	NEW	1.5	1263
HTR-4	4E	Line Heater	TBD	NEW	0.5	1263
RBV-1	10E	Reboiler	TBD	NEW	0.500	1263

- ¹ Enter the appropriate Emission Unit (or Source) identification number for each fuel burning unit located at the production pad. Gas Producing Unit Burners should be designated GPU-1, GPU-2, etc. Heater Treaters should be designated HT-1, HT-2, etc. Heaters or Line Heaters should be designated LH-1, LH-2, etc. For sources, use 1S, 2S, 3S...or other appropriate designation. Enter glycol dehydration unit Reboiler Vent data on the Glycol Dehydration Unit Data Sheet.
- ² Enter the appropriate Emission Point identification numbers for each fuel burning unit located at the production pad. Gas Producing Unit Burners should be designated GPU-1, GPU-2, etc. Heater Treaters should be designated HT-1, HT-2, etc. Heaters or Line Heaters should be designated LH-1, LH-2, etc. For emission points, use 1E, 2E, 3E...or other appropriate designation.
- ³ New, modification, removal
- ⁴ Enter design heat input capacity in MMBtu/hr.
- ⁵ Enter the fuel heating value in BTU/standard cubic foot.

ATTACHMENT N

Internal Combustion Engine Data Sheet(s)

ATTACHMENT N – INTERNAL COMBUSTION ENGINE DATA SHEET

Complete this data sheet for each internal combustion engine at the facility. Include manufacturer performance data sheet(s) or any other supporting document if applicable. Use extra pages if necessary. *Generator(s) and microturbine generator(s) shall also use this form.*

Emission Unit ID# ¹		VRU-1					
Engine Manufacturer/Model		Cummins G5.9					
Manufacturers Rated bhp/rpm		84 @ 1800					
Source Status ²		NS					
Date Installed/ Modified/Removed/Relocated ³		Upon Receipt of Permit					
Engine Manufactured /Reconstruction Date ⁴		After 3/1/2013					
Check all applicable Federal Rules for the engine (include EPA Certificate of Conformity if applicable) ⁵		<input checked="" type="checkbox"/> 40CFR60 Subpart JJJJ <input type="checkbox"/> JJJJ Certified? <input type="checkbox"/> 40CFR60 Subpart IIII <input type="checkbox"/> IIII Certified? <input type="checkbox"/> 40CFR63 Subpart ZZZZ <input type="checkbox"/> NESHAP ZZZZ/ NSPS JJJJ Window <input type="checkbox"/> NESHAP ZZZZ Remote Sources		<input type="checkbox"/> 40CFR60 Subpart JJJJ <input type="checkbox"/> JJJJ Certified? <input type="checkbox"/> 40CFR60 Subpart IIII <input type="checkbox"/> IIII Certified? <input type="checkbox"/> 40CFR63 Subpart ZZZZ <input type="checkbox"/> NESHAP ZZZZ/ NSPS JJJJ Window <input type="checkbox"/> NESHAP ZZZZ Remote Sources		<input type="checkbox"/> 40CFR60 Subpart JJJJ <input type="checkbox"/> JJJJ Certified? <input type="checkbox"/> 40CFR60 Subpart IIII <input type="checkbox"/> IIII Certified? <input type="checkbox"/> 40CFR63 Subpart ZZZZ <input type="checkbox"/> NESHAP ZZZZ/ NSPS JJJJ Window <input type="checkbox"/> NESHAP ZZZZ Remote Sources	
		Engine Type ⁶		4SRB			
		APCD Type ⁷		NSCR			
		Fuel Type ⁸		RG			
		H ₂ S (gr/100 scf)		<1			
Operating bhp/rpm		84 @ 1800					
BSFC (BTU/bhp-hr)		7914					
Hourly Fuel Throughput		526.4 ft ³ /hr gal/hr		ft ³ /hr gal/hr		ft ³ /hr gal/hr	
Annual Fuel Throughput (Must use 8,760 hrs/yr unless emergency generator)		4.62 MMft ³ /yr gal/yr		MMft ³ /yr gal/yr		MMft ³ /yr gal/yr	
.Fuel Usage or Hours of Operation Metered		Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>		Yes <input type="checkbox"/> No <input type="checkbox"/>		Yes <input type="checkbox"/> No <input type="checkbox"/>	
Calculation Methodology ⁹	Pollutant ¹⁰	Hourly PTE (lb/hr) ¹¹	Annual PTE (tons/year) ¹¹	Hourly PTE (lb/hr) ¹¹	Annual PTE (tons/year) ¹¹	Hourly PTE (lb/hr) ¹¹	Annual PTE (tons/year) ¹¹
AP	NO _x	0.19	0.81				
AP	CO	0.37	1.62				
AP	VOC	0.04	0.18				
AP	SO ₂	<0.01	<0.01				
AP	PM ₁₀	0.013	0.06				
AP	Formaldehyde	0.015	0.065				
AP	Total HAPs	0.022	0.10				
AP	GHG (CO ₂ e)	89.7	393				

1 Enter the appropriate Source Identification Number for each natural gas-fueled reciprocating internal combustion compressor/generator engine located at the compressor station. Multiple compressor engines should be designated CE-1, CE-2, CE-3 etc. Generator engines should be designated GE-1, GE-2, GE-3 etc. Microturbine generator engines should be designated MT-1, MT-2, MT-3 etc. If more than three (3) engines exist, please use additional sheets.

2 Enter the Source Status using the following codes:

NS Construction of New Source (installation)
MS Modification of Existing Source

ES Existing Source
RS Relocated Source

REM Removal of Source

- 3 Enter the date (or anticipated date) of the engine's installation (construction of source), modification, relocation or removal.
- 4 Enter the date that the engine was manufactured, modified or reconstructed.
- 5 Is the engine a certified stationary spark ignition internal combustion engine according to 40CFR60 Subpart IIII/JJJJ? If so, the engine and control device must be operated and maintained in accordance with the manufacturer's emission-related written instructions. You must keep records of conducted maintenance to demonstrate compliance, but no performance testing is required. If the certified engine is not operated and maintained in accordance with the manufacturer's emission-related written instructions, the engine will be considered a non-certified engine and you must demonstrate compliance as appropriate.

Provide a manufacturer's data sheet for all engines being registered.

- 6 Enter the Engine Type designation(s) using the following codes:

2SLB	Two Stroke Lean Burn	4SRB	Four Stroke Rich Burn
4SLB	Four Stroke Lean Burn		

- 7 Enter the Air Pollution Control Device (APCD) type designation(s) using the following codes:

A/F	Air/Fuel Ratio	IR	Ignition Retard
HEIS	High Energy Ignition System	SIPC	Screw-in Precombustion Chambers
PSC	Prestratified Charge	LEC	Low Emission Combustion
NSCR	Rich Burn & Non-Selective Catalytic Reduction	OxCat	Oxidation Catalyst
SCR	Lean Burn & Selective Catalytic Reduction		

- 8 Enter the Fuel Type using the following codes:

PQ	Pipeline Quality Natural Gas	RG	Raw Natural Gas /Production Gas	D	Diesel
----	------------------------------	----	---------------------------------	---	--------

- 9 Enter the Potential Emissions Data Reference designation using the following codes. Attach all reference data used.

MD	Manufacturer's Data	AP	AP-42
GR	GRI-HAPCalc TM	OT	Other (please list)

- 10 Enter each engine's Potential to Emit (PTE) for the listed regulated pollutants in pounds per hour and tons per year. PTE shall be calculated at manufacturer's rated brake horsepower and may reflect reduction efficiencies of listed Air Pollution Control Devices. Emergency generator engines may use 500 hours of operation when calculating PTE. PTE data from this data sheet shall be incorporated in the *Emissions Summary Sheet*.
- 11 PTE for engines shall be calculated from manufacturer's data unless unavailable.

Engine Air Pollution Control Device (Emission Unit ID# VRU-1)	
Air Pollution Control Device Manufacturer's Data Sheet included? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	
<input checked="" type="checkbox"/> NSCR <input type="checkbox"/> SCR <input type="checkbox"/> Oxidation Catalyst	
Provide details of process control used for proper mixing/control of reducing agent with gas stream: N/A	
Manufacturer: Miratech	Model #: VXC-1408-04-HSG
Design Operating Temperature: 1000 °F	Design gas volume: 430 + scfm
Service life of catalyst: 2+ years, depending on site conditions	Provide manufacturer data? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Volume of gas handled: 430 acfm at 1078 °F	Operating temperature range for NSCR/Ox Cat: From 750 °F to 1250 °F
Reducing agent used, if any: None	Ammonia slip (ppm): N/A
Pressure drop against catalyst bed (delta P): 3.0 inches of H₂O	
Provide description of warning/alarm system that protects unit when operation is not meeting design conditions: Part of the routine maintenance inspection to warn or alert operations of emissions control degradation is a task called the post-PM emissions check.	
Is temperature and pressure drop of catalyst required to be monitored per 40CFR63 Subpart ZZZZ? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
How often is catalyst recommended or required to be replaced (hours of operation)? Because there are so many factors that impact life of a catalyst, the vendor does not recommend "hours of operation prior to replacement." The routine post-PM emissions check task (every 60 days or 1440 hrs of operation, whichever comes first) determines when the catalyst needs to be serviced or replaced.	
How often is performance test required? <input type="checkbox"/> Initial <input type="checkbox"/> Annual <input type="checkbox"/> Every 8,760 hours of operation <input type="checkbox"/> Field Testing Required <input checked="" type="checkbox"/> No performance test required. If so, why (please list any maintenance required and the applicable sections in NSPS/GACT: Per 40 CFR 60.4243(a)(iii), an owner or operator of a stationary SI internal combustion engine less than 100 HP, must keep a maintenance plan and records of conducted maintenance to demonstrate compliance and must, to the extent practicable, maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions, but no performance testing is required for an owner or operator	

ATTACHMENT O

Tanker Truck Loading Data Sheet(s)

ATTACHMENT O – TANKER TRUCK LOADING DATA SHEET

Complete this data sheet for each new or modified bulk liquid transfer area or loading rack at the facility. This is to be used for bulk liquid transfer operations to tanker trucks. Use extra pages if necessary.

Truck Loadout Collection Efficiencies

The following applicable capture efficiencies of a truck loadout are allowed:

- For tanker trucks passing the MACT level annual leak test – 99.2%
- For tanker trucks passing the NSPS level annual leak test – 98.7%
- For tanker trucks not passing one of the annual leak tests listed above – 70%

Compliance with this requirement shall be demonstrated by keeping records of the applicable MACT or NSPS Annual Leak Test certification for **every** truck and railcar loaded/unloaded. This requirement can be satisfied if the trucking company provided certification that its entire fleet was compliant. This certification must be submitted in writing to the Director of the DAQ. These additional requirements must be noted in the Registration Application.

Emission Unit ID#: TL-1 & TL-2	Emission Point ID#: 5E & 6E	Year Installed/Modified: TBD		
Emission Unit Description: Condensate Truck Loading				
Loading Area Data				
Number of Pumps: 2	Number of Liquids Loaded: 2	Max number of trucks loading at one (1) time: 2		
Are tanker trucks pressure tested for leaks at this or any other location? <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Not Required				
If Yes, Please describe:				
Provide description of closed vent system and any bypasses. None				
Are any of the following truck loadout systems utilized? No				
<input type="checkbox"/> Closed System to tanker truck passing a MACT level annual leak test?				
<input type="checkbox"/> Closed System to tanker truck passing a NSPS level annual leak test?				
<input type="checkbox"/> Closed System to tanker truck not passing an annual leak test and has vapor return?				
Projected Maximum Operating Schedule (for rack or transfer point as a whole)				
Time	Jan – Mar	Apr - Jun	Jul – Sept	Oct - Dec
Hours/day	24	24	24	24
Days/week	7	7	7	7
Bulk Liquid Data (use extra pages as necessary)				
Liquid Name	Condensate	Produced Water		
Max. Daily Throughput (1000 gal/day)	4.2	5.04		
Max. Annual Throughput (1000 gal/yr)	856.8	1,814.4		
Loading Method ¹	SUB	SP		
Max. Fill Rate (gal/min)	50	50		
Average Fill Time (min/loading)	120	120		
Max. Bulk Liquid Temperature (°F)	75	75		
True Vapor Pressure ²	3.6 psia	n/a		
Cargo Vessel Condition ³	U	U		
Control Equipment or Method ⁴	None	None		
Max. Collection Efficiency (%)	n/a	n/a		

Max. Control Efficiency (%)		n/a	n/a	
Max.VOC Emission Rate	Loading (lb/hr)	2.96	0.08	
	Annual (ton/yr)	0.91	0.04	
Max.HAP Emission Rate	Loading (lb/hr)	0.16	0.01	
	Annual (ton/yr)	0.05	<0.01	
Estimation Method ⁵		EPA	EPA	

- 1 BF Bottom Fill SP Splash Fill SUB Submerged Fill
- 2 At maximum bulk liquid temperature
- 3 B Ballasted Vessel C Cleaned U Uncleaned (dedicated service)
- O Other (describe)
- 4 List as many as apply (complete and submit appropriate Air Pollution Control Device Sheets)
- CA Carbon Adsorption VB Dedicated Vapor Balance (closed system)
- ECD Enclosed Combustion Device F Flare
- TO Thermal Oxidization or Incineration
- 5 EPA EPA Emission Factor in AP-42 MB Material Balance
- TM Test Measurement based upon test data submittal O Other (describe)

ATTACHMENT P

Glycol Dehydration Unit Data Sheet(s)

ATTACHMENT P – GLYCOL DEHYDRATION UNIT DATA SHEET

Complete this data sheet for each Glycol Dehydration Unit, Reboiler, Flash Tank and/or Regenerator at the facility. Include gas sample analysis and GRI- GLYCalc™ input and aggregate report. Use extra pages if necessary.

Manufacturer: Exterran	Model:				
Max. Dry Gas Flow Rate: 40 mmscf/day	Reboiler Design Heat Input: 0.500 MMBTU/hr				
Design Type: <input checked="" type="checkbox"/> TEG <input type="checkbox"/> DEG <input type="checkbox"/> EG	Source Status ¹ : NS				
Date Installed/Modified/Removed ² : TBD	Regenerator Still Vent APCD/ERD ³ : TO				
Control Device/ERD ID# ³ : EC-2	Fuel HV (BTU/scf): 1263				
H ₂ S Content (gr/100 scf): <0.001%	Operation (hours/year): 8760				
Pump Rate (gpm): 7.5					
Water Content (wt %) in: Wet Gas: Saturated Dry Gas: 7.0 lb/MMscf					
<p>Is the glycol dehydration unit exempt from 40CFR63 Section 764(d)? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No: If Yes, answer the following:</p> <p>The actual annual average flowrate of natural gas to the glycol dehydration unit is less than 85 thousand standard cubic meters per day, as determined by the procedures specified in §63.772(b)(1) of this subpart. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No</p> <p>The actual average emissions of benzene from the glycol dehydration unit process vent to the atmosphere are less than 0.90 megagram per year (1 ton per year), as determined by the procedures specified in §63.772(b)(2) of this subpart. <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No</p>					
Is the glycol dehydration unit located within an Urbanized Area (UA) or Urban Cluster (UC)? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					
Is a lean glycol pump optimization plan being utilized? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					
Recycling the glycol dehydration unit back to the flame zone of the reboiler. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					
Recycling the glycol dehydration unit back to the flame zone of the reboiler and mixed with fuel. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No					
What happens when temperature controller shuts off fuel to the reboiler? Still vent to enclosed combustor. <input type="checkbox"/> Still vent emissions to the atmosphere. <input type="checkbox"/> Still vent emissions stopped with valve. <input type="checkbox"/> Still vent emissions to glow plug.					
Please indicate if the following equipment is present. <input type="checkbox"/> Flash Tank <input type="checkbox"/> Burner management system that continuously burns condenser or flash tank vapors					
Control Device Technical Data					
Pollutants Controlled	Manufacturer's Guaranteed Control Efficiency (%)				
Hydrocarbons	99+% (Note: 98% used for calculations)				
Emissions Data					
Emission Unit ID / Emission Point ID ⁴	Description	Calculation Methodology ⁵	PTE ⁶	Controlled Maximum Hourly Emissions (lb/hr)	Controlled Maximum Annual Emissions (tpy)
RBV-1 / 11E	Reboiler Vent	AP-42	NO _x	0.05	0.22
		AP-42	CO	0.04	0.18
		AP-42	VOC	<0.01	0.01
		AP-42	SO ₂	<0.01	<0.01
		AP-42	PM ₁₀	<0.01	0.02
		AP-42	GHG (CO ₂ e)	60.4	264.5

RSV-1 / 11E	Glycol Regenerator Still Vent	GRI-GlyCalc™	VOC	0.80	3.51
		GRI-GlyCalc™	Benzene	0.01	0.04
		GRI-GlyCalc™	Toluene	0.03	0.15
		GRI-GlyCalc™	Ethylbenzene	<0.01	<0.01
		GRI-GlyCalc™	Xylenes	<0.01	<0.01
		GRI-GlyCalc™	n-Hexane	0.02	0.09
NONE	Glycol Flash Tank	GRI-GlyCalc™	VOC		
		GRI-GlyCalc™	Benzene		
		GRI-GlyCalc™	Toluene		
		GRI-GlyCalc™	Ethylbenzene		
		GRI-GlyCalc™	Xylenes		
		GRI-GlyCalc™	n-Hexane		

- 1 Enter the Source Status using the following codes:
NS Construction of New Source ES Existing Source
MS Modification of Existing Source
- 2 Enter the date (or anticipated date) of the glycol dehydration unit's installation (construction of source), modification or removal.
- 3 Enter the Air Pollution Control Device (APCD)/Emission Reduction Device (ERD) type designation using the following codes and the device ID number:
NA None CD Condenser FL Flare
CC Condenser/Combustion Combination TO Thermal Oxidizer O Other (please list)
- 4 Enter the appropriate Emission Unit ID Numbers and Emission Point ID Numbers for the glycol dehydration unit reboiler vent and glycol regenerator still vent. The glycol dehydration unit reboiler vent and glycol regenerator still vent should be designated RBV-1 and RSV-1, respectively. If the compressor station incorporates multiple glycol dehydration units, a Glycol Dehydration Emission Unit Data Sheet shall be completed for each, using Source Identification RBV-2 and RSV-2, RBV-3 and RSV-3, etc.
- 5 Enter the Potential Emissions Data Reference designation using the following codes:
MD Manufacturer's Data AP AP-42
GR GRI-GLYCalc™ OT Other (please list)
- 6 Enter the Reboiler Vent and Glycol Regenerator Still Vent Potential to Emit (PTE) for the listed regulated pollutants in lbs per hour and tons per year. The Glycol Regenerator Still Vent potential emissions may be determined using the most recent version of the thermodynamic software model GRI-GLYCalc™ (Radian International LLC & Gas Research Institute). **Attach all referenced Potential Emissions Data (or calculations) and the GRI-GLYCalc™ Aggregate Calculations Report (shall include emissions reports, equipment reports, and stream reports) to this Glycol Dehydration Emission Unit Data Sheet(s). Backup pumps do not have to be considered as operating for purposes of PTE.** This PTE data shall be incorporated in the Emissions Summary Sheet.

**ATTACHMENT Q – PNEUMATIC CONTROLLERS
DATA SHEET**

Are there any continuous bleed natural gas driven pneumatic controllers at this facility that commenced construction, modification or reconstruction after August 23, 2011?

☐ Yes ☒ No

Please list approximate number.

Are there any continuous bleed natural gas driven pneumatic controllers at this facility with a bleed rate greater than 6 standard cubic feet per hour that are required based on functional needs, including but not limited to response time, safety and positive actuation that commenced construction, modification or reconstruction after August 23, 2011?

☐ Yes ☒ No

Please list approximate number.

ATTACHMENT R

Air Pollution Control Device Sheet(s)

ATTACHMENT R – AIR POLLUTION CONTROL DEVICE / EMISSION REDUCTION DEVICE SHEETS

Complete the applicable air pollution control device sheets for each flare, vapor combustor, thermal oxidizer, condenser, adsorption system, vapor recovery unit, BTEX Eliminator, Reboiler with and without Glow Plug, etc. at the facility. Use extra pages if necessary.

Emissions calculations must be performed using the most conservative control device efficiency.

The following five (5) rows are only to be completed if registering an alternative air pollution control device.

Emission Unit ID: T01-T06	Make/Model: Condensate and Produced Water Tanks
Primary Control Device ID: VRU-1	Make/Model: Arrow/WRC2
Control Efficiency (%): 98	APCD/ERD Data Sheet Completed: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Secondary Control Device ID: EC-1	Make/Model: Hy-Bon CH 10.0
Control Efficiency (%): 98	APCD/ERD Data Sheet Completed: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

VAPOR COMBUSTION (Including Enclosed Combustors)

General Information

Control Device ID#: EC-1	Installation Date: TBD – Upon Permit <input checked="" type="checkbox"/> New <input type="checkbox"/> Modified <input type="checkbox"/> Relocated	
Maximum Rated Total Flow Capacity scfh scfd	Maximum Design Heat Input (from mfg. spec sheet) 10.0 MMBTU/hr	Design Heat Content BTU/scf

Control Device Information

Type of Vapor Combustion Control?		
<input checked="" type="checkbox"/> Enclosed Combustion Device <input type="checkbox"/> Thermal Oxidizer	<input type="checkbox"/> Elevated Flare	<input type="checkbox"/> Ground Flare
Manufacturer: Hy-Bon Model: CH 10.0	Hours of operation per year? 8760	

List the emission units whose emissions are controlled by this vapor control device (Emission Point ID#)

Emission Unit ID#	Emission Source Description	Emission Unit ID#	Emission Source Description
T01-T03	Condensate Tanks		
T04-T06	Produced Water Tanks		

If this vapor combustor controls emissions from more than six (6) emission units, please attach additional pages.

Assist Type (Flares only)	Flare Height	Tip Diameter	Was the design per §60.18?
<input type="checkbox"/> Steam <input type="checkbox"/> Air <input type="checkbox"/> Pressure <input checked="" type="checkbox"/> Non	feet	feet	<input type="checkbox"/> Yes <input type="checkbox"/> No Provide determination.

Waste Gas Information

Maximum Waste Gas Flow Rate 19.79 (scfm)	Heat Value of Waste Gas Stream 2313 BTU/ft ³	Exit Velocity of the Emissions Stream (ft/s)
---	--	---

Provide an attachment with the characteristics of the waste gas stream to be burned.

Pilot Gas Information

Number of Pilot Lights 1	Fuel Flow Rate to Pilot Flame per Pilot 798 scfh	Heat Input per Pilot 985,100 BTU/hr	Will automatic re-ignition be used? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
-----------------------------	--	--	--

If automatic re-ignition is used, please describe the method. **The unit will try to re-ignite up to 25 times. After that, it will go into manual mode which means someone will need to manually start. Gas flow is shut off if it fails to ignite.**

Is pilot flame equipped with a monitor to detect the presence of the flame? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	If Yes, what type? <input checked="" type="checkbox"/> Thermocouple <input type="checkbox"/> Infrared <input type="checkbox"/> Ultraviolet <input type="checkbox"/> Camera <input type="checkbox"/> Other:
---	---

Describe all operating ranges and maintenance procedures required by the manufacturer to maintain the warranty. *(If unavailable, please indicate).* **Combustor burner, pilot, and air inlet arrestor must be checked for foreign debris (dust, sand, etc.) and cleaned at least quarterly.**

Additional information attached? ☒ Yes ☐ No
 Please attach copies of manufacturer's data sheets, drawings, flame demonstration per §60.18 or §63.11(b) and performance testing.

VAPOR RECOVERY UNIT

***See Attachment N**

General Information

Emission Unit ID#:

Installation Date:

☐ New

☐ Modified

☐ Relocated

Device Information

Manufacturer:

Model:

List the emission units whose emissions are controlled by this vapor recovery unit (Emission Point ID#)

Emission Unit ID#	Emission Source Description	Emission Unit ID#	Emission Source Description

If this vapor recovery unit controls emissions from more than six (6) emission units, please attach additional pages.

Additional information attached? ☐ Yes ☐ No

Please attach copies of manufacturer's data sheets, drawings, and performance testing.

The registrant may claim a capture and control efficiency of 95 % (which accounts for 5% downtime) for the vapor recovery unit.

The registrant may claim a capture and control efficiency of 98% if the VRU has a backup flare that meet the requirements of Section 8.1.2 of this general permit.

The registrant may claim a capture and control efficiency of 98% if the VRU has a backup VRU.

VAPOR COMBUSTION (Including Enclosed Combustors)			
General Information			
Control Device ID#: EC-2		Installation Date: TBD – Upon Permit <input checked="" type="checkbox"/> New <input type="checkbox"/> Modified <input type="checkbox"/> Relocated	
Maximum Rated Total Flow Capacity scfh scfd		Maximum Design Heat Input (from mfg. spec sheet) 10.0 MMBTU/hr	Design Heat Content BTU/scf
Control Device Information			
Type of Vapor Combustion Control? <input checked="" type="checkbox"/> Enclosed Combustion Device <input type="checkbox"/> Elevated Flare <input type="checkbox"/> Ground Flare <input type="checkbox"/> Thermal Oxidizer			
Manufacturer: Hy-Bon Model: CH 10.0		Hours of operation per year? 8760	
List the emission units whose emissions are controlled by this vapor control device (Emission Point ID#)			
Emission Unit ID#	Emission Source Description	Emission Unit ID#	Emission Source Description
RBV-1	Dehydration Unit Still Vent		
<i>If this vapor combustor controls emissions from more than six (6) emission units, please attach additional pages.</i>			
Assist Type (Flares only)		Flare Height	Tip Diameter
<input type="checkbox"/> Steam <input type="checkbox"/> Air <input type="checkbox"/> Pressure <input checked="" type="checkbox"/> Non		feet	feet
		Was the design per §60.18? <input type="checkbox"/> Yes <input type="checkbox"/> No Provide determination.	
Waste Gas Information			
Maximum Waste Gas Flow Rate 64.3 (scfm)		Heat Value of Waste Gas Stream 660.7 BTU/ft ³	Exit Velocity of the Emissions Stream (ft/s)
<i>Provide an attachment with the characteristics of the waste gas stream to be burned.</i>			
Pilot Gas Information			
Number of Pilot Lights 1	Fuel Flow Rate to Pilot Flame per Pilot 798 scfh	Heat Input per Pilot 985,100 BTU/hr	Will automatic re-ignition be used? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
If automatic re-ignition is used, please describe the method. The unit will try to re-ignite up to 25 times. After that, it will go into manual mode which means someone will need to manually start. Gas flow is shut off if it fails to ignite.			
Is pilot flame equipped with a monitor to detect the presence of the flame? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		Is pilot flame equipped with a monitor to detect the presence of the flame? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Describe all operating ranges and maintenance procedures required by the manufacturer to maintain the warranty. <i>(If unavailable, please indicate).</i> Combustor burner, pilot, and air inlet arrestor must be checked for foreign debris (dust, sand, etc.) and cleaned at least quarterly.			
Additional information attached? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Please attach copies of manufacturer's data sheets, drawings, flame demonstration per §60.18 or §63.11(b) and performance testing.			

ATTACHMENT S

Emission Calculations

Jay-Bee Oil & Gas, Inc.
EMISSIONS SUMMARY

Moe Well Pad Production Facility
Tyler County, WV

Emission Unit ID	Description	NOx lb/hr	CO lb/hr	CO2e lb/hr	VOC lb/hr	SO2 lb/hr	PM lb/hr	Benzene lb/hr	Ethylbenzene lb/hr	Xylenes lb/hr	n-Hexane lb/hr	Toluene lb/hr	Formaldehyde lb/hr	Total HAPs lb/hr
HTR-1	GPU #1	0.15	0.13	181.1	0.01	0.001	0.011				0.003		0.000	0.003
HTR-2	GPU #2	0.15	0.13	181.1	0.01	0.001	0.011				0.003		0.000	0.003
HTR-3	GPU #3	0.15	0.13	181.1	0.01	0.001	0.011				0.003		0.000	0.003
HTR-4	Line Heater	0.05	0.04	60.4	0.00	0.000	0.004				0.001		0.000	0.001
TL-1	Truck Loading - Condensate ²				2.96						0.16			0.16
TL-2	Truck Loading - Produced Water ²				0.08						0.01			0.01
VRU-1	VRU Compressor	0.19	0.37	89.7	0.04	0.000	0.013	0.001	0.000	0.000		0.000	0.015	0.022
TEG-1	Thermoelectric Generator	0.00	0.00	1.6	0.00	0.000	0.000				0.000		0.000	0.000
EC-1	Condensate Tanks + Water Tanks ¹	0.29	1.10	446.6	1.84	0.001	0.017				0.004		0.000	0.00
RBV-1	500 MBTU/hr Reboiler	0.05	0.04	60.4	0.003	0.000	0.004				0.001		0.000	0.001
EC-2	Dehydration Unit Combustor	0.27	1.03	417.4	0.81	0.001	0.037	0.010			0.02	0.034	0.000	0.06
---	Truck Traffic Fugitive Dust						30.10							
---	Fugitive Emissions			8.9	0.40									0.004
Total (Excluding Fugitive Emissions)		1.29	2.96	1619.51	5.76	0.00	0.11	0.01	0.00	0.00	0.20	0.03	0.02	0.27
Total		1.29	2.96	1628.37	6.16	0.00	30.20	0.01	0.00	0.00	0.20	0.03	0.02	0.27

Emission Unit ID	Description	NOx tpy	CO tpy	CO2e tpy	VOC tpy	SO2 tpy	PM tpy	Benzene tpy	Ethylbenzene tpy	Xylenes tpy	n-Hexane tpy	Toluene tpy	Formaldehyde tpy	Total HAPs tpy
HTR-1	GPU #1	0.66	0.55	793	0.04	0.004	0.05				0.01		0.000	0.01
HTR-2	GPU #2	0.66	0.55	793	0.04	0.004	0.05				0.01		0.000	0.01
HTR-3	GPU #3	0.66	0.55	793	0.04	0.004	0.05				0.01		0.000	0.01
HTR-4	Line Heater	0.22	0.18	264	0.01	0.001	0.02				0.00		0.000	0.00
TL-1	Truck Loading - Condensate ²				0.91						0.05			0.05
TL-2	Truck Loading - Produced Water ²				0.04						0.00			0.00
VRU-1	VRU Compressor	0.81	1.62	393	0.18	0.002	0.06	0.005	0.000	0.001		0.002	0.065	0.10
TEG-1	Thermoelectric Generator	0.01	0.00	7	0.00	0.000	0.00				0.00		0.000	0.00
EC-1	Condensate Tanks + Water Tanks ¹	1.25	4.81	1956	0.43	0.00	0.07				0.01		0.001	0.02
RBV-1	500 MBTU/hr Reboiler	0.22	0.18	264.5	0.01	0.001	0.017				0.004		0.000	0.004
EC-2	Dehydration Unit Combustor	1.19	4.50	1828.1	3.54	0.003	0.161	0.04			0.09	0.15	0.002	0.28
---	Truck Traffic Fugitive Dust						5.98							
---	Fugitive Emissions			38.78	1.76									0.018
Total (Excluding Fugitive Emissions)		5.67	12.96	7093.46	5.22	0.02	0.47	0.05	0.00	0.00	0.20	0.15	0.07	0.50
Total		5.67	12.96	7132.24	6.98	0.02	6.46	0.05	0.00	0.00	0.20	0.15	0.07	0.52

¹ Condensate and water tank emissions are currently controlled by a VRU + Enclosed Combustor at 98%. This line represents the un-controlled 2%.

² Truck loading is un-controlled.

Jay-Bee Oil & Gas, LLC

Moe Well Pad Production Facility Tyler County, WV

Controlled Emission Rates

Source VRU-1

Engine Data:

Engine Manufacturer Cummins
Engine Model G5.9
Type (Rich-burn or Low Emission) Rich Burn
Aspiration (Natural or Turbocharged) Natural

Manufacturer Rating 84 hp
Speed at Above Rating 1,800 rpm
Configuration (In-line or V) In-line
Number of Cylinders 6
Engine Bore 4.020 inches
Engine Stroke 4.720 inches

Engine Displacement 359 cu. in.
Engine BMEP 103 psi
Fuel Consumption (HHV) 7,914 Btu/bhp-hr

Emission Rates:

	g/bhp-hr	lb/hr	tpy	g/hr	lb/day	AP-42 4strokerich lb/MMBtu
Oxides of Nitrogen, NOx	1.000	0.19	0.81	84	4.44	
Carbon Monoxide CO	2.000	0.37	1.62	168	8.89	
VOC (NMNEHC)	0.220	0.04	0.18	18	0.98	
CO2	449	83	364	37,716	1,996	
CO2e		90	393			

Comment
453.59 grams = 1 pound
2,000 pounds = 1 ton

Total Annual Hours of Operation

	8,760			
SO2		0.0004	0.0017	0.0006
PM2.5		0.00632	0.0277	0.0095
PM (Condensable)		0.00659	0.0289	0.00991
CH4		0.12623	0.5529	0.0022
N2O		0.01148	0.0503	0.0002
acrolein		0.00175	0.0077	0.00263
acetaldehyde		0.00185	0.0081	0.00279
formaldehyde	0.080	0.0148	0.0649	
benzene		0.00105	0.0046	0.00158
toluene		0.00037	0.0016	0.000558
ethylbenzene		1.6E-05	0.0001	0.0000248
xylene		0.00013	0.0006	0.000195
methanol		0.00203	0.0089	0.00306
Total HAPs		0.02202	0.0964	

Factor From 40 CFR 98, Table C-2
Factor From 40 CFR 98, Table C-2

Per Mfg.

Exhaust Parameters:

Exhaust Gas Temperature 1,078 deg. F
Exhaust Gas Mass Flow Rate lb/hr
Exhaust Gas Mass Flow Rate 430 acfm

Exhaust Stack Height 96 inches
8.00 feet

Exhaust Stack Inside Diameter 4 inches
0.333 feet

Exhaust Stack Velocity 82.1 ft/sec
4,927.4 ft/min

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

Potential Emission Rates

Source HTR-1 Through HTR-3

***Emissions shown below are for each Gas Processing Unit**

Burner Duty Rating	1500.0 Mbtu/hr
Burner Efficiency	98.0 %
Gas Heat Content (HHV)	1263.0 Btu/scf
Total Gas Consumption	29,084.8 scfd
H2S Concentration	0.000 Mole %
Hours of Operation	8760

NOx	0.1501	lb/hr	0.657	tpy
CO	0.1261	lb/hr	0.552	tpy
CO2	180.1	lb/hr	788.7	tpy
CO2e	181	lb/hr	793	tpy
VOC	0.0083	lb/hr	0.036	tpy
SO2	0.0009	lb/hr	0.004	tpy
H2S	0.0000	lb/hr	0.000	tpy
PM10	0.0114	lb/hr	0.050	tpy
CHOH	0.0001	lb/hr	0.000	tpy
Benzene	0.0000	lb/hr	0.000	tpy
N-Hexane	0.0027	lb/hr	0.012	tpy
Toluene	0.0000	lb/hr	0.000	tpy
Total HAPs	0.0028	lb/hr	0.012	tpy

AP-42 Factors Used

NOx	100 lb/MMCF	
CO	84 lb/MMCF	
CO ₂	120,000 lb/MMCF	Global Warming Potential = 1
VOC	5.5 lb/MMCF	
PM	7.6 lb/MMCF	
SO ₂	0.6 lb/MMCF	
CH ₄	2.3 lb/MMCF	Global Warming Potential = 25
N ₂ O	2.2 lb/MMCF	Global Warming Potential = 298
HCOH	0.075 lb/MMCF	
Benzene	0.0021 lb/MMCF	
n-Hexane	1.8 lb/MMCF	
Toluene	0.0034 lb/MMCF	

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

Potential Emission Rates

Source HTR-4 Line Heater

Burner Duty Rating 500.0 Mbtu/hr
Burner Efficiency 98.0 %
Gas Heat Content (HHV) 1263.0 Btu/scf
Total Gas Consumption 9,694.9 scfd
H2S Concentration 0.000 Mole %
Hours of Operation 8760

NOx	0.0500	lb/hr	0.219	tpy
CO	0.0420	lb/hr	0.184	tpy
CO2	60.0	lb/hr	262.9	tpy
CO2e	60	lb/hr	264	tpy
VOC	0.0028	lb/hr	0.012	tpy
SO2	0.0003	lb/hr	0.001	tpy
H2S	0.0000	lb/hr	0.000	tpy
PM10	0.0038	lb/hr	0.017	tpy
CHOH	0.0000	lb/hr	0.000	tpy
Benzene	0.0000	lb/hr	0.000	tpy
N-Hexane	0.0009	lb/hr	0.004	tpy
Toluene	0.0000	lb/hr	0.000	tpy
Total HAPs	0.0009	lb/hr	0.004	tpy

AP-42 Factors Used

NOx	100 lb/MMCF	
CO	84 lb/MMCF	
CO ₂	120,000 lb/MMCF	Global Warming Potential = 1
VOC	5.5 lb/MMCF	
PM	7.6 lb/MMCF	
SO ₂	0.6 lb/MMCF	
CH ₄	2.3 lb/MMCF	Global Warming Potential = 25
N ₂ O	2.2 lb/MMCF	Global Warming Potential = 298
HCOH	0.075 lb/MMCF	
Benzene	0.0021 lb/MMCF	
n-Hexane	1.8 lb/MMCF	
Toluene	0.0034 lb/MMCF	

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility Tyler County, WV

Potential Emission Rates

Source TEG-1

Burner Duty Rating	13.0 MBtu/hr
Burner Efficiency	98.0 %
Gas Heat Content (HHV)	1263.0 Btu/scf
Total Gas Consumption	252.1 scfd
H2S Concentration	0.000 Mole %
Hours of Operation	8760

NOx	0.0013	lb/hr	0.006	tpy
CO	0.0011	lb/hr	0.005	tpy
CO2	1.6	lb/hr	6.8	tpy
CO2e	2	lb/hr	7	tpy
VOC	0.0001	lb/hr	0.000	tpy
SO2	0.0000	lb/hr	0.000	tpy
H2S	0.0000	lb/hr	0.000	tpy
PM10	0.0001	lb/hr	0.000	tpy
CHOH	0.0000	lb/hr	0.000	tpy
Benzene	0.0000	lb/hr	0.000	tpy
N-Hexane	0.0000	lb/hr	0.000	tpy
Toluene	0.0000	lb/hr	0.000	tpy
Total HAPs	0.0000	lb/hr	0.000	tpy

AP-42 Factors Used

NOx	100 lb/MMCF	
CO	84 lb/MMCF	
CO ₂	120,000 lb/MMCF	Global Warming Potential = 1
VOC	5.5 lb/MMCF	
PM	7.6 lb/MMCF	
SO ₂	0.6 lb/MMCF	
CH ₄	2.3 lb/MMCF	Global Warming Potential = 25
N ₂ O	2.2 lb/MMCF	Global Warming Potential = 298
HCOH	0.075 lb/MMCF	
Benzene	0.0021 lb/MMCF	
n-Hexane	1.8 lb/MMCF	
Toluene	0.0034 lb/MMCF	

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

Potential Emission Rates

Source EC-1 Enclosed Combustor Pilot

Burner Duty Rating 985.1 MBtu/hr
Burner Efficiency 98.0 %
Gas Heat Content (HHV) 1263.0 Btu/scf
Total Gas Consumption 19100.9 scfd
H2S Concentration 0.000 Mole %
Hours of Operation 8760

NOx	0.0985	lb/hr	0.432	tpy
CO	0.0828	lb/hr	0.363	tpy
CO2	118.3	lb/hr	518.0	tpy
CO2e	119	lb/hr	521	tpy
VOC	0.0054	lb/hr	0.024	tpy
SO2	0.0006	lb/hr	0.003	tpy
H2S	0.0000	lb/hr	0.000	tpy
PM10	0.0075	lb/hr	0.033	tpy
CHOH	0.0001	lb/hr	0.000	tpy
Benzene	0.0000	lb/hr	0.000	tpy
N-Hexane	0.0018	lb/hr	0.008	tpy
Toluene	0.0000	lb/hr	0.000	tpy
Total HAPs	0.0019	lb/hr	0.008	tpy

AP-42 Factors Used (Tables 1.4.1-1.4.3)

NOx	100 lb/MMCF	
CO	84 lb/MMCF	
CO ₂	120,000 lb/MMCF	Global Warming Potential = 1
VOC	5.5 lb/MMCF	
PM	7.6 lb/MMCF	
SO ₂	0.6 lb/MMCF	
CH ₄	2.3 lb/MMCF	Global Warming Potential = 25
N ₂ O	2.2 lb/MMCF	Global Warming Potential = 298
HCOH	0.075 lb/MMCF	
Benzene	0.0021 lb/MMCF	
n-Hexane	1.8 lb/MMCF	
Toluene	0.0034 lb/MMCF	

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

Potential Emission Rates

Source EC-1 Enclosed Vapor Combustor - Control of Tank Emissions

Destruction Efficiency	98.0 %		
Gas Heat Content (HHV)	2313.1 Btu/scf		
Max Flow to T-E	0.028 MMSCFD	10.401 MMSCF/yr	
Max BTUs to Flare	2.746 MMBTU/hr	24,058 MMBTU/yr	

NOx	0.19	lb/hr	0.82	tpy
CO	1.02	lb/hr	4.45	tpy
CO2	321.02	lb/hr	1,406.07	tpy
CO2e	327.68	lb/hr	1,435.26	tpy
VOC	1.83	lb/hr	0.40	tpy
CH4	0.26	lb/hr	0.06	tpy
N2O	0.0006	lb/hr	0.0026	tpy
PM	0.0090	lb/hr	0.0395	tpy
CHOH	0.0001	lb/hr	0.0004	tpy
Benzene	0.0000	lb/hr	0.0000	tpy
n-Hexane	0.0021	lb/hr	0.0094	tpy
Toluene	0.0000	lb/hr	0.0000	tpy
Total HAP	0.0022	lb/hr	0.0098	tpy

Notes: VOC, Total HAP, N-Hexane and CH4 emissions are taken from the Condensate and Produced Water Tank Emissions

Factors Used

AP-42 Table 13.5-1	NOx	0.068 lb/MMBTU	
AP-42 Table 13.5-1	CO	0.37 lb/MMBTU	
40 CFR 98 Table C-1	CO2	116.89 lb/MMBTU	Global Warming Potential = 1
40 CFR 98 Table C-2	CH4	0.0022 lb/MMBTU	Global Warming Potential = 25
40 CFR 98 Table C-2	N2O	0.00022 lb/MMBTU	Global Warming Potential = 298
AP-42 Table 1.4-2	PM	7.6 lb/MMSCF	
AP-42 Table 1.4-3	Benzene	0.0021 lb/MMSCF	
AP-42 Table 1.4-3	Toluene	0.0034 lb/MMSCF	
AP-42 Table 1.4-3	Hexane	1.8 lb/MMSCF	
AP-42 Table 1.4-3	CHOH	0.075 lb/MMSCF	

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility Tyler County, WV

Source RBV-1

Burner Duty Rating	500.0 MBtu/hr
Burner Efficiency	98.0 %
Gas Heat Content (HHV)	1263.0 Btu/scf
Total Gas Consumption	9,695 scfd
H2S Concentration	0.000 Mole %
Hours of Operation	8760

NOx	0.0500	lb/hr	0.219	tpy
CO	0.0420	lb/hr	0.184	tpy
CO2	60.0	lb/hr	262.9	tpy
CO2e	60.4	lb/hr	264.5	tpy
VOC	0.0028	lb/hr	0.012	tpy
SO2	0.0003	lb/hr	0.001	tpy
H2S	0.0000	lb/hr	0.000	tpy
PM10	0.0038	lb/hr	0.017	tpy
CHOH	0.0000	lb/hr	0.000	tpy
Benzene	0.0000	lb/hr	0.000	tpy
N-Hexane	0.0009	lb/hr	0.004	tpy
Toluene	0.0000	lb/hr	0.000	tpy
Total HAPs	0.0009	lb/hr	0.004	tpy

AP-42 Factors Used

NOx	100 lb/MMCF	
CO	84 lb/MMCF	
CO ₂	120,000 lb/MMCF	Global Warming Potential = 1
VOC	5.5 lb/MMCF	
PM	7.6 lb/MMCF	
SO ₂	0.6 lb/MMCF	
CH ₄	2.3 lb/MMCF	Global Warming Potential = 25
N ₂ O	2.2 lb/MMCF	Global Warming Potential = 298
HCOH	0.075 lb/MMCF	
Benzene	0.0021 lb/MMCF	
n-Hexane	1.8 lb/MMCF	
Toluene	0.0034 lb/MMCF	

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

Potential Emission Rates

Source EC-2 Enclosed Combustor Pilot

Burner Duty Rating 985.1 MBtu/hr
Burner Efficiency 98.0 %
Gas Heat Content (HHV) 1263.0 Btu/scf
Total Gas Consumption 19100.9 scfd
H2S Concentration 0.000 Mole %
Hours of Operation 8760

NOx	0.0985	lb/hr	0.432	tpy
CO	0.0828	lb/hr	0.363	tpy
CO2	118.3	lb/hr	518.0	tpy
CO2e	119	lb/hr	521	tpy
VOC	0.0054	lb/hr	0.024	tpy
SO2	0.0006	lb/hr	0.003	tpy
H2S	0.0000	lb/hr	0.000	tpy
PM10	0.0075	lb/hr	0.033	tpy
CHOH	0.0001	lb/hr	0.000	tpy
Benzene	0.0000	lb/hr	0.000	tpy
N-Hexane	0.0018	lb/hr	0.008	tpy
Toluene	0.0000	lb/hr	0.000	tpy
Total HAPs	0.0019	lb/hr	0.008	tpy

AP-42 Factors Used (Tables 1.4.1-1.4.3)

NOx	100 lb/MMCF	
CO	84 lb/MMCF	
CO ₂	120,000 lb/MMCF	Global Warming Potential = 1
VOC	5.5 lb/MMCF	
PM	7.6 lb/MMCF	
SO ₂	0.6 lb/MMCF	
CH ₄	2.3 lb/MMCF	Global Warming Potential = 25
N ₂ O	2.2 lb/MMCF	Global Warming Potential = 298
HCOH	0.075 lb/MMCF	
Benzene	0.0021 lb/MMCF	
n-Hexane	1.8 lb/MMCF	
Toluene	0.0034 lb/MMCF	

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility Tyler County, WV

Potential Emission Rates

Source EC-2 Enclosed Vapor Combustor

Destruction Efficiency 98.0 %
 Gas Heat Content (HHV) 660.7 Btu/scf
 Max Flow to T-E 0.09264 MMSCFD 811.526 MMSCF/yr
 Max BTUs to Flare 2.55 MMBtu/hr 22,341 MMBtu/yr

NOx	0.17	lb/hr	0.76	tpy
CO	0.94	lb/hr	4.13	tpy
CO2	298.11	lb/hr	1,305.74	tpy
CO2e	298.42	lb/hr	1,307.09	tpy
VOC	0.80	lb/hr	3.51	tpy
CH4	0.01	lb/hr	0.0246	tpy
N2O	0.001	lb/hr	0.0025	tpy
PM	0.029	lb/hr	0.128	tpy
Benzene	0.010	lb/hr	0.042	tpy
CHOH	0.000	lb/hr	0.001	tpy
n-Hexane	0.020	lb/hr	0.086	tpy
Toluene	0.034	lb/hr	0.147	tpy
Total HAPs	0.063	lb/hr	0.276	tpy

Note: VOCs and HAPs are set at 2% of the still vent emissions in the Glycalc Report.

Factors Used

AP-42 Table 13.5-1	NOx	0.068 lb/MMBTU	
AP-42 Table 13.5-1	CO	0.37 lb/MMBTU	
40 CFR 98 Table C-1	CO2	116.89 lb/MMBTU	Global Warming Potential = 1
40 CFR 98 Table C-2	CH4	0.0022 lb/MMBTU	Global Warming Potential = 25
40 CFR 98 Table C-2	N2O	0.00022 lb/MMBTU	Global Warming Potential = 298
AP-42 Table 1.4-2	PM	7.6 lb/MMSCF	
AP-42 Table 1.4-3	CHOH	0.075 lb/MMSCF	

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

TL-1 Truck Loading - Condensate

Per AP-42, Chapter 5.2.2.1.1, the uncontrolled loading loss emission factor LL can be estimated as follows:

$$L_L = 12.46 * (SPM/T)$$

Where,

Loading Loss	$L_L =$	2.979 lb/1000 gallons
Saturation Factor	$S =$	0.6
True Vapor Pressure	$P =$	3.1 psia
Molecular Weight of Vapors	$M =$	66.84 lb/lb-mol
Temperature	$T =$	520 deg R

Maximum Daily Loading	100	BBL/day
	4,200	gpd
Hours of Loading	3	hr

Total VOC	8.9	lb/day	2.96	lb/hr
Total HAP	0.5	lb/day	0.16	lb/hr

Maximum Annual Loading	20,400	BBL/yr
	856,800	gpy

Total VOC	1813.7	lb/yr	0.91	tpy
Total HAP	98.0	lb/yr	0.05	tpy

Emissions

Total VOC	71.059	%
Total HAP	3.841	%

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

TL-2 Truck Loading - Produced Water

Per AP-42, Chapter 5.2.2.1.1, the uncontrolled loading loss emission factor LL can be estimated as follows:

$$L_L = 12.46 * (SPM/T)$$

Where,

Loading Loss	$L_L =$	0.132 lb/1000 gallons
Saturation Factor	$S =$	0.6
True Vapor Pressure	$P =$	0.3 psia
Molecular Weight of Vapors	$M =$	30.68 lb/lb-mol
Temperature	$T =$	520 deg R

Maximum Daily Loading	120	BBL/day
	5,040	gpd
Hours of Loading	3	hr

Total VOC	0.2	lb/day	0.08	lb/hr
Total HAP	0.0	lb/day	0.009	lb/hr

Maximum Annual Loading	43,200	BBL/yr
	1,814,400	gpy

Total VOC	87.3	lb/yr	0.04	tpy
Total HAP	9.6	lb/yr	0.00	tpy

Emissions

Total VOC	36.376	%
Total HAP	4.009	%

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

Truck Loading Fugitive Dust

Item Number	Description	Number of Wheels	Mean Vehicle Weight (tons)	Mean Vehicle Speed (mph)	Miles per Trip	Maximum Trips per Hour	Truck Capacity (BBL/Truck)	Maximum Trips per Year	Control	Control Efficiency (%)
1	Produced Water Transportation Trucks	18	27	10	1.75	1	80	540	None	---
2	Condensate Transportation Trucks	18	27	10	1.75	1	80	255	None	---
			54000	lbs						

		PM	PM-10
k =	Particle size multiplier	0.8	0.36
s =	Silt content of road surface material (%)	10	3
S =	Mean vehicle speed (mph)	10	10
W =	Mean vehicle weight (tons)	27	27
w =	Mean number of wheels per vehicle	18	27
p =	Number of days per year with precipitation >0.01 in.	157	157

$$E (\text{lb/ vehicle mile traveled}) = k \times 5.9 \times (s \div 12) \times (S \div 30) \times (W \div 3)^{0.7} \times (w \div 4)^{0.5} \times ((365 - p) \div 365)$$

Item 1 - Produced Water		PM	PM-10
E	lb/vmt	7.378804125	1.220015589
E	$[\text{lb} \div \text{VMT}] \times [\text{VMT} \div \text{trip}] \times [\text{Trips} \div \text{Hour}] = \text{lb/hr}$	12.913	2.135
E	$[\text{lb} \div \text{VMT}] \times [\text{VMT} \div \text{trip}] \times [\text{Trips} \div \text{Hour}] \times [\text{Ton} \div 2000 \text{ lb}] = \text{tpy}$	3.486	0.576

Item 2 - Condensate		PM	PM-10
E	lb/vmt	7.378804125	1.220015589
E	$[\text{lb} \div \text{VMT}] \times [\text{VMT} \div \text{trip}] \times [\text{Trips} \div \text{Hour}] = \text{lb/hr}$	12.913	2.135
E	$[\text{lb} \div \text{VMT}] \times [\text{VMT} \div \text{trip}] \times [\text{Trips} \div \text{Hour}] \times [\text{Ton} \div 2000 \text{ lb}] = \text{tpy}$	1.646	0.272

Flash Emission Calculations - Condensate

Using Gas-Oil Ratio Method

Un-Controlled

Site specific data

Gas-Oil-ratio	=	500 scf/bbl	Using GOW from comparable well pads.
Throughput	=	20,400 bbl/yr	
Stock tank gas molecular weight	=	39.56 g/mole	

Conversions

1 lb	=	453.6 g
1 mole	=	22.4 L
1 scf	=	28.32 L
1 ton	=	2000 lb

Equations

$$E_{TOT} = Q \frac{(bbl)}{(yr)} \times R \frac{(scf)}{(bbl)} \times \frac{28.32(L)}{1(scf)} \times \frac{1(mole)}{22.4(L)} \times MW \frac{(g)}{(mole)} \times \frac{1(lb)}{453.6(g)} \times \frac{1(ton)}{2000(lb)}$$

E_{TOT} = Total stock tank flash emissions (TPY)

R = Measured gas-oil ratio (scf/bbl)

Q = Throughput (bbl/yr)

MW = Stock tank gas molecular weight (g/mole)

$$E_{spec} = E_{TOT} \times X_{spec}$$

E_{spec} = Flash emission from constituent

X_{spec} = Weight fraction of constituent in stock tank gas

Flash Emissions

Constituent	TPY
Total	562.3396
VOC	394.5881
Nitrogen	1.41E-01
Carbon Dioxide	8.83E-01
Methane	5.58E+01
Ethane	1.11E+02
Propane	1.46E+02
Isobutane	3.94E+01
n-Butane	9.07E+01
2,2 Dimethylpropane	1.11E+00
Isopentane	3.10E+01
n-Pentane	3.26E+01
2,2 Dimethylbutane	1.18E+00
Cyclopentane	0.00E+00
2,3 Dimethylbutane	1.70E+00
2 Methylpentane	9.04E+00
3 Methylpentane	5.40E+00
n-Hexane	1.18E+01
Methylcyclopentane	8.60E-01
Benzene	2.02E-01
Cyclohexane	1.22E+00
2-Methylhexane	2.62E+00
3-Methylhexane	2.58E+00
2,2,4 Trimethylpentane	0.00E+00
Other C7's	2.45E+00
n-Heptane	3.79E+00
Methylcyclohexane	2.36E+00
Toluene	4.61E-01
Other C8's	3.85E+00
n-Octane	1.28E+00
Ethylbenzene	2.81E-02
M & P Xylenes	3.32E-01
O-Xylene	4.50E-02
Other C9's	1.60E+00
n-Nonane	3.82E-01
Other C10's	6.02E-01
n-Decane	7.87E-02
Undecanes (11)	8.44E-02

E_{TOT}

Sum of C3+

HAP

HAP

HAP

HAP

HAP

HAP

Flash Emission Calculations - Produced Water

Using Gas-Water Ratio Method

Un-Controlled

Site specific data

Gas-Water-ratio	=	4.06 scf/bbl	Using GOW from comparable well pads.
Throughput	=	43,200 bbl/yr	
Stock tank gas molecular weight	=	30.68 g/mole	

Conversions

1 lb	=	453.6 g
1 mole	=	22.4 L
1 scf	=	28.32 L
1 ton	=	2000 lb

Equations

$$E_{TOT} = Q \frac{(bbl)}{(yr)} \times R \frac{(scf)}{(bbl)} \times \frac{28.32(L)}{1(scf)} \times \frac{1(mole)}{22.4(L)} \times MW \frac{(g)}{(mole)} \times \frac{1(lb)}{453.6(g)} \times \frac{1(ton)}{2000(lb)}$$

E_{TOT} = Total stock tank flash emissions (TPY)

R = Measured gas-oil ratio (scf/bbl)

Q = Throughput (bbl/yr)

MW = Stock tank gas molecular weight (g/mole)

$$E_{spec} = E_{TOT} \times X_{spec}$$

E_{spec} = Flash emission from constituent

X_{spec} = Weight fraction of constituent in stock tank gas

Flash Emissions

Constituent	TPY
Total	7.4991
VOC	3.8354
Nitrogen	1.25E-01
Carbon Dioxide	1.13E-01
Methane	2.22E+00
Ethane	1.21E+00
Propane	8.62E-01
Isobutane	2.15E-01
n-Butane	6.07E-01
2,2 Dimethylpropane	9.52E-03
Isopentane	3.05E-01
n-Pentane	4.24E-01
2,2 Dimethylbutane	1.58E-02
Cyclopentane	0.00E+00
2,3 Dimethylbutane	3.05E-02
2 Methylpentane	1.70E-01
3 Methylpentane	1.10E-01
n-Hexane	2.96E-01
Methylcyclopentane	2.76E-02
Benzene	5.40E-03
Cyclohexane	3.80E-02
2-Methylhexane	8.26E-02
3-Methylhexane	8.59E-02
2,2,4 Trimethylpentane	0.00E+00
Other C7's	7.90E-02
n-Heptane	1.44E-01
Methylcyclohexane	7.63E-02
Toluene	1.18E-02
Other C8's	1.31E-01
n-Octane	4.11E-02
Ethylbenzene	8.25E-04
M & P Xylenes	6.75E-03
O-Xylene	7.50E-04
Other C9's	3.97E-02
n-Nonane	7.42E-03
Other C10's	8.70E-03
n-Decane	1.50E-03
Undecanes (11)	1.42E-03

E_{TOT}
Sum of C3+

HAP

HAP

HAP

HAP

HAP

HAP

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility

Tyler County, WV

Fugitive VOC Emissions

Volatile Organic Compounds, NMNEHC from gas analysis:	18.40 weight percent
Methane from gas analysis:	59.35 weight percent
Carbon Dioxide from gas analysis:	0.32 weight percent
HAPs from gas analysis:	
Hexane	0.62 weight percent
Gas Density:	0.0580 lb/scf

Emission Source:	Count	Oil & Gas Production*	VOC %	VOC (lb/hr)	VOC (tpy)	CO2 (lb/hr)	CO2 (tpy)	CH4 (lb/hr)	CH4 (tpy)	CO2e (tpy)	Hexane (tpy)
Pump Seals:											
Gas:	1	0.00529 lb/hr	18.4	0.001	0.004	0.000	0.000	0.003	0.0138	0.344	0.000
Valves:											
Gas/Vapor:	26	0.02700 scf/hr	18.4	0.007	0.033	0.000	0.001	0.024	0.1058	2.646	0.001
Light Liquid:	18	0.05000 scf/hr	100.0	0.052	0.229						
Low Bleed Pneumatic	-	1.39000 scf/hr	18.4	0.000	0.000	0.000	0.000	0.000	0.0000	0.000	0.000
Relief Valves:	3	0.04000 scf/hr	18.4	0.001	0.006	0.000	0.000	0.004	0.0181	0.452	0.000
Open-ended Lines, gas:	20	0.06100 scf/hr	18.4	0.013	0.057	0.000	0.001	0.042	0.1839	4.598	0.002
Sampling Connectors:											
Gas:	11	0.03300 lb/hr	18.4	0.067	0.293	0.001	0.005	0.215	0.9436	23.595	0.010
Light Liquid:	6	0.03300 lb/hr	100.0	0.198	0.867						
Connectors:											
Gas:	120	0.00300 scf/hr	18.4	0.004	0.017	0.000	0.000	0.012	0.0543	1.357	0.001
Light Liquid:	60	0.00700 scf/hr	100.0	0.024	0.107						
Compressor Seals, Gas:	1	0.01940 lb/hr	18.4	0.004	0.016	0.000	0.000	0.012	0.0504	1.261	0.001
Flanges:											
Gas:	80	0.00086 lb/hr	18.4	0.013	0.055	0.000	0.001	0.041	0.1788	4.472	0.002
Light Liquid:	40	0.00300 scf/hr	100.0	0.007	0.030						

Blowdowns:

	Pressure (psig)	Internal Volume (scf)	Projected Blowdown Events (per year)	Gas Released Per Year (scf)	Gas Released Per Year (lbs)	Composition of Gas (% by volume)	Released (lb/hr)	Released (tpy)	CO2e (tpy)
VOC	300	65	16	1040	124.8	0.70	0.0100	0.0438	
CH4	300	65	16	1040	44.0	0.10	0.0005	0.0022	0.0546
HAPs	300	65	16	1040	116.3	0.02	0.0003	0.0013	

Fugitive Calculations:

	lb/hr	tpy
VOC	0.401	1.757
CH4	0.354	1.551
CO2	0.002	0.008
CO2e	8.854	38.779
HAPs	0.004	0.018

Notes:

Factors are from 40 CFR 98, Table W-1A (scf/hr), where available. Remaining are API (lb/hr)
Sampling Connectors are from TECQ. Remaining are API (lb/hr)

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

Inlet Gas Composition Information:

	Fuel Gas mole %	Fuel M.W. lb/lb-mole	Fuel S.G.	Fuel Wt. %	LHV, dry Btu/scf	HHV, dry Btu/scf	AFR vol/vol	VOC NM / NE	Z Factor	GPM
Nitrogen, N2	0.394	0.110	0.004	0.530			-		0.0039	
Carbon Dioxide, CO2	0.151	0.066	0.002	0.319			-		0.0015	
Hydrogen Sulfide, H2S	-	-	-	-			-		-	
Helium, He	-	-	-	-			-		-	
Oxygen, O2	-	-	-	-			-		-	
Methane, CH4	77.080	12.366	0.427	59.347	701.0	778.5	7.346		0.7693	
Ethane, C2H6	14.832	4.460	0.154	21.405	240.1	262.5	2.474		0.1471	3.945
Propane	4.967	2.190	0.076	10.512	115.0	125.0	1.183	10.512	0.0488	1.361
Iso-Butane	0.616	0.358	0.012	1.718	18.5	20.0	0.191	1.718	0.0060	0.200
Normal Butane	1.210	0.703	0.024	3.375	36.4	39.5	0.375	3.375	0.0117	0.379
Iso Pentane	0.266	0.192	0.007	0.921	9.8	10.6	0.101	0.921	0.0027	0.097
Normal Pentane	0.262	0.189	0.007	0.907	9.7	10.5	0.100	0.907	0.0026	0.094
Hexane	0.151	0.130	0.004	0.625	6.6	7.2	0.068	0.625	0.0015	0.062
Heptane	0.071	0.071	0.002	0.341	3.6	3.9	0.037	0.341	0.0007	0.033
	100.000	20.837	0.719		1,140.8	1,257.7	11.875	18.400	0.9958	6.172

Gas Density (STP) = 0.058

Ideal Gross (HHV)	1,257.7
Ideal Gross (sat'd)	1,236.6
GPM	-
Real Gross (HHV)	1,263.0
Real Net (LHV)	1,145.6

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

Condensate Tank Flash Vapor Composition Information:

	Fuel Gas mole %	Fuel M.W. lb/lb-mole	Fuel S.G.	Fuel Wt. %	LHV, dry Btu/scf	HHV, dry Btu/scf	AFR vol/vol	VOC NM / NE	Z Factor	GPM
Nitrogen, N2	0.036	0.009	0.000	0.022			-		0.0003	
Carbon Dioxide, CO2	0.141	0.041	0.001	0.103			-		0.0009	
Hydrogen Sulfide, H2S	-	0.000	0.000	0.000	0.0	0.0	0.000		0.0000	
Helium, He	-	-	-	-			-		-	
Oxygen, O2	-	-	-	-			-		-	
Methane, CH4	24.485	3.370	0.116	8.458	191.0	212.2	2.002		0.2096	
Ethane, C2H6	25.943	8.112	0.280	20.358	436.7	477.4	4.500		0.2676	7.176
Propane	23.253	11.311	0.391	28.386	593.8	645.4	6.110	28.386	0.2520	7.030
Iso-Butane	4.773	3.064	0.106	7.690	158.2	171.4	1.633	7.690	0.0512	1.715
Normal Butane	10.980	6.916	0.239	17.357	358.3	388.2	3.685	17.357	0.1150	3.731
Iso Pentane	3.135	2.367	0.082	5.941	121.4	131.3	1.250	5.941	0.0328	1.195
Normal Pentane	3.175	2.307	0.080	5.791	118.5	128.2	1.219	5.791	0.0320	1.152
Hexane	2.378	1.531	0.053	3.841	78.2	84.5	0.804	3.841	0.0175	0.726
Heptane	1.701	0.818	0.028	2.052	41.6	44.9	0.428	2.052	0.0081	0.374
	100.000	39.846	1.376		2,097.7	2,283.4	21.630	71.059	0.9872	23.100

Gas Density (STP) = 0.111

Ideal Gross (HHV)	2,283.4
Ideal Gross (sat'd)	2,244.3
GPM	-
Real Gross (HHV)	2,313.1
Real Net (LHV)	2,124.9

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

Water Tank Flash Vapor Composition Information:

	Fuel Gas mole %	Fuel M.W. lb/lb-mole	Fuel S.G.	Fuel Wt. %	LHV, dry Btu/scf	HHV, dry Btu/scf	AFR vol/vol	VOC NM / NE	Z Factor	GPM
Nitrogen, N2	1.821	0.161	0.006	0.652			-		0.0057	
Carbon Dioxide, CO2	1.049	0.705	0.024	2.855			-		0.0160	
Hydrogen Sulfide, H2S	-	0.000	0.000	0.000	0.0	0.0	0.000		0.0000	
Helium, He	-	-	-	-			-		-	
Oxygen, O2	-	-	-	-			-		-	
Methane, CH4	56.602	11.902	0.411	48.188	674.7	749.3	7.070		0.7404	
Ethane, C2H6	16.424	2.946	0.102	11.929	158.6	173.4	1.634		0.0972	2.606
Propane	8.000	1.933	0.067	7.827	101.5	110.3	1.044	7.827	0.0431	1.202
Iso-Butane	1.516	1.070	0.037	4.332	55.2	59.9	0.570	4.332	0.0179	0.599
Normal Butane	4.274	1.187	0.041	4.808	61.5	66.6	0.633	4.808	0.0197	0.641
Iso Pentane	1.784	0.942	0.033	3.812	48.3	52.2	0.497	3.812	0.0131	0.475
Normal Pentane	2.405	0.670	0.023	2.711	34.4	37.2	0.354	2.711	0.0093	0.334
Hexane	2.953	0.990	0.034	4.009	50.6	54.6	0.520	4.009	0.0114	0.470
Heptane	3.172	2.192	0.076	8.877	111.6	120.4	1.147	8.877	0.0218	1.004
100.000	24.699	0.853			1,296.4	1,424.0	13.469	36.376	0.9954	7.331

Gas Density (STP) = 0.069

Ideal Gross (HHV)	1,424.0
Ideal Gross (sat'd)	1,399.9
GPM	-
Real Gross (HHV)	1,430.5
Real Net (LHV)	1,302.3

Jay-Bee Oil & Gas, Inc.

Moe Well Pad Production Facility
Tyler County, WV

Still Vent Gas Composition Information:

	Fuel Gas mole %	Fuel M.W. lb/lb-mole	Fuel S.G.	Fuel Wt. %	LHV, dry Btu/scf	HHV, dry Btu/scf	AFR vol/vol	VOC NM / NE	Z Factor	GPM
Nitrogen, N ₂	0.158	0.044	0.002	0.211	0.0	0.0	-		0.0016	
Carbon Dioxide, CO ₂	0.164	0.072	0.002	0.343	0.0	0.0	0.012		0.0016	
Hydrogen Sulfide, H ₂ S	-	-	-	-	0.0	0.0	-		-	
Water	54.800	9.864	0.341	46.930	0.0	0.0	-		0.5483	
Oxygen, O ₂	-	-	-	-	0.0	0.0	-		-	
Methane, CH ₄	30.600	4.909	0.170	23.356	278.3	309.1	5.104		0.3054	
Ethane, C ₂ H ₆	7.680	2.309	0.080	10.987	124.3	135.9	1.829		0.0762	2.043
Propane	3.300	1.455	0.050	6.923	76.4	83.0	1.022	6.923	0.0324	0.904
Iso-Butane	0.506	0.294	0.010	1.399	15.2	16.5	0.157	1.399	0.0049	0.165
Normal Butane	1.190	0.692	0.024	3.291	35.8	38.8	0.454	3.291	0.0115	0.373
Iso Pentane	0.278	0.201	0.007	0.954	10.3	11.1	0.113	0.954	0.0028	0.101
Normal Pentane	0.328	0.237	0.008	1.126	12.2	13.1	0.133	1.126	0.0033	0.118
Hexane	0.406	0.350	0.012	1.665	17.9	19.3	0.197	1.665	0.0040	0.166
Heptane	0.590	0.591	0.020	2.813	30.1	32.5	1.310	2.813	0.0059	0.271
	100.000	21.018	0.726		600.4	659.3	10.330	18.172	0.9979	4.141

Gas Density (STP) = 0.058

Ideal Gross (HHV)	659.3
Ideal Gross (sat'd)	648.7
GPM	-
Real Gross (HHV)	660.7
Real Net (LHV)	601.7

Jay-Bee Oil & Gas, Inc.

Specific Gravity of Air, @ 29.92 in. Hg and 60 -F, 28.9625
 One mole of gas occupies, @ 14.696 psia & 32 -F, 359.2 cu ft. per lb-mole
 One mole of gas occupies, @ 14.696 psia & 60 -F, 379.64 cu ft. per lb-mole

Hydrogen Sulfide (H₂S) conversion chart:

Q grains H ₂ S/100 scf	=	0.00000 mole % H ₂ S
		0.0 ppmv H ₂ S
Q mole % H ₂ S	=	Q grains H ₂ S/100 scf
		0.0 ppmv H ₂ S
Q ppmv H ₂ S	=	0.000 grains H ₂ S/100 scf
		0.00000 mole % H ₂ S

Ideal Gas at 14.696 psia and 60°F

		MW lb/mol	Specific Gravity	Lb per Cu Ft	Cu Ft per Lb	LHV, dry Btu/scf	HHV, dry Btu/scf	LHV Btu/lb	HHV Btu/lb	cu ft of air / 1 cu ft of gas	Z factor
Nitrogen	N ₂	28.013	0.9672	0.0738	13.552	0	0	0	0	0	0.9997
Carbon Dioxide	CO ₂	44.010	1.5196	0.1159	8.626	0	0	0	0	0	0.9964
Hydrogen Sulfide	H ₂ S	34.076	1.1766	0.0898	11.141	587	637	6,545	7,100	7.15	0.9846
Water	H ₂ O	18.000	0.6215	0.0474	21.091	0	0	0	0	0	1.0006
Oxygen	O ₂	31.999	1.1048	0.0843	11.864	0	0	0	0	0	0.9992
Methane	CH ₄	16.043	0.5539	0.0423	23.664	909.4	1,010.0	21,520	23,879	9.53	0.9980
Ethane	C ₂ H ₆	30.070	1.0382	0.0792	12.625	1,618.7	1,769.6	20,432	22,320	16.68	0.9919
Propane	C ₃ H ₈	44.097	1.5226	0.1162	8.609	2,314.9	2,516.1	19,944	21,661	23.82	0.9825
Iso-Butane	C ₄ H ₁₀	58.124	2.0069	0.1531	6.532	3,000.4	3,251.9	19,629	21,257	30.97	0.9711
Normal Butane	C ₄ H ₁₀	58.124	2.0069	0.1531	6.532	3,010.8	3,262.3	19,680	21,308	30.97	0.9667
Iso Pentane	C ₅ H ₁₂	72.151	2.4912	0.1901	5.262	3,699.0	4,000.9	19,478	21,052	38.11	1.0000
Normal Pentane	C ₅ H ₁₂	72.151	2.4912	0.1901	5.262	3,706.9	4,008.9	19,517	21,091	38.11	1.0000
Hexane	C ₆ H ₁₄	86.178	2.9755	0.2270	4.405	4,403.8	4,755.9	19,403	20,940	45.26	0.9879
Heptane	C ₇ H ₁₆	100.205	3.4598	0.2639	3.789	5,100.0	5,502.5	22,000	23,000	52.41	0.9947

Real Gas at 14.696 psia and 60°F

		MW lb/mol	Specific Gravity	Lb per Cu Ft	Cu Ft per Lb	LHV, dry Btu/scf	HHV, dry Btu/scf	LHV Btu/lb	HHV Btu/lb	cu ft of air / 1 cu ft of gas	Gal/Mole
Nitrogen	N ₂	28.013	0.9672	0.0738	13.552	0	0	0	0	0	4.1513
Carbon Dioxide	CO ₂	44.010	1.5196	0.1159	8.626	0	0	0	0	0	6.4532
Hydrogen Sulfide	H ₂ S	34.076	1.1766	0.0898	11.141	621	672	6,545	7,100	7.15	5.1005
Water	H ₂ O	18.000	0.6215	0.0474	21.091						3.8376
Oxygen	O ₂	31.999	1.1048	0.0843	11.864	0	0	0	0	0	3.3605
Methane	CH ₄	16.043	0.5539	0.0423	23.664	911	1,012	21,520	23,879	9.53	6.4172
Ethane	C ₂ H ₆	30.070	1.0382	0.0792	12.625	1,631	1,783	20,432	22,320	16.68	10.126
Propane	C ₃ H ₈	44.097	1.5226	0.1162	8.609	2,353	3,354	19,944	21,661	23.82	10.433
Iso-Butane	C ₄ H ₁₀	58.124	2.0069	0.1531	6.532	3,101	3,369	19,629	21,257	30.97	12.386
Normal Butane	C ₄ H ₁₀	58.124	2.0069	0.1531	6.532	3,094	3,370	19,680	21,308	30.97	11.937
Iso Pentane	C ₅ H ₁₂	72.151	2.4912	0.1901	5.262	3,709	4,001	19,478	21,052	38.11	13.86
Normal Pentane	C ₅ H ₁₂	72.151	2.4912	0.1901	5.262	3,698	4,009	19,517	21,091	38.11	13.713
Hexane	C ₆ H ₁₄	86.178	2.9755	0.2270	4.405	4,404	4,756	19,403	20,940	45.26	15.566
Heptane	C ₇ H ₁₆	100.205	3.4598	0.2639	3.789	5,101	5,503	22,000	23,000	52.41	17.468



USA Compression Partners, LLC

Unit Information Sheet

Date: May 27, 2014
Unit #: 6041
Customer: To Be Determined

To:

Lease Location: To Be Determined

Please find the below information for the USA Compression unit number listed above:

Package Information	
Compressor Manufacturer:	Arrow
Compressor Model:	VRC2
Compressor Serial Number:	12095
Compressor Cylinders:	6.5" x 4.0" x 2.25"
Driver Manufacturer:	Cummins
Driver Model:	G5.9
Rated HP & Speed	84 HP @ 1800 RPM
Driver Type:	4-stroke Rich Burn
Engine Serial Number:	73364060
Engine Manufacturing Date:	3/19/2012
Engine Catalyst Model:	VXC-1408-04-HSG
Engine Catalyst Element:	VX-RE-08XC
Engine AFR Model:	AFR-1RD-10-TK2
Engine Stack Height:	9' 5"
Engine Stack Diameter:	4"
Operating Information	
Suction Pressure:	N/A psig
Discharge Pressure:	N/A psig
Design Capacity:	N/A MSCFD
Gas Specific Gravity:	N/A

Emission Output information included in the attached catalyst specification sheet.

MIRATECH Emissions Control Equipment Specification Summary

Proposal Number: TJ-14-0081 Rev(1)

Engine Data

Number of Engines:	1
Application:	Gas Compression
Engine Manufacturer:	Cummins
Model Number:	G 5.9
Power Output:	84 bhp
Lubrication Oil:	0.6 wt% sulfated ash or less
Type of Fuel:	Natural Gas
Exhaust Flow Rate:	430 acfm (cfm)
Exhaust Temperature:	1,078°F

System Details

Housing Model Number:	VXC-1408-04-HSG
Element Model Number:	VX-RE-08XC
Number of Catalyst Layers:	1
Number of Spare Catalyst Layers:	1
System Pressure Loss:	3.0 inches of WC (Fresh)
Sound Attenuation:	28-32 dBA insertion loss
Exhaust Temperature Limits:	750 – 1250°F (catalyst inlet); 1350°F (catalyst outlet)

NSCR Housing & Catalyst Details

Model Number:	VXC-1408-04-XC1
Material:	Carbon Steel
Approximate Diameter:	14 inches
Inlet Pipe Size & Connection:	4 inch FF Flange, 150# ANSI standard bolt pattern
Outlet Pipe Size & Connection:	4 inch FF Flange, 150# ANSI standard bolt pattern
Overall Length:	53 inches
Weight Without Catalyst:	152 lbs
Weight Including Catalyst:	162 lbs
Instrumentation Ports:	1 inlet/1 outlet (1/2" NPT)

Emission Requirements

Exhaust Gases	Engine Outputs (g/ bhp-hr)	Reduction (%)	Warranted Converter Outputs (g/ bhp-hr)	Requested Emissions Targets
NOx	11.41	91%	1.00	1.00 g/bhp-hr
CO	14.64	86%	2.00	2.00 g/bhp-hr
NMNEHC	0.22	0%	0.70	0.70 g/bhp-hr
CH ₂ O	0.08	0%	1.00	1.00 g/bhp-hr
Oxygen	0.5%			

MIRATECH warrants the performance of the converter, as stated above, per the MIRATECH General Terms and Conditions of Sale.



Engine Performance Data

Cummins Inc

Columbus, Indiana 47202-3005
<http://www.cummins.com>

Industrial

G5.9

FR 9961

84 BHP (63 kW) @ 1800 RPM
245 lb-ft (332 N-m) @ 1800 RPM

Configuration
D491010CX02

CPL Code
8655


Revision
12-May-2011

Compression Ratio: **10.5:1**
Fuel System: **Field Gas, Dry Processed Nat Gas**
Emission Certification: **Non-certified**

Displacement: **359 in3 (5.9 L)**
Aspiration: **Naturally Aspirated**


All data is based on the engine operating with fuel system, water pump, and 7 in H₂O (1.74 kPa) inlet air restriction with 3.5 in (89 mm) inner diameter, and with 1 in Hg (3 kPa) exhaust restriction with 3 in (76 mm) inner diameter; not included are alternator, fan, optional equipment and driven components. Coolant flows and heat rejection data based on coolants as 50% ethylene glycol/50% water. All data is subject to change without notice.

Rating Type: Continuous/WMR




Torque Output

RPM	lb-ft	N-m
1,000	245	332
1,100	245	332
1,200	245	332
1,300	245	332
1,400	245	332
1,500	245	332
1,600	245	332
1,700	245	332
1,800	245	332



Power Output

RPM	hp	kW
1,000	47	35
1,100	51	38
1,200	56	42
1,300	61	45
1,400	65	48
1,500	70	52
1,600	75	56
1,700	79	59
1,800	84	63



Fuel Consumption @ 1,800 RPM

hp	kW	% Load	BTU/hp-hr	MJ/kW-hr
84	63	100	7,914	11.2
76	57	90	7,987	11.3
67	50	80	8,056	11.4
59	44	70	8,452	11.96
50	37	60	8,689	12.29
42	31	50	9,094	12.87
34	25	40	10,083	14.27
25	19	30	11,069	15.66
17	13	20	12,116	17.14
8	6	10	13,889	19.65

Data represents gross engine capabilities obtained and corrected in accordance with SAE J1995 using dry processed natural gas fuel with 905 BTU per standard cubic foot lower heating value. Deration may be required due to altitude, temperature and type of fuel. Consult Cummins Customer Engineering for operation above this altitude.

STATUS FOR CURVES AND DATA: Limited-(measured data)

TOLERANCE: Within +/- 5 %

CHIEF ENGINEER:

Alfred S Weber

Bold entries revised after 1-Mar-2010

© 2010, Cummins Inc., All Rights Reserved
Cummins Confidential and Proprietary
Controlled copy is located on gce.cummins.com

Intake Air System

Maximum allowable air temperature rise over ambient at Intake Manifold (Naturally Aspirated Engines) or Turbo Compressor inlet (Turbo-charged Engines): (This parameter impacts emissions, LAT and/or altitude capability)

15 delta deg F 8.3 delta deg C

Cooling System

Maximum coolant temperature for engine protection controls

215 deg F 102 deg C

Maximum coolant operating temperature at engine outlet (max. top tank temp):

212 deg F 100 deg C

Exhaust System

Maximum exhaust back pressure:

2 in-Hg 7 kPa

Recommended exhaust piping size (inner diameter):

3 in 76 mm

Lubrication System

Nominal operating oil pressure

@ minimum low idle

10 psi 69 kPa

@ maximum rated speed

50 psi 345 kPa

Minimum engine oil pressure for engine protection devices

@ minimum low idle

10 psi 69 kPa

Fuel System

Maximum fuel inlet pressure:

1 psi 5 kPa

Performance Data

Engine low idle speed:

900 RPM

Maximum low idle speed:

1,800 RPM

Minimum low idle speed:

800 RPM

Engine high idle speed

1,800 RPM

Governor break speed:

Maximum torque available at closed throttle low idle speed:

50 lb-ft 68 N-m

	100% Load		75% Load		50% Load	
Engine Speed	1,800 RPM		1,800 RPM		1,800 RPM	
Output Power	84 hp	63 kW	63 hp	47 kW	42 hp	31 kW
Torque	245 lb-ft	332 N-m	184 lb-ft	249 N-m	123 lb-ft	167 N-m
Intake Manifold Pressure	-1 in-Hg	-3 kPa	-5 in-Hg	-17 kPa	-9 in-Hg	-30 kPa
Inlet Air Flow	121 ft ³ /min	57 L/s	101 ft ³ /min	48 L/s	82 ft ³ /min	39 L/s
Exhaust Gas Flow	430 ft ³ /min	203 L/s	360 ft ³ /min	170 L/s	292 ft ³ /min	138 L/s
Exhaust Gas Temperature	1,078 deg F	581 deg C	999 deg F	537 deg C	902 deg F	483 deg C
Heat Rejection to Coolant	3,824 BTU/min	67 kW	3,244 BTU/min	57 kW	2,596 BTU/min	46 kW
Heat Rejection to Ambient	1,194 BTU/min	21 kW	784 BTU/min	14 kW	613 BTU/min	11 kW
Heat Rejection to Exhaust	2,523 BTU/min	44 kW	1,916 BTU/min	34 kW	1,371 BTU/min	24 kW
Fuel Consumption	7,914 BTU/hp-hr	11 MJ/kW-hr	8,214 BTU/hp-hr	12 MJ/kW-hr	9,094 BTU/hp-hr	13 MJ/kW-hr
Air Fuel Ratio (dry)	16.52 vol/vol		16.51 vol/vol		16.52 vol/vol	
Ignition timing (BTDC)	26 deg	26 deg	26 deg	26 deg	26 deg	26 deg
Total Hydrocarbons	1.48 g/hp-hr		1.3 g/hp-hr		1.62 g/hp-hr	
VOC ppm w/o Catalyst						
VOC ppm with Catalyst						
NOx	11.41 g/hp-hr	15.3 g/kW-hr	13.7 g/hp-hr	18.37 g/kW-hr	12.85 g/hp-hr	17.23 g/kW-hr
NOx ppm w/o Catalyst						
NOx ppm with Catalyst						
CO	14.64 g/hp-hr	19.63 g/kW-hr	0.82 g/hp-hr	1.1 g/kW-hr	1.38 g/hp-hr	1.85 g/kW-hr
CO ppm w/o Catalyst						
CO ppm with Catalyst						
CO ₂	449 g/hp-hr	602 g/kW-hr	489 g/hp-hr	656 g/kW-hr	540 g/hp-hr	724 g/kW-hr
O ₂	0.45 %		1.66 %		3.67 %	

Bold entries revised after 1-Mar-2010

Cranking System (Cold Starting Capability)

Unaided Cold Start:

Minimum cranking speed

250 RPM

Cold starting aids available

Block Heater, Oil Pan Heater

Maximum parasitic load at 10 deg F @

Noise Emissions

Top

89.9 dBa

Right Side

90.1 dBa

Left Side

89.8 dBa

Front

90.5 dBa

Exhaust noise emissions

103.1 dBa

Estimated Free Field Sound Pressure Level at 3.28ft (1m) and Full-Load Governed Speed
(Excludes Noise from Intake, Exhaust, Cooling System and Driven Components)

Aftercooler Heat Rejection - Heat Load on Aftercooler




BTU/min (kW)

Ambient Temp deg F (deg C)

Altitude ft (m)	Ambient Temp deg F (deg C)					
	120 (49)	110 (43)	100 (38)	90 (32)	80 (27)	70 (21)
0 (0)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)
1000 (305)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)
2000 (610)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)
3000 (914)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)
4000 (1219)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)
5000 (1524)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)
6000 (1829)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)
7000 (2134)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)
8000 (2438)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)
9000 (2743)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)
10000 (3048)	(.0)	(.0)	(.0)	(.0)	(.0)	(.0)


End of Report

Bold entries revised after 1-Mar-2010

	Gas/Site Analysis & Engine Selection/Derate Cummins Stationary Natural Gas Engines Date: 4/10/2014		Industrial G5.9 Available FR Number(s) From Selection: FR9936, FR9961	NG 84 HP (63 kW) @1800 RPM & 10.5:1 Compression Ratio Catalyst Fuel Rating Industrial Continuous
Engine (as entered by user)				
Application: Fuel Type: Engine: Fuel Rating: Compression Ratio: RPM: HP (Natural Gas): HP (Propane):		Industrial NG G5.9 Catalyst 10.5:1 1800 84 HP (63 kW) NA HP (NA kW)		
Site (as entered by user)				
Ambient Air Temperature: Relative Humidity: Altitude: Cooling Fan Load: Generator Efficiency: Vapor Pressure (Calculated from Site Conditions Entered): Dew Point (Calculated from Site Conditions Entered): Dry Barometer (Calculated from Site Conditions Entered):		90° F 30% 1200 ft 8 HP 93% 0.427 inHg 54.4° F 28.22 inHg		
Derate (Natural Gas)				
Advertised NG Rating: Engine Derate Due to Site Altitude and Temperature: Engine Derate Due to Gas Composition: Derate Due to Low BTU Fuel: Derate Due to Methane Number: Total Power Available (%) After All Applicable Derates: Total Site Derate due to Altitude, Temperature, and Gas Composition: Total Available Horsepower from Selected Engine Running on Specified Fuel Composition at Specified Site (includes 8 HP reduction for for cooling fan load):		84 HP (63 kW) 2% 0% 0% 98% of rated 2 HP (1 kW) 74 HP (55 kW)		 The sample percentage for "Name Sample" is 99.991%. Results are based on the input sample normalized to 100%.
Derate (Propane)				
Advertised Propane Rating: Engine Derate Due to Site Altitude and Temperature: Total Power Available (%) After All Applicable Derates: Total Site Derate due to Altitude and Temperature: Total Available Horsepower from Selected Engine Running on Propane at Specified Site (includes 8 HP reduction for for cooling fan load):		NA HP (NA kW) NA% NA% of rated NA HP (NA kW) NA HP (NA kW)		
Intake Manifold Requirements for Turbocharged Engines				
Maximum Allowed Intake Manifold Temperature for Selected Engine is na °F with a Maximum Aftercooler Water Inlet (CAC air inlet) of na °F based on FR9936				
Factory Set Points		Factory Supplied	Recommended	
Engine Speed Target: Spark Plug Gap: Excess Oxygen Target-PV: Propane Engine Timing Target: Propane Gas over air Press at Carb Low: Propane Gas Press at Sec Reg Target: Excess Oxygen Target-NG: Natural Gas Engine Timing Target: Natural Gas over air Press at Carb Target: Natural Gas Press at Sec Reg Target:		1800 rpm 0.020 in na %O2 na °BTDC na inH2O na inH2O 0.45% O ₂ Factory: 26 °BTDC 5 inH2O 15 inH2O	 NOTICE: A Change to Ignition Timing Is Recommended Due to Methane Number of Fuel Recommended Timing: 25 ° BTDC	

FR9936 Created/Revised On: 4/30/2013. Data Files Updated On: 12/12/2013

©2014 Cummins Inc., All Rights Reserved
 All Data is Subject To Change Without Notice
 Information contained in this report may be considered ©2014 Cummins Confidential
 Discretion is recommended when distributing. All rights reserved.
 Cummins, Inc. reserves the right to make changes at any time without obligation.

Gas Sample Analysis		
		 <p>The sample percentage for "Name Sample" is 99.991%. Results are based on the input sample normalized to 100%.</p>
Sample Name: Name Sample		
Gas Compound:	Volume Fraction % (User Input)	Mass Fraction % (Calculated)
Methane:	77.09	59.36
Ethane:	14.83	21.41
Propane:	4.97	10.51
i-Butane:	0.62	1.72
n-Butane:	1.21	3.38
i-Pentane:	0.27	0.92
n-Pentane:	0.26	0.91
n-Hexane:	0.15	0.62
n-Heptane:	0.04	0.2
n-Octane:	0.02	0.09
n-Nonane:	0	0
n-Decane:	0	0.02
Hydrogen:	0	0
Hydrogen Sulfide (H ₂ S):	0 ppm	0 ppm
Carbon Dioxide:	0.15	0.32
Carbon Monoxide:	0	0
Nitrogen:	0.39	0.53
Oxygen:	0	0
Total Percent: (Sample Input Percentage: 99.991%)	Normalized Percentage: 100%	
Performance Parameters:		
		Standard Units
Lower Heating Value (LHV): Standard Conditions (60F/14.696psia)	by volume	1140.6 Btu/scf
	by mass	20776 Btu/lbm
Higher Heating Value (HHV): Standard Conditions (60F/14.696psia)	by volume	1257.5 Btu/scf
	by mass	22906 Btu/lbm
Methane Number:		56.1
Specific Gravity (SG):		0.7193
Wobbe Index :	LHV/√ SG	1345 Btu/scf
	HHV/√ SG	1483 Btu/scf
Molecular Weight:		20.83 g/mol
Specific Heat (Cp):		0.473 BTU/lbm-R
Specific Heat Ratio (Cp/Cv):		1.253
Ideal Gas Density:		0.0549 lbm/ft3
H/C Ratio:		3.492
Gas Constant (R _{GAS}):		95.3 BTU/lbm-°R
Stoich Air Fuel Ratio (Dry):		16.54
Fuel Flow Data		
BTU/HP-HR:	7914	
Maximum Fuel Flow (SCFH):	583	
Maximum Fuel Flow Calculation is Based on 100% Continuous Rating of 84 HP at 1800 RPM and 10.5:1 Compression Ratio from FR9936		
Gas Regulator Details		
The Industrial G5.9 uses a Maxitrol Regulator		Notes:

FR Differences for Selected Engine		
Description of FR Differences for Selected Engine		
	FR9936	FR9961
Exhaust Manifold	Dry	Wet
Exhaust Stack Temp High	1300	1220

©2014 Cummins Inc., All Rights Reserved
All Data is Subject To Change Without Notice
Information contained in this report may be considered ©2014 Cummins Confidential
Discretion is recommended when distributing. All rights reserved.
Cummins, Inc. reserves the right to make changes at any time without obligation.

Gas Analysis Tool

References & Standards

Date: 4/10/2014

Tool Revision Date: 3/27/2014

[illegible]

All Data is Subject To Change Without Notice

Discretion is recommended when distributing. All rights reserved.

Cummins, Inc. reserves the right to make changes at any time without obligation.

Model 5120 Thermoelectric Generators



Standard Features

- Automatic Spark Ignition (SI)
- Fuel Filter
- Low Voltage Alarm Contacts (VSR)
- Volt & Amp Meter

Optional Features

- Cathodic Protection Interface
- Pole Mount or bench stand
- Automatic Fuel Shut-off (SO)
- Corrosive Environmental Fuel System
- Flame Arrestor

Note: Specifications shown are for standard configurations. Global Thermoelectric's Applications Engineering Department is available to design custom voltages, fuel supply systems and non-standard operating temperatures.



Power where you need it.

Global Thermoelectric's Model 5120 Thermoelectric Generator contains no moving parts. It is a reliable, low maintenance source of DC electrical power for any application where regular utilities are unavailable or unreliable.

Power Specifications

Power Rating at 20°C

120 Watts at 6.7 Volts

108 Watts at 12 Volts

108 Watts at 24 Volts

108 Watts at 48 Volts

Electrical

Adjustment:	6.7V	up to 11 Volts
	12 V	12 - 18 Volts
	24 V	24 - 30 Volts
	48 V	48 - 60 Volts

Reverse current protection included.

Output: Terminal block which accepts up to 8 AWG wire. Opening for 3/4" conduit in the base of the cabinet.

Fuel

Natural Gas:	8.8 m ³ /day (311 ft ³ /day) of Std. 1000 BTU/SCF (37.7 MJ/SM ³) gas
Propane:	11.4 l/day (3.0 US gal/day)
Max. Supply Pressure:	1724 kPa (250 psi)
Min. Supply Pressure:	103 kPa (15 psi)
Fuel Connection:	1/4" MNPT

Environmental

Ambient Operation Temperature: Max. 55°C (130°F) Min. -55°C (-67°F)


Operating Conditions: Unsheltered operation

Materials of Construction

Cabinet:	304 SS
Cooling Type:	Natural Convection
Thermopile:	Hermetically Sealed Lead Tin-Telluride (PbSnTe)
Burner:	Meeker Type/Inconel 600
Fuel System:	Brass, Aluminum & SS



Typical Installation



NOTES:

1. GENERATOR WEIGHT: 60 kg [132 lb].
2. DIMENSIONS IN mm [INCHES].



Power where you need it.

Corporate Office

#9, 3700 - 78 Avenue SE
Calgary, Alberta T2C 2L8
CANADA
Phone: (403) 236-5556
Fax: (403) 236-5575

US Sales

P.O. Box 38624
Houston, TX 77238
Phone: (281) 445-1515
Fax: (281) 445-6060
Toll Free: 1 800 848-4113


Model 5120 Thermoelectric Generator

Vapor Combustor Unit (VCU)


HY-BON/EDI is pleased to provide the CH2.5 and CH10.0 enclosed combustors as an effective solution for eliminating VOC emissions. HY-BON/EDI's insulated combustors are automated and have been successfully tested per EPA 40, CFR 60 guidelines – making it the perfect blend of performance and safety. The combustor comes as a complete, skid mounted package containing the liquid knock-out vessel, liquid transfer pump, flame arrestor, bird screen and burner control system. Installation is simple and field performance adjustments can be made as production changes – making it the most flexible solution in the industry.

- EPA 40 CFR 60, Quad O Compliant
[List of EPA Approved Combustion Control Devices](#)
- Completely Enclosed Combustion
- 99.99% Destruction Efficiency
- User Friendly Automated System
- Operational and Quad O reporting data can be saved to a USB Key
- RS-232 or RS-485 Communication supports satellite, cellular, or radio
- Modbus Slave Protocol allows it to communicate with SCADA systems and other devices/software

GENERAL PROPERTIES	CH2.5	CH10.0
BURNER SIZE (MMBTU/hr)	2.5	10.0
OUTER DIAMETER (inches)	34	54
HEIGHT (feet)	16	20
INLET PRESSURE (oz/in ²)	≥ 0.5	
DESTRUCTION EFFICIENCY	≥ 99.99%	
SMOKELESS CAPACITY	100%	
TURN DOWN	SCALABLE	




With the fairly recent publication of the NSPS OOOO emission standard, all storage tank facilities constructed on or after August 23, 2011 will be allowed to emit 6 Tons or less of VOC's per year. This regulation not only forces companies to monitor and control their emissions, but it also forces the *means* of emission monitoring and controlling to be more reliable and exact. In response to such a stringent protocol, HY-BON Engineering Company is pleased to offer the **CH10.0** enclosed Vapor Combustor Unit (VCU). Built upon a foundation of 60+ years' experience with tank vapors, the VCU is the solution for reducing residual tank vapor emissions when a Vapor Recovery Unit (VRU) is not sufficient or a viable option.



- EPA 40 CFR 60, Quad O Compliant
- Completely Enclosed Combustion
- 99.99% Destruction Efficiency
- Fully Automated System
- Output Operational Data via Thumb Drive
- Capable of SCADA Integration

GENERAL PROPERTIES	
TYPE	Enclosed Tank Battery Flare
AMBIENT TEMPERATURE	-20 °F to +100 °F
PILOT FUEL REQUIREMENTS	Propane or Site Gas @5psi of natural gas = 13.3 SCFM @5psi of propane = 12.5 SCFM
BURNER SIZE	10.0 million BTU/hr
INLET PRESSURE REQUIREMENTS	Minimum 0.5 oz/in ² (~1.0 inches w.c.)
TURN DOWN RATIO	5:1
DESTRUCTION EFFICIENCY	99.99% DRE
MECHANICAL PROPERTIES	
DESIGN WIND SPEED	100 MPH
AMBIENT TEMPERATURE	-20 °F to +120 °F
ELECTRICAL AREA CLASSIFICATION	General Area Classification (Non-Hazardous)
ELEVATION	up to 3,000ft ASL
PROCESS PROPERTIES	
SMOKELESS CAPACITY	100%
OPERATING TEMPERATURE	800 °F to 2000 °F (1500 °F Nominal)
UTILITIES	
PILOT GAS	Process Gas
ELECTRICITY	1 Phase, 60 Hz, 120V/10A
SOLAR PANEL OPTION AVAILABLE	YES

CH10.0: Flow Rate vs Flow Pressure with Corresponding Specific Gravity





Certificate of Analysis
Number: 2030-14030288-003A

Carencro Laboratory
4780 NE Evangeline Thruway
Carencro, LA 70620

Alan Ball
Gas Analytical Services
PO Box 1028
Bridgeport, WV 26330

Apr. 02, 2014

Field: Jay Bee Oil & Gas
Station Name: RPT 8-1H
Sample Point: Submeter
Cylinder No: 0258
Analyzed: 04/01/2014 13:29:16 by GR14

Sampled By: DW-GAS
Sample Of: Gas Spot
Sample Date: 03/25/2014 12:00
Sample Conditions: 290 psig
Method: GPA 2286

Analytical Data

Components	Mol. %	Wt. %	GPM at 14.73 psia	
Nitrogen	0.394	0.530		GPM TOTAL C2+ 6.223
Carbon Dioxide	0.151	0.319		
Methane	77.080	59.336		
Ethane	14.832	21.401	3.980	
Propane	4.967	10.510	1.373	
Iso-Butane	0.616	1.718	0.202	
n-Butane	1.210	3.375	0.383	
Iso-Pentane	0.266	0.921	0.097	
n-Pentane	0.262	0.907	0.095	
i-Hexanes	0.093	0.376	0.037	
n-Hexane	0.058	0.239	0.023	
Benzene	0.001	0.004	NIL	
Cyclohexane	0.006	0.023	0.002	
i-Heptanes	0.031	0.150	0.014	
n-Heptane	0.011	0.056	0.005	
Toluene	0.002	0.008	0.001	
i-Octanes	0.015	0.080	0.007	
n-Octane	0.002	0.012	0.001	
Ethylbenzene	NIL	NIL	NIL	
Xylenes	NIL	NIL	NIL	
i-Nonanes	NIL	NIL	NIL	
n-Nonane	NIL	NIL	NIL	
Decane Plus	0.003	0.035	0.003	
	100.000	100.000	6.223	

Physical Properties	Total	C10+
Calculated Molecular Weight	20.84	162.34
GPA 2172-09 Calculation:		
Calculated Gross BTU per ft ³ @ 14.73 psia & 60°F		
Real Gas Dry BTU	1265.2	8778.9
Water Sat. Gas Base BTU	1243.1	8626.1
Relative Density Reel Gas	0.7218	5.6078
Compressibility Factor	0.9964	

Patricia L. Petro

Hydrocarbon Laboratory Manager

Quality Assurance:

The above analyses are performed in accordance with ASTM, UOP, GPA guidelines for quality assurance, unless otherwise stated.



Certificate of Analysis
Number: 2030-14030288-003A

Carencro Laboratory
4790 NE Evangeline Thruway
Carencro, LA 70520

Alan Ball
Gas Analytical Services
PO Box 1028
Bridgeport, WV 26330

Apr. 02, 2014

Field: Jay Bee Oil & Gas
Station Name: RPT 8-1H
Sample Point: Submeter
Cylinder No: 0258
Analyzed: 04/01/2014 13:29:16 by GR14

Sampled By: DW-GAS
Sample Of: Gas Spot
Sample Date: 03/25/2014 12:00
Sample Conditions: 290 psig
Method: GPA 2286

Analytical Data

Components	Mol. %	Wt. %	GPM at 14.73 psia		
Nitrogen	0.394	0.630		GPM TOTAL C2+	8.223
Carbon Dioxide	0.151	0.319		GPM TOTAL C3+	2.243
Methane	77.080	59.336		GPM TOTAL IC5+	0.285
Ethane	14.832	21.401	3.980		
Propane	4.967	10.510	1.373		
iso-butane	0.818	1.718	0.202		
n-Butane	1.210	3.375	0.383		
iso-pentane	0.268	0.921	0.097		
n-Pentane	0.262	0.907	0.095		
Hexanes Plus	0.222	0.983	0.093		
	100.000	100.000	8.223		

Physical Properties	Total	C8+
Relative Density Real Gas	0.7218	3.1591
Calculated Molecular Weight	20.84	91.60
Compressibility Factor	0.9984	
GPA 2172-09 Calculation:		
Calculated Gross BTU per ft ³ @ 14.73 psia & 60°F		
Real Gas Dry BTU	1286.2	5014.1
Water Sat. Gas Base BTU	1243.1	4926.8
Comments: H2O Mol% : 1.740 ; Wt% : 1.506		

Patricia L. Peters

Hydrocarbon Laboratory Manager

Quality Assurance:

The above analyses are performed in accordance with ASTM, UOP, GPA guidelines for quality assurance, unless otherwise stated.



Certificate of Analysis

Number: 2030-14030288-003A

Carencro Laboratory
4790 NE Evangeline Thruway
Carencro, LA 70520

Alan Ball
Gas Analytical Services
PO Box 1028
Bridgeport, WV 26330

Apr. 02, 2014

Field: Jay Bee Oil & Gas
Station Name: RPT 8-1H
Sample Point: Submeter
Cylinder No: 0258
Analyzed: 04/01/2014 13:29:16 by GR14

Sampled By: DW-GAS
Sample Of: Gas Spot
Sample Date: 03/26/2014 12:00
Sample Conditions: 280 psig
Method: GPA 2286

Analytical Data

Components	Mol. %	Wt. %	GPM at 14.73 psia		
Nitrogen	0.394	0.530		GPM TOTAL C2+	6.223
Carbon Dioxide	0.151	0.319		GPM TOTAL C3+	2.243
Methane	77.080	69.336		GPM TOTAL IC5+	0.285
Ethane	14.832	21.401	3.980		
Propane	4.967	10.510	1.373		
Iso-Butane	0.616	1.718	0.202		
n-Butane	1.210	3.376	0.383		
Iso-Pentane	0.266	0.921	0.097		
n-Pentane	0.262	0.907	0.096		
Hexanes	0.151	0.616	0.060		
Heptanes Plus	0.071	0.368	0.033		
	100.000	100.000	6.223		

Physical Properties	Total	C7+
Relative Density Real Gas	0.7218	3.6570
Calculated Molecular Weight	20.84	103.02
Compressibility Factor	0.9964	

GPA 2172-08 Calculation:

Calculated Gross BTU per ft³ @ 14.73 psia & 60°F

Real Gas Dry BTU	1265.2	5577.8
------------------	--------	--------

Water Sat. Gas Base BTU	1243.1	5480.7
-------------------------	--------	--------

Comments: H₂O Mol% : 1.740 ; Wt% : 1.508

Hydrocarbon Laboratory Manager

Quality Assurance:

The above analyses are performed in accordance with ASTM, UOP, GPA guidelines for quality assurance, unless otherwise stated.



FESCO, Ltd.
1100 Fesco Avenue - Alice, Texas 78332

For: Jay-Bee Oil & Gas, Inc.
 1720 Route 22 East
 Union, New Jersey 07083

Date Sampled: 04/07/14

Date Analyzed: 04/21/14

Sample: RPT 8-1

Job Number: J42794

FLASH LIBERATION OF HYDROCARBON LIQUID		
	Separator HC Liquid	Stock Tank
Pressure, psig	340	0
Temperature, °F	65	70
Gas Oil Ratio (1)	-----	500
Gas Specific Gravity (2)	-----	1.387
Separator Volume Factor (3)	1.2987	1.000

STOCK TANK FLUID PROPERTIES	
Shrinkage Recovery Factor (4)	0.7700
Oil API Gravity at 60 °F	70.79
Reid Vapor Pressure, psi (5)	5.28

Quality Control Check			
	Sampling Conditions	Test Samples	
Cylinder No.	-----	W-2408*	W-2423
Pressure, psig	340	299	297
Temperature, °F	65	66	66

(1) - Sct of flashed vapor per barrel of stock tank oil

(2) - Air = 1.000

(3) - Separator volume / Stock tank volume

(4) - Fraction of first stage separator liquid

(5) - Absolute pressure at 100 deg F

Analyst: M. G.

* Sample used for flash study

Base Conditions: 14.85 PSI & 60 °F

Certified: FESCO, Ltd. - Alice, Texas

David Dannhaus 361-661-7015

April 23, 2014

FESCO, Ltd.
1100 Fesco Ave. - Alice, Texas 78332

For: Jay-Bee Oil & Gas, Inc.
1720 Route 22 East
Union, New Jersey 07083

Sample: RPT 8-1

Gas Evolved from Hydrocarbon Liquid Flashed
From 340 psig & 65 °F to 0 psig & 70 °F

Date Sampled: 04/07/14

Job Number: 42794.001

CHROMATOGRAPH EXTENDED ANALYSIS - SUMMATION REPORT - GPA 2286

COMPONENT	MOL%	GPM
Hydrogen Sulfide*	< 0.001	
Nitrogen	0.036	
Carbon Dioxide	0.141	
Methane	24.485	
Ethane	25.943	6.993
Propane	23.253	6.457
Isobutane	4.773	1.574
n-Butane	10.980	3.489
2-2 Dimethylpropane	0.108	0.042
Isopentane	3.027	1.116
n-Pentane	3.175	1.180
Hexanes	2.378	0.988
Heptanes Plus	<u>1.701</u>	<u>0.761</u>
Totals	100.000	22.579

Computed Real Characteristics Of Heptanes Plus:

Specific Gravity ----- 3.599 (Air=1)
Molecular Weight ----- 102.69
Gross Heating Value ----- 5488 BTU/CF

Computed Real Characteristics Of Total Sample:

Specific Gravity ----- 1.387 (Air=1)
Compressibility (Z) ----- 0.9850
Molecular Weight ----- 39.56
Gross Heating Value
Dry Basis ----- 2321 BTU/CF
Saturated Basis ----- 2282 BTU/CF

*Hydrogen Sulfide tested in laboratory by: Stained Tube Method (GPA 2377)
Results: <0.013 Gr/100 CF, <0.2 PPMV or <0.001 Mol %

Base Conditions: 14.850 PSI & 60 Deg F

Analyst: MR
Processor: AL
Cylinder ID: ST# 20

Certified: FESCO, Ltd. - Alice, Texas

David Dannhaus 361-661-7015

CHROMATOGRAPH EXTENDED ANALYSIS
TOTAL REPORT - GPA 2286

COMPONENT	MOL %	GPM	WT %
Hydrogen Sulfide*	< 0.001		< 0.001
Nitrogen	0.036		0.025
Carbon Dioxide	0.141		0.157
Methane	24.485		9.930
Ethane	25.943	6.993	19.719
Propane	23.253	6.457	25.920
Isobutane	4.773	1.574	7.013
n-Butane	10.980	3.489	16.132
2,2 Dimethylpropane	0.108	0.042	0.197
Isopentane	3.027	1.116	5.521
n-Pentane	3.175	1.160	5.791
2,2 Dimethylbutane	0.096	0.040	0.209
Cyclopentane	0.000	0.000	0.000
2,3 Dimethylbutane	0.139	0.057	0.303
2 Methylpentane	0.736	0.309	1.608
3 Methylpentane	0.441	0.181	0.961
n-Hexane	0.964	0.400	2.100
Methylcyclopentane	0.072	0.025	0.153
Benzene	0.018	0.005	0.036
Cyclohexane	0.102	0.035	0.217
2-Methylhexane	0.184	0.086	0.466
3-Methylhexane	0.181	0.083	0.458
2,2,4 Trimethylpentane	0.000	0.000	0.000
Other C7's	0.174	0.076	0.436
n-Heptane	0.266	0.124	0.674
Methylcyclohexane	0.189	0.068	0.419
Toluene	0.035	0.012	0.082
Other C8's	0.246	0.115	0.685
n-Octane	0.079	0.041	0.228
Ethylbenzene	0.002	0.001	0.005
M & P Xylenes	0.022	0.009	0.059
O-Xylene	0.003	0.001	0.008
Other C9's	0.089	0.046	0.284
n-Nonane	0.021	0.012	0.068
Other C10's	0.030	0.018	0.107
n-Decane	0.004	0.002	0.014
Undecanes (11)	<u>0.004</u>	<u>0.002</u>	<u>0.015</u>
Totals	100.000	22.579	100.000

Computed Real Characteristics Of Total Sample:

Specific Gravity -----	1.387	(Air=1)
Compressibility (Z) -----	0.9850	
Molecular Weight -----	39.56	
Gross Heating Value		
Dry Basis -----	2321	BTU/CF
Saturated Basis -----	2282	BTU/CF

May 2, 2014

FESCO, Ltd.
1100 Fesco Ave. - Alice, Texas 78332

For: Jay-Bee Oil & Gas, Inc.
1720 Route 22 East
Union, New Jersey 07083

Sample: RPT 8-1
Breathing Vapor
From 0 psig & 70 °F to 0 psig & 100 °F

Date Sampled: 04/07/14

Job Number: 42794.011

CHROMATOGRAPH EXTENDED ANALYSIS - SUMMATION REPORT - GPA 2286

COMPONENT	MOL%	GPM
Hydrogen Sulfide*	< 0.001	
Nitrogen	0.185	
Carbon Dioxide	0.018	
Methane	0.000	
Ethane	0.202	0.054
Propane	10.137	2.815
Isobutane	8.852	2.920
n-Butane	30.167	9.586
2-2 Dimethylpropane	0.370	0.142
Isopentane	15.123	5.574
n-Pentane	17.412	6.361
Hexanes	13.160	5.466
Heptanes Plus	<u>4.374</u>	<u>1.881</u>
Totals	100.000	34.799

Computed Real Characteristics Of Heptanes Plus:

Specific Gravity ----- 3.547 (Air=1)
Molecular Weight ----- 98.01
Gross Heating Value ----- 5251 BTU/CF

Computed Real Characteristics Of Total Sample:

Specific Gravity ----- 2.412 (Air=1)
Compressibility (Z) ----- 0.9539
Molecular Weight ----- 66.64
Gross Heating Value
Dry Basis ----- 3921 BTU/CF
Saturated Basis ----- 3853 BTU/CF

*Hydrogen Sulfide tested in laboratory by: Stained Tube Method (GPA 2377)

Results: <0.013 Gr/100 CF, <0.2 PPMV or <0.001 Mol %

Base Conditions: 14.850 PSI & 60 Deg F

Certified: FESCO, Ltd. - Alice, Texas

Analyst: MR
Processor: AL
Cylinder ID: ST# 21

David Dannhaus 361-661-7015

**CHROMATOGRAPH EXTENDED ANALYSIS
TOTAL REPORT - GPA 2286**

COMPONENT	MOL %	GPM	WT %
Hydrogen Sulfide*	< 0.001		< 0.001
Nitrogen	0.185		0.078
Carbon Dioxide	0.018		0.012
Methane	0.000		0.001
Ethane	0.202	0.054	0.091
Propane	10.137	2.815	6.708
Isobutane	8.852	2.920	7.721
n-Butane	30.167	9.586	26.312
2,2 Dimethylpropane	0.370	0.142	0.401
Isopentane	15.123	5.574	16.374
n-Pentane	17.412	6.361	18.852
2,2 Dimethylbutane	0.570	0.240	0.737
Cyclopentane	0.000	0.000	0.000
2,3 Dimethylbutane	0.805	0.332	1.041
2 Methylpentane	4.259	1.782	5.508
3 Methylpentane	2.477	1.019	3.203
n-Hexane	5.049	2.093	6.529
Methylcyclopentane	0.356	0.124	0.450
Benzene	0.078	0.022	0.091
Cyclohexane	0.432	0.148	0.545
2-Methylhexane	0.606	0.284	0.911
3-Methylhexane	0.589	0.261	0.856
2,2,4 Trimethylpentane	0.000	0.000	0.000
Other C7's	0.649	0.285	0.966
n-Heptane	0.658	0.306	0.989
Methylcyclohexane	0.408	0.165	0.601
Toluene	0.071	0.024	0.098
Other C8's	0.379	0.178	0.627
n-Octane	0.082	0.042	0.141
Ethylbenzene	0.002	0.001	0.003
M & P Xylenes	0.020	0.008	0.032
O-Xylene	0.002	0.001	0.003
Other C9's	0.048	0.025	0.091
n-Nonane	0.007	0.004	0.013
Other C10's	0.005	0.003	0.011
n-Decane	0.002	0.001	0.004
Undecanes (11)	<u>0.000</u>	<u>0.000</u>	<u>0.000</u>
Totals	100.000	34.799	100.000

Computed Real Characteristics Of Total Sample:

Specific Gravity -----	2.412	(Air=1)
Compressibility (Z) -----	0.9539	
Molecular Weight -----	66.64	
Gross Heating Value		
Dry Basis -----	3921	BTU/CF
Saturated Basis -----	3853	BTU/CF



FESCO, Ltd.
1100 Fesco Avenue - Alice, Texas 78332

For: SE Technologies, LLC
Building D, Second Floor
98 Vanadium Road
Bridgeville, Pennsylvania 15017-3061

Date Sampled: 08/12/15

Date Analyzed: 08/22/15

Job Number: ~~XXXXXX~~

Sample: ~~XXXXXX~~ Well B1 2H

FLASH LIBERATION OF SEPARATOR WATER		
	Separator	Stock Tank
Pressure, psig	540	0
Temperature, °F	78	70
Gas Water Ratio (1)	-----	4.06
Gas Specific Gravity (2)	-----	1.069

(1) - Scf of water saturated vapor per barrel of stock tank water

(2) - Air = 1.000

(3) - Separator volume / Stock tank volume

Analyst: T.G.

Piston No. : WF# 235

Base Conditions: 14.65 PSI & 60 °F

Certified: FESCO, Ltd. Alice, Texas

David Dannhaus 361-661-7015

FESCO, Ltd.
1100 Fesco Ave. - Alice, Texas 78332

For: SE Technologies, LLC
 Building D, Second Floor
 98 Vanadium Road
 Bridgeville, Pennsylvania 15017-3061

Sample: [REDACTED] Well B1 2H
 Gas Liberated from Separator Water
 From 540 psig & 78 °F to 0 psig & 70 °F

Date Sampled: 08/12/15

Job Number: [REDACTED]

CHROMATOGRAPH EXTENDED ANALYSIS - SUMMATION REPORT - GPA 2286

COMPONENT	MOL%	GPM
Hydrogen Sulfide*	< 0.001	
Nitrogen	1.821	
Carbon Dioxide	1.049	
Methane	56.602	
Ethane	16.424	4.367
Propane	8.000	2.191
Isobutane	1.516	0.493
n-Butane	4.274	1.340
2-2 Dimethylpropane	0.054	0.020
Isopentane	1.730	0.629
n-Pentane	2.405	0.867
Hexanes	2.953	1.209
Heptanes Plus	<u>3.172</u>	<u>1.397</u>
Totals	100.000	12.514

Computed Real Characteristics Of Heptanes Plus:

Specific Gravity ----- 3.549 (Air=1)
 Molecular Weight ----- 101.90
 Gross Heating Value ----- 5380 BTU/CF

Computed Real Characteristics Of Total Sample:

Specific Gravity ----- 1.069 (Air=1)
 Compressibility (Z) ----- 0.9914
 Molecular Weight ----- 30.68
 Gross Heating Value
 Dry Basis ----- 1741 BTU/CF
 Saturated Basis ----- 1712 BTU/CF

*Hydrogen Sulfide tested in laboratory by: Stained Tube Method (GPA 2377)

Results: <0.013 Gr/100 CF, <0.2 PPMV or <0.001 Mol %

Base Conditions: 14.650 PSI & 60 Deg F

Sampled By: (16) Gonzalez
 Analyst: MR
 Processor: OA
 Cylinder ID: WF# 10S

Certified: FESCO, Ltd. Alice, Texas

David Dannhaus

David Dannhaus 361-661-7015

**CHROMATOGRAPH EXTENDED ANALYSIS
TOTAL REPORT - GPA 2286**

COMPONENT	MOL %	GPM	WT %
Hydrogen Sulfide*	< 0.001		< 0.001
Nitrogen	1.821		1.663
Carbon Dioxide	1.049		1.505
Methane	56.602		29.592
Ethane	16.424	4.367	16.095
Propane	8.000	2.191	11.497
Isobutane	1.516	0.493	2.872
n-Butane	4.274	1.340	8.096
2,2 Dimethylpropane	0.054	0.020	0.127
Isopentane	1.730	0.629	4.069
n-Pentane	2.405	0.867	5.655
2,2 Dimethylbutane	0.075	0.031	0.211
Cyclopentane	0.000	0.000	0.000
2,3 Dimethylbutane	0.145	0.059	0.407
2 Methylpentane	0.807	0.333	2.268
3 Methylpentane	0.520	0.211	1.461
n-Hexane	1.405	0.575	3.947
Methylcyclopentane	0.134	0.046	0.368
Benzene	0.028	0.008	0.072
Cyclohexane	0.185	0.063	0.507
2-Methylhexane	0.337	0.156	1.102
3-Methylhexane	0.351	0.159	1.145
2,2,4 Trimethylpentane	0.000	0.000	0.000
Other C7's	0.326	0.141	1.054
n-Heptane	0.588	0.270	1.921
Methylcyclohexane	0.318	0.127	1.018
Toluene	0.053	0.018	0.158
Other C8's	0.486	0.225	1.747
n-Octane	0.147	0.075	0.548
Ethylbenzene	0.003	0.001	0.011
M & P Xylenes	0.026	0.010	0.090
O-Xylene	0.003	0.001	0.010
Other C9's	0.129	0.065	0.530
n-Nonane	0.024	0.013	0.099
Other C10's	0.025	0.015	0.116
n-Decane	0.004	0.003	0.020
Undecanes (11)	<u>0.004</u>	<u>0.002</u>	<u>0.019</u>
Totals	100.000	12.514	100.000

Computed Real Characteristics Of Total Sample:

Specific Gravity -----	1.069	(Air=1)
Compressibility (Z) -----	0.9914	
Molecular Weight -----	30.68	
Gross Heating Value		
Dry Basis -----	1741	BTU/CF
Saturated Basis -----	1712	BTU/CF

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Identification and Physical Characteristics

Identification

User Identification:	Moe Condensate
City:	Huntington
State:	West Virginia
Company:	Jay-Bee Oil & Gas, Inc.
Type of Tank:	Vertical Fixed Roof Tank
Description:	210 BBL Condensate Tanks - Emissions from a Single Tank

Tank Dimensions

Shell Height (ft):	15.00
Diameter (ft):	10.00
Liquid Height (ft) :	14.00
Avg. Liquid Height (ft):	10.00
Volume (gallons):	8,225.29
Turnovers:	51.06
Net Throughput(gal/yr):	419,983.21
Is Tank Heated (y/n):	N

Paint Characteristics

Shell Color/Shade:	Gray/Light
Shell Condition	Good
Roof Color/Shade:	Gray/Light
Roof Condition:	Good

Roof Characteristics

Type:	Cone
Height (ft)	0.25
Slope (ft/ft) (Cone Roof)	0.05

Breather Vent Settings

Vacuum Settings (psig):	-0.03
Pressure Settings (psig)	0.03

Meterological Data used in Emissions Calculations: Huntington, West Virginia (Avg Atmospheric Pressure = 14.33 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

Moe Condensate - Vertical Fixed Roof Tank
Huntington, West Virginia

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F)			Liquid Bulk Temp (deg F)	Vapor Pressure (psia)			Vapor Mol. Weight.	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
		Avg.	Min.	Max.		Avg.	Min.	Max.					
Gasoline (RVP 6)	All	61.42	53.10	69.74	57.09	3.0220	2.5373	3.5797	69.0000			92.00	Option 4: RVP=6, ASTM Slope=3

TANKS 4.0.9d

Emissions Report - Detail Format

Detail Calculations (AP-42)

Moe Condensate - Vertical Fixed Roof Tank Huntington, West Virginia

Annual Emission Calculations	
Standing Losses (lb):	451.6638
Vapor Space Volume (cu ft):	399.2441
Vapor Density (lb/cu ft):	0.0373
Vapor Space Expansion Factor:	0.1508
Vented Vapor Saturation Factor:	0.5512
Tank Vapor Space Volume:	
Vapor Space Volume (cu ft):	399.2441
Tank Diameter (ft):	10.0000
Vapor Space Outage (ft):	5.0833
Tank Shell Height (ft):	15.0000
Average Liquid Height (ft):	10.0000
Roof Outage (ft):	0.0833
Roof Outage (Cone Roof)	
Roof Outage (ft):	0.0833
Roof Height (ft):	0.2500
Roof Slope (ft/ft):	0.0500
Shell Radius (ft):	5.0000
Vapor Density	
Vapor Density (lb/cu ft):	0.0373
Vapor Molecular Weight (lb/lb-mole):	69.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	3.0220
Daily Avg. Liquid Surface Temp. (deg. R):	521.0866
Daily Average Ambient Temp. (deg. F):	54.8458
Ideal Gas Constant R (psia cu ft / (lb-mol-deg R)):	10.731
Liquid Bulk Temperature (deg. R):	516.7558
Tank Paint Solar Absorptance (Shell):	0.5400
Tank Paint Solar Absorptance (Roof):	0.5400
Daily Total Solar Insulation Factor (Btu/sqft day):	1,246.2101
Vapor Space Expansion Factor	
Vapor Space Expansion Factor:	0.1508
Daily Vapor Temperature Range (deg. R):	33.2847
Daily Vapor Pressure Range (psia):	1.0425
Breather Vent Press. Setting Range (psia):	0.0600
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	3.0220
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):	2.5373
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):	3.5797
Daily Avg. Liquid Surface Temp. (deg R):	521.0866
Daily Min. Liquid Surface Temp. (deg R):	512.7654
Daily Max. Liquid Surface Temp. (deg R):	529.4077
Daily Ambient Temp. Range (deg. R):	20.0583
Vented Vapor Saturation Factor	
Vented Vapor Saturation Factor:	0.5512
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	3.0220
Vapor Space Outage (ft):	5.0833

Working Losses (lb):	1,572.6233
Vapor Molecular Weight (lb/lb-mole):	69.0000
Vapor Pressure at Daily Average Liquid	
Surface Temperature (psia):	3.0220
Annual Net Throughput (gal/yr.):	419,983.2053
Annual Turnovers:	51.0600
Turnover Factor:	0.7542
Maximum Liquid Volume (gal):	8,225.2880
Maximum Liquid Height (ft):	14.0000
Tank Diameter (ft):	10.0000
Working Loss Product Factor:	1.0000
 Total Losses (lb):	 2,024.2871

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: Annual

Moe Condensate - Vertical Fixed Roof Tank
Huntington, West Virginia

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Gasoline (RVP 6)	1,572.62	451.66	2,024.29

Total Emissions for all Tanks:
 $2,024.29 \times 3 \text{ tanks} = 6,072.87 \text{ lb/yr} = 3.04 \text{ tpy}$

GRI-GLYCalc VERSION 4.0 - SUMMARY OF INPUT VALUES

Case Name: Moe Well Pad

File Name: C:\Rogers_Files\Misc\Jay-Bee Oil & Gas\Moe\Moe No Cond 8-17-16.ddf

Date: August 17, 2016

DESCRIPTION:

Description: 40 MMSCFD
Still Vent to Combustor
No Flash Tank

Annual Hours of Operation: 8760.0 hours/yr

WET GAS:

Temperature: 85.00 deg. F
Pressure: 500.00 psig
Wet Gas Water Content: Saturated

Component	Conc. (vol %)
Carbon Dioxide	0.1510
Nitrogen	0.3940
Methane	77.0800
Ethane	14.8320
Propane	4.9670
Isobutane	0.6160
n-Butane	1.2100
Isopentane	0.2660
n-Pentane	0.2620
n-Hexane	0.0580
Cyclohexane	0.0060
Other Hexanes	0.0930
Heptanes	0.0420
Benzene	0.0010
Toluene	0.0020
C8+ Heavies	0.0200

DRY GAS:

Flow Rate: 40.0 MMSCF/day
Water Content: 7.0 lbs. H2O/MMSCF

LEAN GLYCOL:

Glycol Type: TEG
Water Content: 1.5 wt% H₂O
Flow Rate: 7.5 gpm

PUMP:

Glycol Pump Type: Gas Injection
Gas Injection Pump Volume Ratio: 0.080 acfm gas/gpm glycol

REGENERATOR OVERHEADS CONTROL DEVICE:

Control Device: Combustion Device
Destruction Efficiency: 98.0 %
Excess Oxygen: 5.0 %
Ambient Air Temperature: 60.0 deg. F

GRI-GLYCalc VERSION 4.0 - AGGREGATE CALCULATIONS REPORT

Case Name: Moe Well Pad

File Name: C:\Rogers_Files\Misc\Jay-Bee Oil & Gas\Moe\Moe No Cond 8-17-16.ddf

Date: August 17, 2016

DESCRIPTION:

Description: 40 MMSCFD

Still Vent to Combustor

No Flash Tank

Annual Hours of Operation: 8760.0 hours/yr

EMISSIONS REPORTS:

CONTROLLED REGENERATOR EMISSIONS

Component	lbs/hr	lbs/day	tons/yr
Methane	0.9985	23.963	4.3732
Ethane	0.4697	11.272	2.0571
Propane	0.2965	7.116	1.2987
Isobutane	0.0599	1.437	0.2623
n-Butane	0.1412	3.389	0.6186
Isopentane	0.0407	0.978	0.1784
n-Pentane	0.0482	1.156	0.2109
n-Hexane	0.0197	0.474	0.0865
Cyclohexane	0.0076	0.181	0.0331
Other Hexanes	0.0251	0.603	0.1100
Heptanes	0.0304	0.730	0.1332
Benzene	0.0097	0.233	0.0426
Toluene	0.0336	0.807	0.1472
C8+ Heavies	0.0895	2.148	0.3919
Total Emissions	2.2703	54.487	9.9438

Total Hydrocarbon Emissions	2.2703	54.487	9.9438
Total VOC Emissions	0.8022	19.252	3.5134
Total HAP Emissions	0.0631	1.514	0.2763
Total BTEX Emissions	0.0433	1.040	0.1898

UNCONTROLLED REGENERATOR EMISSIONS

Component	lbs/hr	lbs/day	tons/yr
Methane	49.9229	1198.150	218.6624
Ethane	23.4833	563.598	102.8567

Propane	14.8254	355.809	64.9351
Isobutane	2.9941	71.858	13.1141
n-Butane	7.0614	169.473	30.9288
Isopentane	2.0370	48.887	8.9219
n-Pentane	2.4077	57.786	10.5459
n-Hexane	0.9870	23.687	4.3229
Cyclohexane	0.3780	9.073	1.6558
Other Hexanes	1.2554	30.131	5.4988
Heptanes	1.5206	36.493	6.6600
Benzene	0.4862	11.668	2.1293
Toluene	1.6806	40.334	7.3610
C8+ Heavies	4.4743	107.382	19.5973

Total Emissions	113.5137	2724.330	497.1901
-----------------	----------	----------	----------

Total Hydrocarbon Emissions	113.5137	2724.330	497.1901
Total VOC Emissions	40.1075	962.581	175.6711
Total HAP Emissions	3.1537	75.689	13.8132
Total BTEX Emissions	2.1667	52.002	9.4903

EQUIPMENT REPORTS:

COMBUSTION DEVICE

Ambient Temperature: 60.00 deg. F
 Excess Oxygen: 5.00 %
 Combustion Efficiency: 98.00 %
 Supplemental Fuel Requirement: 5.51e-001 MM BTU/hr

Component	Emitted	Destroyed
Methane	2.00%	98.00%
Ethane	2.00%	98.00%
Propane	2.00%	98.00%
Isobutane	2.00%	98.00%
n-Butane	2.00%	98.00%
Isopentane	2.00%	98.00%
n-Pentane	2.00%	98.00%
n-Hexane	2.00%	98.00%
Cyclohexane	2.00%	98.00%
Other Hexanes	2.00%	98.00%
Heptanes	2.00%	98.00%
Benzene	2.00%	98.00%
Toluene	2.00%	98.00%
C8+ Heavies	2.00%	98.00%

ABSORBER

NOTE: Because the Calculated Absorber Stages was below the minimum allowed, GRI-GLYCalc has set the number of Absorber Stages to 1.25 and has calculated a revised Dry Gas Dew Point.

Calculated Absorber Stages: 1.25
 Calculated Dry Gas Dew Point: 3.53 lbs. H₂O/MMSCF

Temperature: 85.0 deg. F
 Pressure: 500.0 psig
 Dry Gas Flow Rate: 40.0000 MMSCF/day
 Glycol Losses with Dry Gas: 0.1475 lb/hr
 Wet Gas Water Content: Saturated
 Calculated Wet Gas Water Content: 63.67 lbs. H₂O/MMSCF
 Calculated Lean Glycol Recirc. Ratio: 4.49 gal/lb H₂O

Component	Remaining in Dry Gas	Absorbed in Glycol
Water	5.54%	94.46%
Carbon Dioxide	99.83%	0.17%
Nitrogen	99.99%	0.01%
Methane	99.99%	0.01%
Ethane	99.96%	0.04%
Propane	99.93%	0.07%
Isobutane	99.89%	0.11%
n-Butane	99.85%	0.15%
Isopentane	99.84%	0.16%
n-Pentane	99.79%	0.21%
n-Hexane	99.63%	0.37%
Cyclohexane	98.38%	1.62%
Other Hexanes	99.72%	0.28%
Heptanes	99.26%	0.74%
Benzene	85.91%	14.09%
Toluene	79.32%	20.68%
C8+ Heavies	97.09%	2.91%

REGENERATOR

No Stripping Gas used in regenerator.

Component	Remaining in Glycol	Distilled Overhead
Water	38.66%	61.34%
Carbon Dioxide	0.00%	100.00%

Nitrogen	0.00%	100.00%
Methane	0.00%	100.00%
Ethane	0.00%	100.00%
Propane	0.00%	100.00%
Isobutane	0.00%	100.00%
n-Butane	0.00%	100.00%
Isopentane	0.33%	99.67%
n-Pentane	0.36%	99.64%
n-Hexane	0.41%	99.59%
Cyclohexane	3.05%	96.95%
Other Hexanes	0.77%	99.23%
Heptanes	0.45%	99.55%
Benzene	4.97%	95.03%
Toluene	7.88%	92.12%
C8+ Heavies	11.75%	88.25%

STREAM REPORTS:

WET GAS STREAM

Temperature: 85.00 deg. F
 Pressure: 514.70 psia
 Flow Rate: 1.67e+006 scfh

Component	Conc. (vol%)	Loading (lb/hr)
Water	1.34e-001	1.06e+002
Carbon Dioxide	1.51e-001	2.92e+002
Nitrogen	3.93e-001	4.85e+002
Methane	7.70e+001	5.43e+004
Ethane	1.48e+001	1.96e+004
Propane	4.96e+000	9.62e+003
Isobutane	6.15e-001	1.57e+003
n-Butane	1.21e+000	3.09e+003
Isopentane	2.66e-001	8.43e+002
n-Pentane	2.62e-001	8.31e+002
n-Hexane	5.79e-002	2.20e+002
Cyclohexane	5.99e-003	2.22e+001
Other Hexanes	9.29e-002	3.52e+002
Heptanes	4.19e-002	1.85e+002
Benzene	9.99e-004	3.43e+000
Toluene	2.00e-003	8.10e+000
C8+ Heavies	2.00e-002	1.50e+002

DRY GAS STREAM

Temperature: 85.00 deg. F
Pressure: 514.70 psia
Flow Rate: 1.67e+006 scfh

Component	Conc. (vol%)	Loading (lb/hr)
Water	7.44e-003	5.89e+000
Carbon Dioxide	1.51e-001	2.91e+002
Nitrogen	3.94e-001	4.85e+002
Methane	7.71e+001	5.43e+004
Ethane	1.48e+001	1.96e+004
Propane	4.96e+000	9.62e+003
Isobutane	6.15e-001	1.57e+003
n-Butane	1.21e+000	3.09e+003
Isopentane	2.66e-001	8.42e+002
n-Pentane	2.61e-001	8.29e+002
n-Hexane	5.78e-002	2.19e+002
Cyclohexane	5.90e-003	2.18e+001
Other Hexanes	9.28e-002	3.51e+002
Heptanes	4.17e-002	1.84e+002
Benzene	8.59e-004	2.95e+000
Toluene	1.59e-003	6.42e+000
C8+ Heavies	1.94e-002	1.45e+002

Total Components 100.00 9.16e+004

LEAN GLYCOL STREAM

Temperature: 85.00 deg. F
Flow Rate: 7.50e+000 gpm

Component	Conc. (wt%)	Loading (lb/hr)
TEG	9.85e+001	4.16e+003
Water	1.50e+000	6.33e+001
Carbon Dioxide	1.18e-012	4.97e-011
Nitrogen	1.35e-013	5.71e-012
Methane	4.78e-018	2.02e-016
Ethane	8.54e-008	3.61e-006
Propane	6.79e-009	2.87e-007
Isobutane	1.22e-009	5.17e-008
n-Butane	2.68e-009	1.13e-007
Isopentane	1.61e-004	6.81e-003

n-Pentane 2.07e-004 8.73e-003
 n-Hexane 9.63e-005 4.07e-003
 Cyclohexane 2.82e-004 1.19e-002
 Other Hexanes 2.32e-004 9.81e-003
 Heptanes 1.63e-004 6.89e-003

Benzene 6.03e-004 2.54e-002
 Toluene 3.40e-003 1.44e-001
 C8+ Heavies 1.41e-002 5.96e-001

 Total Components 100.00 4.22e+003

RICH GLYCOL AND PUMP GAS STREAM

 Temperature: 85.00 deg. F

Pressure: 514.70 psia

Flow Rate: 7.95e+000 gpm

NOTE: Stream has more than one phase.

Component	Conc. (wt%)	Loading (lb/hr)
-----------	----------------	--------------------

TEG	9.37e+001	4.16e+003
Water	3.69e+000	1.64e+002
Carbon Dioxide	1.65e-002	7.33e-001
Nitrogen	1.01e-002	4.49e-001
Methane	1.13e+000	4.99e+001

Ethane	5.29e-001	2.35e+001
Propane	3.34e-001	1.48e+001
Isobutane	6.75e-002	2.99e+000
n-Butane	1.59e-001	7.06e+000
Isopentane	4.61e-002	2.04e+000

n-Pentane	5.45e-002	2.42e+000
n-Hexane	2.23e-002	9.91e-001
Cyclohexane	8.79e-003	3.90e-001
Other Hexanes	2.85e-002	1.27e+000
Heptanes	3.44e-002	1.53e+000

Benzene	1.15e-002	5.12e-001
Toluene	4.11e-002	1.82e+000
C8+ Heavies	1.14e-001	5.07e+000

 Total Components 100.00 4.44e+003

REGENERATOR OVERHEADS STREAM

 Temperature: 212.00 deg. F

Pressure: 14.70 psia

Flow Rate: 3.86e+003 scfh

Component	Conc. (vol%)	Loading (lb/hr)
-----------	-----------------	--------------------

Water	5.48e+001	1.00e+002
Carbon Dioxide	1.64e-001	7.33e-001
Nitrogen	1.58e-001	4.49e-001
Methane	3.06e+001	4.99e+001
Ethane	7.68e+000	2.35e+001
Propane	3.30e+000	1.48e+001
Isobutane	5.06e-001	2.99e+000
n-Butane	1.19e+000	7.06e+000
Isopentane	2.78e-001	2.04e+000
n-Pentane	3.28e-001	2.41e+000
n-Hexane	1.13e-001	9.87e-001
Cyclohexane	4.42e-002	3.78e-001
Other Hexanes	1.43e-001	1.26e+000
Heptanes	1.49e-001	1.52e+000
Benzene	6.12e-002	4.86e-001
Toluene	1.79e-001	1.68e+000
C8+ Heavies	2.58e-001	4.47e+000
Total Components	100.00	2.15e+002

COMBUSTION DEVICE OFF GAS STREAM

Temperature: 1000.00 deg. F
 Pressure: 14.70 psia
 Flow Rate: 3.46e+001 scfh

Component	Conc. (vol%)	Loading (lb/hr)
-----------	-----------------	--------------------

Methane	6.82e+001	9.98e-001
Ethane	1.71e+001	4.70e-001
Propane	7.37e+000	2.97e-001
Isobutane	1.13e+000	5.99e-002
n-Butane	2.66e+000	1.41e-001
Isopentane	6.19e-001	4.07e-002
n-Pentane	7.32e-001	4.82e-002
n-Hexane	2.51e-001	1.97e-002
Cyclohexane	9.85e-002	7.56e-003
Other Hexanes	3.19e-001	2.51e-002
Heptanes	3.33e-001	3.04e-002
Benzene	1.36e-001	9.72e-003
Toluene	4.00e-001	3.36e-002
C8+ Heavies	5.76e-001	8.95e-002
Total Components	100.00	2.27e+000

ATTACHMENT T

Facility-wide Emission Summary Sheet(s)

ATTACHMENT T – FACILITY-WIDE CONTROLLED EMISSIONS SUMMARY SHEET

List all sources of emissions in this table. Use extra pages if necessary.

Emission Point ID#	NO _x		CO		VOC		SO ₂		PM ₁₀		PM _{2.5}		GHG (CO ₂ e)	
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy
1E	0.15	0.66	0.13	0.55	0.01	0.04	<0.01	<0.01	0.01	0.05	0.01	0.05	181.1	793
2E	0.15	0.66	0.13	0.55	0.01	0.04	<0.01	<0.01	0.01	0.05	0.01	0.05	181.1	793
3E	0.15	0.66	0.13	0.55	0.01	0.04	<0.01	<0.01	0.01	0.05	0.01	0.05	181.1	793
4E	0.05	0.22	0.04	0.18	<0.01	0.01	<0.01	<0.01	<0.01	0.02	<0.01	0.02	60.4	264
5E					2.96	0.91								
6E					0.08	0.04								
7E	0.19	0.81	0.37	1.62	0.04	0.18	<0.01	<0.01	0.01	0.06	0.01	0.06	89.7	393
8E	<0.01	0.01	<0.01	0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	1.6	7
9E	0.29	1.25	1.10	4.81	1.84	0.43	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	446.7	1956
10E	0.05	0.22	0.04	0.18	<0.01	0.01	<0.01	<0.01	<0.01	0.02	<0.01	0.02	60.4	264.5
11E	0.27	1.19	1.03	4.5	0.81	3.54	<0.01	<0.01	0.04	0.16	0.04	0.16	417.4	1828.1
TOTAL	1.29	5.67	2.96	12.96	5.76	5.22	<0.01	<0.01	0.11	0.47	0.11	0.47	1619.5	7093.5

Annual emissions shall be based on 8,760 hours per year of operation for all emission units except emergency generators.

According to 45CSR14 Section 2.43.e, fugitive emissions are not included in the major source determination because it is not listed as one of the source categories in Table 1. Therefore, fugitive emissions shall not be included in the PTE above.

ATTACHMENT T – FACILITY-WIDE HAP CONTROLLED EMISSIONS SUMMARY SHEET

List all sources of emissions in this table. Use extra pages if necessary.

Emission Point ID#	Formaldehyde		Benzene		Toluene		Ethylbenzene		Xylenes		Hexane		Total HAPs	
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy
1E											<0.01	0.01	<0.01	0.01
2E											<0.01	0.01	<0.01	0.01
3E											<0.01	0.01	<0.01	0.01
4E											<0.01	<0.01	<0.01	<0.01
5E											0.16	0.05	0.16	0.05
6E											0.01	<0.01	0.01	<0.01
7E	0.015	0.065	<0.01	<0.01									0.02	0.10
8E														
9E	<0.01	<0.01									<0.01	0.01	<0.01	0.02
10E	<0.01	<0.01									<0.01	<0.01	<0.01	<0.01
11E	<0.01	<0.01	0.01	0.04	0.03	0.15					0.02	0.09	0.06	0.28
TOTAL	0.02	0.07	0.01	0.05	0.03	0.15	<0.01	<0.01	<0.01	<0.01	0.20	0.20	0.27	0.50

Annual emissions shall be based on 8,760 hours per year of operation for all emission units except emergency generators.

According to 45CSR14 Section 2.43.e, fugitive emissions are not included in the major source determination because it is not listed as one of the source categories in Table 1. Therefore, fugitive emissions shall not be included in the PTE above.

ATTACHMENT U

Class I Legal Advertisement

**Affidavit Notice Will Be Submitted
Upon Receipt**

AIR QUALITY PERMIT NOTICE
Notice of Application

Notice is given that Jay-Bee Oil & Gas, Inc. has applied to the West Virginia Department of Environmental Protection, Division of Air Quality, for a G70-C General Permit Registration for its Moe Well Pad Production Facility located off Klondike Acres Rd near Middlebourne in Tyler County, West Virginia. The latitude and longitude coordinates are: 39.46791, -80.88719.

The applicant estimates the potential to discharge the following Regulated Air Pollutants will be:

5.67 tons of Nitrogen Oxides per year
12.96 tons of Carbon Monoxide per year
6.46 tons of Particulate Matter per year
6.98 tons of Volatile Organic Compounds per year
0.02 tons of Sulfur Dioxide per year
0.07 tons of Formaldehyde per year
0.05 tons of Benzene per year
0.15 tons of Toluene per year
0.20 tons of Hexane per year
0.52 tons of Total Hazardous Air Pollutants per year
7,132 tons of Greenhouse Gases per year

Startup of operation is planned to begin on or about the 31st day of October, 2016. Written comments will be received by the West Virginia Department of Environmental Protection, Division of Air Quality, 601 57th Street, SE, Charleston, WV 25304, for at least 30 calendar days from the date of publication of this notice.

Any questions regarding this permit application should be directed to the DAQ at (304) 926-0499, extension 1250, during normal business hours.

Dated this the **(Day)** day of **(Month)**, **(Year)**.

By: Mr. Shane Dowell
Office Manager
Jay-Bee Oil & Gas, Inc.
3570 Shields Ave.
Cairo, WV 26337