

Division of Air Quality  
601 57<sup>th</sup> Street SE  
Charleston, WV 25304  
Phone (304) 926-0475  
Fax (304) 926-0479



Earl Ray Tomblin, Governor  
Randy C. Huffman, Cabinet Secretary  
www.dep.wv.gov

west virginia department of environmental protection

## G70-C GENERAL PERMIT ENGINEERING EVALUATION

PREVENTION AND CONTROL OF AIR POLLUTION IN REGARD TO THE CONSTRUCTION, MODIFICATION, RELOCATION, ADMINISTRATIVE UPDATE AND OPERATION OF NATURAL GAS PRODUCTION FACILITIES LOCATED AT THE WELL SITE

APPLICATION NO.: G70-C009C

FACILITY ID: 103-00080

- CONSTRUCTION  
 MODIFICATION  
 RELOCATION

- CLASS I ADMINISTRATIVE UPDATE  
 CLASS II ADMINISTRATIVE UPDATE

### BACKGROUND INFORMATION

Name of Applicant (as registered with the WV Secretary of State's Office): **Ascent Resources – Marcellus, LLC**

Federal Employer ID No. (FEIN): 46-5580354

Applicant's Mailing Address: PO Box 13678

City: Oklahoma City

State: OK

ZIP Code: 73113

Facility Name: Long 408/409

Operating Site Physical Address: 1220 Long Ridge Road  
If none available, list road, city or town and zip of facility.

City: Wileyville

Zip Code: 26155

County: Wetzel

Latitude & Longitude Coordinates (NAD83, Decimal Degrees to 5 digits):

Latitude: 39.58411

Longitude: -80.67497

SIC Code: 1311  
NAICS Code: 211111

Date Application Received:  
July 22, 2016

Fee Amount: \$1,500.00

Date Fee Received: July 25, 2016

Applicant Ad Date: July 27, 2016

Newspaper: The Wetzel Chronicle

Date Application Complete: August 29, 2016

Due Date of Final Action: October 14, 2016

Engineer Assigned: Roy F. Kees, P.E.

Description of Permitting Action: Ascent is providing updated engine information, including date of manufacture and manufacturer's guaranteed emissions per their consent order.

## **PROCESS DESCRIPTION**

The following process description was taken from Registration Application G70-C009C:

This application is being filed for Ascent Resources – Marcellus, LLC (Ascent) and addresses administrative updates associated with the Long 408/409 Well Pad (Facility). The Facility currently operates under G70-A009B, issued March 30, 2016. With this Application, Ascent is converting the application to the G70C permit and updating the site specific information for the (1) Cummins G8.3 Reciprocating Compressor Engine, rated at 118 bhp, (30S), including date of manufacture and emission factors. All other operations at the Facility remain unchanged from the previous application.

The raw natural gas flows from the eleven (11) wellheads located on the Long 408/409 site. The raw gas is first routed through the 1.0 MMBtu/hr gas production units (GPUs) (1S to 11S) where the first stage of fluid separation occurs. The GPUs separate the well stream into a high pressure natural gas stream, a condensate liquid stream, and a produced water liquid stream. In the second stage of separation, the liquid streams are routed through one (1) 1.0 MMBtu/hr flash separator (29S) where condensate and produced water are removed. The flash from the low pressure separator is compressed by one (1) natural gas-fired compressor engine (30S) and is routed to the sales gas pipeline. Produced water from the separators is sent to six (6) 210-bbl produced water storage tanks (20S to 25S). The condensate from the separators is sent to the eight (8) 210-bbl condensate storage tanks (12S to 19S).

The natural gas stream will exit the facility via pipeline. Condensate and produced water is transported offsite via truck. Flashing emissions and working and breathing losses from the six (6) 210-bbl produced water storage tanks, eight (8) 210-bbl condensate storage tanks, and truck loading emissions (27S, 28S) will be routed to the onsite enclosed combustor (26S).

## SITE INSPECTION

Site Inspection Date: January 16, 2014

Site Inspection Conducted By: Douglas Hammell

Results of Site Inspection: Closest residences are both ~0.4mi away, either the one West or the one to the South. Drilling ops underway while I was there, No perm.equip yet on site.

Did Applicant meet Siting Requirements? Yes

If applicable, was siting criteria waiver submitted? N/A

Directions to Facility: Route 7 East out of New Martinsville towards Morgantown, Bear right on Route 20 towards Pine Grove, left onto North Fork C/R 15/17, left onto Baker Run C/R 17, left onto McKimmie Ridge C/R 17/1, left on C/R 40, right on lease road.

Overhead Google Earth Image of Facility:



## ESTIMATE OF EMISSIONS BY REVIEWING ENGINEER

The following table indicates which methodology was used in the emissions determination:

Emission Unit ID#	Process Equipment	Calculation Methodology (e.g. ProMax, GlyCalc, mfg. data, AP-42, etc.)
1S-11S	Eleven (11) GPU Burners	AP-42
12S-19S	Eight (8) Condensate Tanks	ProMax & Tanks
20S-25S	Six (6) Produced Water Tanks	ProMax & Tanks
26S	Enclosed Vapor Combustor	AP-42
27S	Condensate Truck Loading	AP-42
28S	Produced Water Truck Loading	AP-42
29S	Flash Separator Heater	AP-42
30S	Compressor Engine	Manufacturer Data / AP-42
31S	Fugitive Emissions	AP-42

The total facility PTE for the facility (including fugitive emissions) is shown in the following table:

Pollutant	Facility Wide PTE (tons/year)	PTE Change for Modification (tons/year)
Nitrogen Oxides	10.83	-6.27
Carbon Monoxide	35.61	+14.56
Volatile Organic Compounds	19.82	-6.17
Particulate Matter	0.44	-0.59
Particulate Matter-10/2.5	0.44	-0.59
Sulfur Dioxide	0.27	+0.20
Formaldehyde	0.09	0.00
Total HAPs	0.55	+0.01
Carbon Dioxide Equivalent	18,871	+3,960

Maximum detailed controlled point source emissions were calculated by the applicant and checked for accuracy by the writer and are summarized in the table on the next page.

APPLICANT: Ascent Resources – Marcellus, LLC FACILITY NAME: Long 408/409 G70-C009C															
Emission Point ID#	NO <sub>x</sub>		CO		VOC		SO <sub>2</sub>		PM <sub>10</sub>		PM <sub>2.5</sub>		GHG (CO <sub>2</sub> e)		
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	
1S-11S	0.88	3.85	0.77	3.19	0.11	0.22	0.11	0.11	0.11	0.11	0.33	0.11	0.33	--	5643
12S-19S	--	--	--	--	0.99	4.32	--	--	--	--	--	--	--	--	--
20S-25S	--	--	--	--	0.03	0.11	--	--	--	--	--	--	--	--	--
26S	1.25	5.49	6.82	29.85	TANKS	TANKS	0.03	0.14	0.00	0.00	0.00	0.00	0.00	--	10823
27S	--	--	--	--	16.26	3.12	--	--	--	--	--	--	--	--	--
28S	--	--	--	--	0.16	0.11	--	--	--	--	--	--	--	--	--
29S	0.08	0.35	0.07	0.29	0.01	0.02	0.00	0.00	0.01	0.03	0.01	0.01	0.03	--	513
30S	0.26	1.14	0.52	2.28	0.18	0.80	0.01	0.01	0.02	0.08	0.02	0.02	0.08	--	486
TOTAL	2.47	10.83	8.18	35.61	20.01	19.82	0.16	0.27	0.14	0.44	0.14	0.44	0.44	--	18871

APPLICANT: Ascent Resources – Marcellus, LLC FACILITY NAME: Long 408/409 G70-C009C														
Emission Point ID#	Formaldehyde		Benzene		Toluene		Ethylbenzene		Xylenes		Hexane		Total HAPs	
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy
1S-11S	--	--	--	--	--	--	--	--	--	--	--	--	0.02	0.11
12S-19S	--	--	--	--	--	--	--	--	--	--	--	--	0.03	0.11
20S-25S	--	--	--	--	--	--	--	--	--	--	--	--	0.00	0.01
26S	--	--	--	--	--	--	--	--	--	--	--	--	TANKS	TANKS
27S	--	--	--	--	--	--	--	--	--	--	--	--	0.42	0.08
28S	--	--	--	--	--	--	--	--	--	--	--	--	0.00	0.00
29S	--	--	--	--	--	--	--	--	--	--	--	--	0.00	0.01
30S	0.02	0.09	--	--	--	--	--	--	--	--	--	--	0.03	0.13
TOTAL	0.02	0.09	0.17	0.12	0.05	0.03	0.00	0.00	0.00	0.00	0.27	0.26	0.53	0.55

## REGULATORY APPLICABILITY

### 45CSR2 (Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers)

The purpose of 45CSR2 (Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers) is to establish emission limitations for smoke and particulate matter which are discharged from fuel burning units.

45CSR2 states that any fuel burning unit that has a heat input under ten (10) MMBTU/hr is exempt from Sections 4 (weight emission standard), 5 (control of fugitive particulate matter), 6 (registration), 8 (testing, monitoring, recordkeeping, reporting) and 9 (startups, shutdowns, malfunctions). However, failure to attain acceptable air quality in parts of some urban areas may require the mandatory control of these sources at a later date. If the individual heat input of all of the proposed fuel burning units are below 10 MMBTU/hr, these units are exempt from the aforementioned sections of 45CSR2. However, the registrant would be subject to the opacity requirements in 45CSR2, which is 10% opacity based on a six minute block average. Fuel burning units greater than 10 MMBTU/hr are ineligible for registration under General Permit G70-C

Emission Unit ID#	Emission Unit Description	Maximum Design Heat Input (MDHI) (MMBTU/hr)
1S-11S	(11) GPU Burners	1.00 each
29S	Flash Separator Heater0	1.0

### 45CSR6 (To Prevent and Control Air Pollution from the Combustion of Refuse)

45CSR6 prohibits open burning, establishes emission limitations for particulate matter, and establishes opacity requirements. Sources subject to 45CSR6 include completion combustion devices, enclosed combustion devices, and flares.

The facility-wide requirements of the general permit include the open burning limitations §§45-6-3.1 and 3.2.

All completion combustion devices, enclosed combustion devices, and flares are subject to the particulate matter weight emission standard set forth in §45-6-4.1; the opacity requirements in §§45-6-4-3 and 4-4; the visible emission standard in §45-6-4.5; the odor standard in §45-6-4.6; and, the testing standard in §§45-6-7.1 and 7.2.

Enclosed combustion control devices and flares that are used to comply with emission standards of NSPS, Subpart OOOO are subject to design, operational, performance, recordkeeping and reporting requirements of the NSPS regulation that meet or exceed the requirements of 45CSR6.

Emission Unit ID#	Maximum Design Heat Input (MDHI) (MMBTU/hr)	Subject to Weight Emission Standard?	Control Efficiency Claimed by Registrant	Provide Justification how 45CSR6 is met.
26S	18.42	X Yes <input type="checkbox"/> No	98	Assuming 20,000 BTU/lb, the allowable PM emissions are 2.50 lb/hr. Using AP-42, the PM emissions were calculated to be <0.01 lb/hr.

**45CSR10 (To Prevent and Control Air Pollution from the Emission of Sulfur Oxides)**

45CSR10 establishes emission limitations for SO<sub>2</sub> emissions which are discharged from stacks of fuel burning units. A “fuel burning unit” means and includes any furnace, boiler apparatus, device, mechanism, stack or structure used in the process of burning fuel or other combustible material for the primary purpose of producing heat or power by indirect heat transfer. Sources that meet the definition of “Fuel Burning Units” per 45CSR10-2.8 include GPUs, in-line heaters, heater treaters, and glycol dehydration unit reboilers.

Fuel burning units less than 10 MMBtu/hr are exempt. The sulfur dioxide emission standard set forth in 45CSR10 is generally less stringent than the potential emissions from a fuel burning unit for natural gas. The SO<sub>2</sub> emissions from a fuel burning unit will be listed in the G70-C permit registration at the discretion of the permit engineer on a case-by-case basis. Issues such as non-attainment designation, fuel use, and amount of sulfur dioxide emissions will be factors used in this determination. Fuel burning units greater than 10 MMBTU/hr are ineligible for registration under General Permit G70-C

Fuel burning units burning natural gas are exempt from Section 8 (Monitoring, Recording and Reporting) as well as interpretive rule 10A. The G70-C eligibility requirements exclude from eligibility any fuel burning unit that does not use natural gas as the fuel; therefore, there are no permit conditions for 45CSR10.

<b>Emission Unit ID#</b>	<b>Emission Unit Description</b>	<b>Maximum Design Heat Input (MDHI) (MMBTU/hr)</b>
1S-11S	(11) GPU Burners	1.00 each
29S	Flash Separator Heater0	1.0

**45CSR13 (Permits for Construction, Modification, Relocation and Operation of Stationary Sources of Air Pollutants, Notification Requirements, Administrative Updates, Temporary Permits, General Permits, and Procedures for Evaluation)**

45CSR13 applies to this source due to the fact that the applicant is defined as a “stationary source” under 45CSR13 Section 2.24.b. *Stationary source* means, for the purpose of this rule, any building, structure, facility, installation, or emission unit or combination thereof, excluding any emission unit which meets or falls below the criteria delineated in Table 45-13B which: (a) is subject to any substantive requirement of an emission control rule promulgated by the Secretary; (b) discharges or has the potential to discharge more than six (6) pounds per hour and ten (10) tons per year, or has the potential to discharge more than 144 pounds per calendar day, of any regulated air pollutant; (c) discharges or has the potential to discharge more than two (2) pounds per hour or five (5) tons per year of hazardous air pollutants considered on an aggregated basis; (d) discharges or has the potential to discharge any air pollutant(s) listed in Table 45-13A in the amounts shown in Table 45-13A or greater; or, (e) an owner or operator voluntarily chooses to be subject to a construction or modification permit pursuant to this rule, even though not otherwise required to do so. 45CSR13 has an original effective date of June 1, 1974.

The applicant meets the definition of a stationary source because (check all that apply):

- Subject to a substantive requirement of an emission control rule promulgated by the Secretary.
- Discharges or has the potential to discharge more than six (6) pounds per hour and ten (10) tons per year, or has the potential to discharge more than 144 pounds per calendar day, of any regulated air pollutant.
- Discharges or has the potential to discharge more than two (2) pounds per hour or five (5) tons per year of hazardous air pollutants considered on an aggregated basis.
- Discharges or has the potential to discharge any air pollutant(s) listed in Table 45-13A in the amounts shown in Table 45-13A or greater.
- Voluntarily chooses to be subject to a construction or modification permit pursuant to this rule, even though not otherwise required to do so.

General Permit G70-C Registration satisfies the construction, modification, relocation and operating permit requirements of 45CSR13. General Permit G70-C sets forth reasonable conditions that enable eligible registrants to establish enforceable permit limits.

Section 5 of 45CSR13 provides the permit application and reporting requirements for construction of and modifications to stationary sources. No person shall cause, suffer, allow or permit the construction, modification, relocation and operation of any stationary source to be commenced without notifying the Secretary of such intent and obtaining a permit to construct, modify, relocate and operate the stationary source as required in the rule or any other applicable rule promulgated by the Secretary.

If applicable, the applicant meets the following (check all that apply):

- Relocation
- Modification
- Class I Administrative Update (45CSR13 Section 4.2.a)
- Class II Administrative Update (45CSR13 Section 4.2.b)

**45CSR16 (Standards of Performance for New Stationary Sources Pursuant to 40 CFR Part 60)**

45CSR16 applies to all registrants that are subject to any of the NSPS requirements described in more detail in the Federal Regulations section. Applicable requirements of NSPS, Subparts IIII, JJJJ and OOOO are included in General Permit G70-C.

The applicant is subject to:

- 40CFR60 Subpart IIII
- 40CFR60 Subpart JJJJ
- 40CFR60 Subpart OOOO

**45CSR22 (Air Quality Management Fee Program)**

45CSR22 is the program to collect fees for certificates to operate and for permits to construct or modify sources of air pollution. 45CSR22 applies to all registrants. The general permit fee of \$500 is defined in 45CSR13. In addition to the application fee, all applicants subject to NSPS requirements or NESHAP requirements shall pay additional fees of \$1,000 and \$2,500, respectively.

Registrants are also required to obtain and have in effect a valid certificate to operate in accordance with 45CSR22 §4.1. The fee group for General Permit G70-C is 9M (all other sources) with an annual operating fee of \$200.

**40CFR60 Subpart IIII (Standards of Performance for Stationary Compression Ignition Internal Combustion Engines)**

Subpart IIII sets forth non-methane hydrocarbon (NMHC), hydrocarbon (HC), nitrogen oxides (NOx), carbon monoxide (CO), and particulate matter (PM) emission limits, fuel requirements, installation requirements, and monitoring requirements based on the year of installation of the subject internal combustion engine. The provisions for stationary compression ignition (CI) internal combustion engines for owners or operators of this Subpart have been included in General Permit G70-C, Section 13. The following CI engines are subject to this section:

Emission Unit ID#	Engine Description (Make, Model)	Engine Size (HP)	Date of Manufacture	Provide Justification how 40CFR60 Subpart IIII is met.
N/A				<input type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine

**40CFR60 Subpart JJJJ (Standards of Performance for Stationary Spark Ignition Internal Combustion Engines)**

Subpart JJJJ sets forth nitrogen oxides (NOx), carbon monoxide (CO), and volatile organic compound (VOC) emission limits, fuel requirements, installation requirements, and monitoring requirements based on the year of installation of the subject internal combustion engine. The provisions for stationary spark ignition (SI) internal combustion engines for owners or operators of this Subpart have been included in General Permit G70-C, Section 13.

Emission Unit ID#	Engine Description (Make, Model)	Engine Size (HP)	Date of Manufacture	Provide Justification how 40CFR60 Subpart JJJJ is met.
30S	Cummings G8.3L	118	5/1/14	<input checked="" type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine

**40CFR60, Subpart OOOO (Standards of Performance for Crude Oil and Natural Gas Production, Transmission and Distribution)**

EPA published its New Source Performance Standards (NSPS) and air toxics rules for the oil and gas sector on August 16, 2012. EPA published final amendments to the Subpart on September 23, 2013.

40CFR60 Subpart OOOO establishes emission standards and compliance schedules for the control of volatile organic compounds (VOC) and sulfur dioxide (SO<sub>2</sub>) emissions from affected facilities that commence construction, modification or reconstruction after August 23, 2011. The affected sources which commence construction, modification or reconstruction after August 23, 2011 are subject to the applicable provisions of this Subpart as described below:

**Gas well affected facilities are included in General Permit G70-C in Section 5.0.**

Are there any applicable gas well affected facilities?  Yes  No

If Yes, list.

API number(s) for each Gas Well at this facility	Date the Gas Well was completed
047-103-02887	1/15/15
047-103-02888	1/4/15
047-103-02889	1/12/15
047-103-02890	12/30/14
047-103-02891	12/30/14
047-103-02878	1/1/15
047-103-02879	1/6/15
047-103-02880	1/10/15
047-103-02881	1/11/15
047-103-02882	1/13/15
047-103-02883	1/19/15

**Centrifugal compressor affected facilities are included in General Permit G70-C, Section 11.0.**

Are there any applicable centrifugal compressor affected facilities not located at the well site?

Yes       No

If Yes, list.

<b>Engine Description (Make, Model)</b>
N/A

Each centrifugal compressor affected facility, which is a single centrifugal compressor using wet seals that is located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment. A centrifugal compressor located at a well site, or an adjacent well site and servicing more than one well site, is not an affected facility under this Subpart.

**Reciprocating compressor affected facilities are included in General Permit G70-C, Section 12.0.**

Are there any applicable reciprocating compressor affected facilities not located at the well site?

Yes       No

If Yes, list.

<b>Engine Description (Make, Model)</b>
N/A

Each reciprocating compressor affected facility, which is a single reciprocating compressor located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment. A reciprocating compressor located at a well site, or an adjacent well site and servicing more than one well site, is not an affected facility under this subpart.

**Pneumatic controllers affected facilities are included in General Permit G70-C, Section 10.0.**

Are there any applicable pneumatic controller affected facilities?  Yes       No

For the natural gas production segment (between the wellhead and the point of custody transfer to the natural gas transmission and storage segment and not including natural gas processing plants), each pneumatic controller affected facility, which is a single continuous bleed natural gas-driven pneumatic controller operating at a natural gas bleed rate greater than 6 scfh.

**Requirements for storage vessel affected facilities are included in General Permit G70-C, Section 7.0.**

**Determination of storage vessel affected facility status is included in Section 6.0 of General Permit G70-C.**

Are there any applicable storage vessel affected facilities?  Yes       No

If No, list any emission reduction devices and control efficiencies used to avoid 40CFR60 Subpart OOOO.

26S, 18.42 MMBtu/hr Vapor Combustor, 98% Control

If Yes, list.

Emission Unit ID#	Storage Vessel Description	SV Size (gal)	Provide Justification how 40CFR60 Subpart OOOO is met.
N/A			

Each storage vessel affected facility, which is a single storage vessel located in the oil and natural gas production segment, natural gas processing segment or natural gas transmission and storage segment, and has the potential for VOC emissions equal to or greater than 6 tpy as determined according to this section by October 15, 2013 for Group 1 storage vessels and by April 15, 2014, or 30 days after startup (whichever is later) for Group 2 storage vessels. A storage vessel affected facility that subsequently has its potential for VOC emissions decrease to less than 6 tpy shall remain an affected facility under this subpart.

**40CFR63 Subpart HH (National Emission Standards for Hazardous Air Pollutants From Oil and Natural Gas Production Facilities)**

This Subpart applies to owners and operators of each triethylene glycol (TEG) dehydration unit that are located at oil and natural gas production facilities. Only area source requirements are included in General Permit G70-C, as defined in §63.761.

For area source applicability, the affected source includes each triethylene glycol (TEG) dehydration unit located at a facility that meets the criteria specified in §63.760(a).

Glycol dehydration unit(s) are included in General Permit G70-C, Section 15.0.

Are there any TEG dehydration unit(s) at this facility?  Yes  No

Are the TEG dehydration unit(s) located within an Urbanized Area (UA) or Urban Cluster (UC)?  
 Yes  No

Are the glycol dehydration unit(s) exempt from 40CFR63 Section 764(d)?  Yes  No

If Yes, answer the following questions:

The actual annual average flowrate of natural gas to the glycol dehydration unit(s) is less than 85 thousand standard cubic meters per day, as determined by the procedures specified in §63.772(b)(1) of this Subpart.  Yes  No

The actual average emissions of benzene from the glycol dehydration unit process vent(s) to the atmosphere are less than 0.90 megagram per year (1 ton per year), as determined by the procedures specified in §63.772(b)(2) of this Subpart.  Yes  No

**40CFR63 Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines)**

Subpart ZZZZ establishes national emission limitations and operating limitations for hazardous air pollutants (HAP) emitted from stationary reciprocating internal combustion engines (RICE) located at major and area sources of HAP emissions. This Subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations and operating limitations. This section reflects EPA's final amendments to 40 CFR part 63, Subpart ZZZZ that were issued on January 15, 2013 and published in the Federal Register on January 30, 2013.

WVDEP DAQ has delegation of the area source air toxics provisions of this Subpart requiring Generally Achievable Control Technology (GACT). The provisions of this Subpart have been included in this general permit under Section 13.0.

<b>Emission Unit ID#</b>	<b>Engine Description (Make, Model)</b>	<b>Engine Size (HP)</b>	<b>Date of Manufacture</b>	<b>New or Existing under 40CFR63 Subpart ZZZZ?</b>	<b>Provide Justification how 40CFR63 Subpart ZZZZ is met.</b>
30S	Cummings G8.3L	118	5/1/14	New	JJJJ

Are there any engines that fall in the window of being new under 40CFR60 Subpart ZZZZ but manufactured before the applicability date in 40CFR60 Subpart JJJJ?  Yes  No

If so, list the engines: N/A

**SOURCE AGGREGATION DETERMINATION**

“Building, structure, facility, or installation” is defined as all the pollutant emitting activities which belong to the same industrial grouping, are located on one or more contiguous and adjacent properties, and are under the control of the same person.

Are there surrounding wells or compressor stations under “common control” of the applicant?  
 Yes  No

Are the properties in question located on “contiguous or adjacent” properties?  
 Yes  No

Are there surrounding facilities that share the same two (2) digit SIC code?  
 Yes  No

**Final Source Aggregation Decision.**

- Source not aggregated with any other source.
- Source aggregated with another source. List Company/Facility Name:

## RECOMMENDATION TO DIRECTOR

The information provided in the permit application, including all supplemental information received, indicates the applicant meets all the requirements of applicable regulations and the applicant has shown they meet the eligibility requirements of General Permit G70-C. Therefore, impact on the surrounding area should be minimized and it is recommended that the facility should be granted registration under General Permit G70-C.

Permit Engineer Signature: 

Name and Title: Roy F. Kees, P.E. – Engineer, NSR Permitting

Date: September 30, 2016